



# Gallery of USAF Weapons

2005 USAF Almanac

By Susan H.H. Young

Note: Inventory numbers are total active inventory figures as of Sept. 30, 2004.



**B-1B Lancer** (SSgt. Suzanne M. Jenkins)

## Bombers

### B-1 Lancer

**Brief:** A long-range, air refuelable multirole bomber capable of flying missions over intercontinental range, then penetrating enemy defenses with a heavy load of ordnance.

**Function:** Long-range conventional bomber.

**Operator:** ACC, AFMC.

**First Flight:** Dec. 23, 1974 (B-1A); Oct. 18, 1984 (B-1B).

**Delivered:** June 1985-May 1988.

**IOC:** Oct. 1, 1986, Dyess AFB, Tex. (B-1B).

**Production:** 104.

**Inventory:** 67.

**Unit Location:** Dyess AFB, Tex., Ellsworth AFB, S.D., Edwards AFB, Calif.

**Contractor:** Boeing; AIL Systems; General Electric.

**Power Plant:** four General Electric F101-GE-102 turbofans, each 30,780 lb thrust.

**Accommodation:** four, pilot, copilot, and two systems officers (offensive and defensive), on zero/zero ejection seats.

**Dimensions:** span spread 137 ft, swept aft 79 ft, length 146 ft, height 34 ft.

**Weights:** empty equipped 192,000 lb, max operating weight 477,000 lb.

**Ceiling:** more than 30,000 ft.

**Performance:** max speed at low level high subsonic; 900+ mph (Mach 1.2 at S/L); range intercontinental.

**Armament:** three internal weapons bays capable of accommodating a wide range of weapons incl up to 84 Mk 82 (500-lb) bombs or Mk 62 naval mines; up to 30 CBU-87/103 Combined Effects Munitions (CEMs), 15 CBU-89/104 Gator munitions, and 15 CBU-97/105 Sensor Fuzed Weapons (SFWs) (CBU-103/104/105s are fitted with Wind-Corrected Munitions Dispenser (WCMD) kits), 12 AGM-154 Joint Standoff Weapons (JSOWs), up to 24 GBU-31 (2,000-lb) Joint Direct Attack Munitions (JDAMs), and AGM-158 Joint Air-to-Surface Standoff Missile (JASSM). GBU-38 (500-lb) JDAM integration under way.

#### COMMENTARY

Of blended wing/body configuration, the B-1's variable-geometry design and turbofan engines combine to provide greater range and high speed at low level,

with enhanced survivability. Unswept wing settings provide for maximum range during high-altitude cruise. The fully swept position is used in supersonic flight and for high subsonic, low-altitude penetration.

The bomber's offensive avionics include synthetic aperture radar (SAR), ground moving target indicator (GMTI), ground moving target track (GMTT), and terrain-following radar (TFR), an extremely accurate Global Positioning System/inertial navigation system (GPS/INS), computer-driven avionics, and a strategic Doppler radar, enabling aircrews to navigate, update target coordinates in flight, and precision bomb.

The current defensive avionics package, built around the ALQ-161 electronic countermeasures (ECM) system, is supplemented by the ALE-50 towed decoy and chaff and flares to protect against radar-guided and heat-seeking missiles. Aircraft structure and radar-absorption materials reduce the aircraft's radar signature to approximately one percent that of a B-52. The ALE-50 provides greater protection against RF threats.

**B-1A.** USAF acquired four prototype flight-test models of this new strategic bomber in the 1970s, but the program was canceled in 1977. Flight-test of the four B-1A models continued through 1981.

**B-1B.** Initiated in 1981, the first production model of the improved variant B-1 flew in October 1984. USAF produced a total of 100. The active B-1B inventory was recently reduced to 67 aircraft (from the remaining 92) along with a consolidation to two main operating bases within Air Combat Command at Dyess AFB, Tex., and Ellsworth AFB, N.D. First used in combat against Iraq during Desert Fox in December 1998, the B-1B has since supported operations in Afghanistan in Enduring Freedom and in Iraqi Freedom.

B-1B's speed, superior handling qualities, and large payload make it a key element of any joint/composite strike force, with the flexibility to deliver a wide range of weapons or to carry additional fuel, as required.

The ongoing conventional mission upgrade program (CMUP) is significantly enhancing B-1B lethality and survivability. Completed Block D upgrades include GPS receivers, a MIL-STD-1760 weapon interface, secure interoperable radios, and improved computers to support precision weapons, initially the GBU-31 JDAM. Block E, now in production, includes follow-on computer and software upgrades permitting simultaneous carriage of mixed guided and unguided weapons and WCMD/JSOW/JASSM integration. Integration of the

JDAM (GBU-38) is also under way. Officials are continuing to assess options for future improvements to the B-1B's defensive system. In addition, planning is under way for a network centric upgrade program aimed at improving B-1B avionics and sensors, with cockpit upgrades to enhance crew communications and situational awareness. An effort to provide a fully integrated data link capability, including Link 16 and Joint Range Extension along with upgraded displays at the rear crew stations, is slated for FY05.

### B-2 Spirit

**Brief:** Stealthy, long-range multirole bomber that can deliver conventional and nuclear munitions anywhere on the globe by flying through previously impenetrable defenses.

**Function:** Long-range heavy bomber.

**Operator:** ACC.

**First Flight:** July 17, 1989.

**Delivered:** Dec. 11, 1993-2002.

**IOC:** April 1997, Whiteman AFB, Mo.

**Production:** 21.

**Inventory:** 21.

**Unit Location:** Whiteman AFB, Mo.

**Contractor:** Northrop Grumman; Boeing; LTV.

**Power Plant:** four General Electric F118-GE-100 turbofans, each 17,300 lb thrust.

**Accommodation:** two, mission commander and pilot, on zero/zero ejection seats.

**Dimensions:** span 172 ft, length 69 ft, height 17 ft.

**Weight:** empty 125,000-153,700 lb, typical T-O weight 336,500 lb.

**Ceiling:** 50,000 ft.

**Performance:** minimum approach speed 140 mph, typical estimated unrefueled range for a hi-lo-hi mission with 16 B61 nuclear free-fall bombs 5,000 miles, with one aerial refueling more than 10,000 miles.

**Armament:** in a nuclear role: up to 16 nuclear weapons (B61 Mod 7, B61 Mod II, B83) on rotary launchers. In a conventional role, 80 Mk 82 500-lb bombs, 36 750-lb M117s, 34 tactical munitions dispensers, 80 Mk 62 sea mines, or 80 GBU-38 (500-lb) JDAMs mounted on bomb rack assemblies, or up to 16 rotary launcher-mounted weapons: 16 GBU-31 (2,000-lb) JDAMs, or a penetration version of a BLU-109, or 16 Mk 84 2,000-lb bombs; 16 JSOWs, 16 JASSMs, or eight 4,700-lb GBU-37/EGBU-28 guided weapons. Wind-Corrected Munitions Dispenser (WCMD) to follow.

#### COMMENTARY

The B-2 bomber is a unique, highly advanced system, combining sophisticated technologies, notably low observable (LO) stealth design, with high aerodynamic efficiency, enabling it to attack heavily defended targets and neutralize enemy defenses.

Based on the flying wing concept, the B-2 has no vertical tail surfaces. The smoothly blended "fuselage" section accommodates two flight crew and two large weapons bays side by side in the lower centerbody. These bays contain rotary launchers or bomb rack assemblies capable of carrying up to 40,000 lb of weapons.

Four nonafterburning turbofan engines are mounted in pairs within the wing structure, with scalloped over-wing intake ducts and shielded over-wing trailing edge nozzles. The aircraft has a quadruple-redundant fly-by-wire digital flight-control system, actuating moving surfaces at the wing trailing edges that combine aileron, elevator, and rudder functions. A landing gear track of 40 ft enables the B-2 to use any runway that can handle a Boeing 727 airliner.

**B-2A.** B-2 production represents three successive blocks of capability. Block 10 aircraft carried B83 nuclear bombs or 16 Mk 84 2,000-lb conventional munitions. Block 20 aircraft additionally carried B61/7 and B61/11



**B-2 Spirit** (MSgt. Val Gempis)

nuclear bombs, as well as GPS-aided munitions (GAMs), and GBU-36B, on two rotary launcher assemblies, providing an interim, near-precision strike capability. All Block 10 and 20 aircraft have been upgraded to Block 30. (The last original Block 20 B-2, used as a test aircraft at Edwards AFB, Calif., was refurbished as an operational bomber and entered operational service in September 2002.)

Block 30 configuration retains weapons capability introduced in Block 10 and 20 and adds significant new capability. Using the rotary launcher assembly, all B-2s are capable of employing 16 Mk 84 JDAMs, 16 JSOWs, 16 JASSMs, or eight GBU-37s or EGBU-28s. All B-2s are also capable of substituting bomb rack assemblies in place of the rotary launchers, providing the capability to employ 80 500-lb Mk 82s, 36 750-lb M117s, 34 tactical munitions dispensers, or 80 Mk 62 sea mines. Modifications to the bomb racks add carriage of 80 independently targeted Mk 82 (500-lb) JDAMs. Other Block 30 enhancements include fully operational defensive and offensive avionics, a more sophisticated mission planning system, and additional operating modes for the synthetic aperture radar (SAR). A new stealth coating introduced under the Alternative High Frequency Material (AHFM) program is intended to improve combat readiness times.

Beyond Block 30, USAF plans to add UHF/EHF satellite communications systems and Link 16 digital data sharing capability and to replace the current mechanically scanned phased-array antenna with an active electronically scanned array.

The first use of B-2s in combat took place March 24, 1999, against Serb targets in Allied Force, with two aircraft each dropping 16 JDAMs. In October 2001, B-2s flew the longest combat sorties during Enduring Freedom, flying 44-hour sorties from Whiteman AFB, Mo., striking targets in Afghanistan, then landing in Diego Garcia for an engine running crew change, the second crew flying a 29-hour sortie back to Whiteman. In March 2003 for Iraqi Freedom, B-2s were deployed for the first time to a forward operating location, Diego Garcia.

#### **B-52 Stratofortress**

**Brief:** A long-range, heavy multirole bomber that can carry nuclear or conventional ordnance or Air Launched Cruise Missiles (ALCMs), with worldwide precision navigation capability.

**Function:** Long-range heavy bomber.

**Operator:** ACC, AFMC, AFRC.

**First Flight:** April 15, 1952 (YB-52 prototype).

**Delivered:** November 1955-October 1962.

**IOC:** June 19, 1955.

**Production:** 744.

**Inventory:** 93.

**Unit Location:** Barksdale AFB, La. (ACC, AFRC), Edwards AFB, Calif. (AFMC), Minot AFB, N.D.

**Contractor:** Boeing.

**Power Plant:** eight Pratt & Whitney TF33-P-3 turbofans, each 17,000 lb thrust.

**Accommodation:** two pilots, side by side, plus navigator, radar navigator, and electronic warfare officer.

**Dimensions:** span 185 ft, length 159.3 ft, height 40.7 ft.

**Weight:** empty approx 188,000 lb, gross 488,000 lb.

**Ceiling:** 50,000 ft.

**Performance** (approx): max level speed 449 mph, range more than 10,000 miles.

**Armament:** 12 AGM-86B ALCMs or AGM-129A Advanced Cruise Missiles (ACMs) externally, with provision for eight more ALCMs or gravity weapons internally. Conventional weapons incl AGM-86C/D Conventional ALCMs (CALCMs), bombs up to 2,000 lb, CBU 87/89/97 unguided cluster munitions, CBU-103/104/105 Wind-



**B-52H Stratofortress** (SSgt. Jocelyn Rich)

Corrected Munitions Dispenser (WCMD)-guided cluster munitions, GBU-31 JDAMs, JSOWs, JASSMs, and on some aircraft eight AGM-84 Harpoons in under-wing clusters. Future weapons incl CBU-113/115 WCMD-Extended Range (WCMD-ER).

#### **COMMENTARY**

The B-52's still-expanding weapons capability reflects its continued ability to perform a wide range of missions, including show of force, maritime operations, long-range precision strikes, close air support (CAS), offensive counterair, air interdiction, and defense suppression. USAF plans include using B-52s as standoff electronic warfare platforms while retaining all weapons carriage capability.

Equipment includes GPS, ARC-210 radios, Have Quick II antijam radio, KY-100 secure radio, an electro-optical (EO) viewing system that uses forward-looking infrared (FLIR) and high-resolution low-light-level television (LLTV) sensors to augment the targeting, battle assessment, flight safety, and terrain avoidance systems, improving combat and low-level flight capability. Pilots have night vision goggles (NVGs) to further enhance operation. Some B-52s are modified to carry weapons targeting pods. Future plans include modification of the entire fleet with an integrated self-targeting and battle damage assessment (BDA) capability. B-52s now support a MIL-STD-1760 interface resulting in an improved weapons capability, including naval mines, precision guided weapons, and advanced weapons such as JDAM, JSOW, JASSM, and WCMD. The B-52's ECM suite uses a combination of electronic detection, jamming, and infrared (IR) countermeasures to protect against hostile air defense systems. The aircraft can also detect and counter missile attack from the rear.

Several versions of the Stratofortress were produced, including:

**B-52A.** Initial production version, with J57-P-1W engines and provision for in-flight refueling. First flown Aug. 5, 1954, the three aircraft built were used by Boeing for technical development purposes. Delivered to SAC November 1957. Finally retired 1969.

**B-52B.** First operational version, 23 of which were built. Also, 27 RB-52B dual-role bomber/reconnaissance variants. First flown January 1955, with deliveries between June 1955-August 1956; powered by J57-P-1W, -19W, -29W, or -29WA engines. Retired in the mid-1960s.

**B-52C.** Multimission version with increased gross

weight and larger under-wing tanks. Powered by J57-P-19W or -29WA engines. First flown March 1956; 35 were delivered June-December 1956. Majority retired 1971.

**B-52D.** Long-range bomber version, first flown June 1956. Total of 170 built, with deliveries beginning late 1956. Retired 1982-83.

**B-52E.** Version with improved bombing, navigation, and electronics systems. First flown October 1957. One hundred delivered October 1957-June 1958. Retired 1969-70.

**B-52F.** Version with uprated J57-P-43WA engines, first flown in May 1958. Eighty-nine delivered June 1958-February 1959. Retired 1978.

**B-52G.** Introduced important design changes, including a redesigned wing containing integral fuel tanks for increased range, fixed under-wing external tanks, a shorter tail fin of greater chord, and a remotely controlled tail gun turret that allowed the gunner to be repositioned with the rest of the crew. Initial flight August 1958, with the first of 193 aircraft entering service in February 1959. Retired 1994.

**B-52H.** The only version still in service, the H introduced TF33 turbofans, providing increased unrefueled

range, and improved defensive armament. First flown July 1960, 102 were built, with deliveries between May 1961 and October 1962.

Primary role of the B-52 is still that of cruise missile carrier with multiple cruise missile launches at high altitude, often followed by B-52 penetration to conduct close air support and attack additional targets using GPS/INS guided weapons.

Ongoing modernization of its conventional capabilities is extending the B-52's service life well into this century, with the ability to provide massive firepower in low- to mid-threat environments supplemented by a standoff attack capability. Iraqi Freedom saw B-52s delivering laser guided bombs for the first time using newly installed Litening targeting pods. Modification of heavy stores adapter beams will enable aircraft to carry all B-52-certified munitions. Avionics improvements include the avionics midlife improvement (AMI) program, which replaces the current system processors and data transfer cartridges. Electronic attack improvements include the ECM improvement upgrade to the ALQ-172 set. The Combat Network Communications Technology (CONNECT) improvement will provide a modern cockpit information avionics architecture, in-flight beyond line of sight (BLOS) and LOS Link 16 intratheater data link connectivity and mission/weapon reprogramming capability. In the projected standoff jammer role, B-52Hs (dubbed **B-52 SOJ**) will carry new wingtip jamming pods, starting in 2009. Current plans call for 76 aircraft to be so equipped.

## **Fighter and Attack Aircraft**

#### **A-10 Thunderbolt II**

**Brief:** A simple, effective, and survivable twin-engine aircraft specifically designed for close air support (CAS) of ground forces and which can be used against all ground targets, including tanks and other armored vehicles.

**Function:** Attack aircraft.

**Operator:** ACC, AFMC, PACAF, USAF, ANG, AFRC.

**First Flight:** Feb. 15, 1975 (preproduction).

**Delivered:** November 1975-March 1984.

**IOC:** October 1977.

**Production:** 713.

**Inventory:** 357.

**Unit Location:** Active: Davis-Monthan AFB, Ariz., Eglin AFB, Fla.; Eielson AFB, Alaska, Nellis AFB, Nev., Osan AB, South Korea, Pope AFB, N.C., Spangdahlem AB, Germany. ANG: Barnes Arpt., Mass., Boise Air Terminal, Idaho, Bradley Arpt., Conn., Martin State Arpt., Md., W.K. Kellogg Arpt., Mich., Willow Grove ARS, Pa. AFRC: Barksdale AFB, La., NAS JRB New Orleans, La., Whiteman AFB, Mo.

**Contractor:** Fairchild Republic; now Lockheed Martin.

**Power Plant:** two General Electric TF34-GE-100 turbofans, each 9,065 lb thrust.

**Accommodation:** pilot only, on zero-height/518 mph-zero-speed ejection seat.

**Dimensions:** span 57.5 ft, length 53.3 ft, height 14.7 ft.

**Weight:** empty 28,000 lb, max gross 51,000 lb.

**Ceiling:** 37,000 ft.

**Performance:** speed 518 mph, combat range with 9,500 lb of weapons and 1.7 hr loiter, 20 min reserve, 288 miles.

**Armament:** one 30 mm, seven-barrel, 1,174-rd capacity GAU-8 Gatling gun capable of carrying inert target practice (TP) rds, straight high-explosive incendiary (HEI), or anti-armor tailored HEI/API "combat mix"; 11 hardpoints for up to 16,000 lb of ordnance, incl various types of free-fall or guided bombs such as Mk 82, Mk 84, GBU-10/12, CBU-87 Combined Effects Munition (CEM), 2.75-in high-explosive, white phosphorous, and covert illumination rockets, SUU-25 over/covert flare and "log" dispensers, up to six AGM-65B/D/G/H/K Maverick missiles, and up to four AIM-9 Sidewinder missiles. Up to 480 chaff and flares carried internally to counter radar or IR threats. Up to three 600-gallon fuel tanks can also be carried. Future weapons incl JDAM and Wind-Corrected Munitions Dispenser (WCMD).

#### COMMENTARY

Supporting the CAS, airborne forward air controller (FAC(A)), interdiction, and combat search and rescue (CSAR) ("Sandy") missions, the A-10 combines large diverse weapons payload, long loiter, austere airfield capability, maneuverability, and wide combat radius with the ability to operate under 1,000-ft ceilings, with 1.5-mile visibility, in darkness with NVGs and advanced targeting pods, and up to 20,000 ft. In a typical mission, the A-10, nicknamed Warthog, can fly 150 miles with a standard payload and remain on station (loiter) for two hours. The 30 mm GAU-8 gun provides a cost-effective weapon with which to defeat a wide array of ground targets, including tanks. The gun/rocket/Maverick medley provides a unique combination of "point-shoot," low-collateral damage, and mobile target capabilities demanded by the danger-close proximity to friendly forces. The cockpit is protected with titanium armor, capable of withstanding projectiles up to 23 mm. A-10s were used extensively in Desert Storm, Kosovo, Enduring Freedom, and Iraqi Freedom, the last operation seeing several A-10 combat firsts, including first use of Litening II targeting pod, first self-lased laser guided bomb (LGB) delivery, and first AGM-65H/K employment. The A-10 is projected to serve well into the 2020s.

**A-10A** equipment includes an enhanced GPS/INS (EGI), head-up display (HUD), NVGs, the Integrated Flight and Fire Control Computer (IFFCC) to enhance weapons delivery accuracy, cockpit presentations, targeting pod integration, and terrain avoidance. Other equipment includes Pave Penny laser target identification pod and self-protection/penetration aids to include ALQ 131/184 ECM pods, ALR-69 radar warning receiver and countermeasures system (CMS) to digitally integrate the ALE-40 chaff-flare dispenser.

**A-10C**, new designation for aircraft to be upgraded for precision engagement, with new cockpit displays, full targeting pod integration, hands-on throttle and stick (HOTAS), a digital stores management system, a Joint Tactical Radio System (JTRS) data link and JDAM/WCMD integration. Low-rate initial production (LRIP) of upgrade kits began in 2004, and debut flight occurred Jan. 20, 2005. Additionally, an upgraded automated chaff and flare system is planned for 2008.

**OA-10A** aircraft are primarily used for FAC(A) missions, combat escort, search and rescue, and visual reconnaissance. The OA-10 is identical to the A-10A. Mission configurations typically include large loads of white phosphorous marking rockets and covert/overt illumination rockets/flares/logs to mark and/or illuminate targets for strike aircraft or friendly ground forces. The first OA-10 unit reached initial operational capability (IOC) in October 1987.

#### AC-130 Gunship

**Brief:** Heavily armed aircraft using side-firing weapons integrated with sophisticated sensor, navigation, and fire-control systems to provide precise firepower or area saturation for long periods, at night and in adverse weather.

**Function:** Attack aircraft.

**Operator:** AFSOC.



**A-10A Thunderbolt II** (TSgt. Bob Sommer)

**First Flight:** 1967.

**Delivered:** 1968-present.

**IOC:** 1972 (AC-130H); 1996 (AC-130U).

**Production:** 39; conversion of four additional C-130s to AC-130 standard contracted.

**Inventory:** 8 (AC-130H); 13 (AC-130U).

**Unit Location:** Hurlburt Field, Fla.

**Contractor:** Lockheed Martin (airframe); Boeing (AC-130H); Rockwell, now Boeing (AC-130U).

**Power Plant:** four Allison T56-A-15 turboprops, each 4,910 shp.

**Accommodation:** AC-130H crew of 14; AC-130U crew of 13.

**Dimensions:** span 132.6 ft, length 99 ft, height 38.5 ft.

**Weight:** gross 155,000 lb.

**Ceiling:** 25,000 ft.

**Performance:** speed 289 mph, range 1,500 miles, with air refueling unlimited.

**Armament:** two 20 mm Vulcan cannons with 3,000 rd (AC-130H); one 25 mm Gatling gun (AC-130U); one 40 mm Bofors cannon with 256 rd, and one 105 mm Howitzer with 100 rd.

#### COMMENTARY

The AC-130 is a C-130 modified with gun systems, electronic and EO sensors, fire-control systems, enhanced navigation systems, sophisticated communications, defensive systems, and in-flight refueling capability. These systems give the gunship crew the capability to acquire and identify targets day or night, coordinate with ground forces and command and control (C2) agencies, and deliver surgical firepower in support of both conventional and special operations missions. During operations in Afghanistan and Iraq, the AC-130 gunships worked in conjunction with the MQ-1 Predator, the latter providing live video and target referencing information.

**AC-130A** was the initial version, deployed in Vietnam 1968-69. Eighteen produced.

**AC-130E**, an improved version, of which eight were built. Converted to H standard after service in Vietnam.

**AC-130H Spectres** serve with the 16th SOW. The unit has eight, each equipped with a digital fire-control computer. They employ EO sensors and target-acquisition systems, including FLIR and LLLTV, and are capable of in-flight refueling. Fire-control computers, navigation, communications, and sensor suites have

been upgraded; an infrared suppression system (IRSS) overhaul is under way. In addition, USAF is evaluating wingtip tanks as replacements for the existing underwing tanks as a means of improving performance.

**AC-130U Spooky**, gunship conversions by Rockwell, of which 13 were delivered to the 16th SOW's 4th SOS in 1994-95. Four additional aircraft have been contracted for conversion by Boeing to U standard. These AC-130Us have greater altitude capability and combine increased firepower, reliability, and superior accuracy with the latest methods of target location. All weapons can be subordinated to the APQ-180 digital fire-control radar, FLIR, or all-light-level television (ALLTV) for adverse weather attack operations.

Although the AC-130H Spectre and AC-130U Spooky gunships use dissimilar avionics and other systems, fire support to troops on the ground is generally comparable. The AC-130U will not be required for most fire support missions but provides benefits under certain circumstances (weather, dual target attack, and defensive avionics).

#### F-15 Eagle

**Brief:** A supersonic, all-weather, highly maneuverable tactical fighter designed to permit USAF to swiftly gain and maintain air superiority in aerial combat.

**Function:** Air superiority fighter.

**Operator:** ACC, AETC, AFMC, PACAF, USAFE, ANG.

**First Flight:** July 27, 1972.

**Delivered:** November 1974-85.

**IOC:** September 1975.

**Production:** 874.

**Inventory:** 511.

**Unit Location:** Active: Eglin AFB, Fla., Elmendorf AFB, Alaska, Kadena AB, Japan, Langley AFB, Va., Mountain Home AFB, Idaho, Nellis AFB, Nev., RAF Lakenheath, UK, Robins AFB, Ga., Tyndall AFB, Fla., ANG: Hickam AFB, Hawaii, Jacksonville Arpt., Fla., Klamath Falls Arpt., Ore., Lambert-St. Louis Arpt., Mo., NAS JRB New Orleans, La., Otis ANGB, Mass., Portland Arpt., Ore.

**Contractor:** McDonnell Douglas (now Boeing); Raytheon.

**Power Plant:** F-15C: two Pratt & Whitney F100-PW-220 turbofans, each 25,000 lb thrust, with max afterburner.



**AC-130 Gunship** (USAF photo)

**Accommodation:** pilot only in F-15A/C; two seats in F-15B/D.

**Dimensions:** span 42.8 ft, length 63.8 ft, height 18.7 ft.

**Weight:** empty 28,600 lb, gross 68,000 lb.

**Ceiling:** 65,000 ft.

**Performance:** F-15C: max speed Mach 2.5, T-O run 900 ft, landing run without braking parachute 3,500 ft, ferry range with external fuel tanks more than 2,878 miles.

**Armament:** one internally mounted M61A1 20 mm six-barrel cannon; up to four AIM-9L/M Sidewinder and up to four AIM-7 Sparrow air-to-air missiles, or up to eight AIM-120 Advanced Medium-Range Air-to-Air Missiles (AMRAAMs), carried externally. Deliveries of AIM-9X from November 2003.

#### COMMENTARY

Superior maneuverability and acceleration, range, weapons, and avionics enable the F-15 to penetrate hostile defenses and establish air superiority over enemy systems. F-15 fighters deployed to the Persian Gulf for Desert Storm accounted for 34 of the 37 USAF air-to-air victories, and in Iraqi Freedom F-15Cs led coalition aircraft in maintaining aerial dominance.

**F-15A** (single-seat) and **F-15B** (two-seat) fighters became USAF's front-line fighter immediately upon introduction in the mid-1970s. A multimission avionics system includes APG-63 pulse-Doppler radar for long-range detection and tracking of small high-speed objects down to treetop level and effective weapons delivery, a HUD for close-in combat, identification, friend or foe (IFF), and INS. F-15A/Bs now serve with ANG. In February 2004, Florida's 125th FW received the first of 19 F-15A/Bs retrofitted with E-kit upgrades providing additional thrust and improved combat capability. Other units are expected to follow.

**F-15C** (single-seat) and **F-15D** (two-seat) models followed in June 1979. Improvements included 2,000 lb of additional internal fuel and provision for carrying conformal fuel tanks (CFTs), reducing in-flight refueling requirements and increasing time in the combat zone. From 1983 through 1997, tactical capabilities were enhanced extensively through the multistaged improvement program (MSIP), a program of installation of new or modification of existing avionics equipment, which allows for the carriage of more advanced weapons, and increased self-protection. The last 43 aircraft included improved APG-70 radar, and F-15C/Ds are receiving an APG-63 upgrade, the APG-63(V)1. One squadron in Alaska received the later APG-63(V)2, featuring an active electronically scanned array (AESA), permitting the aircraft to track multiple targets and to guide air-to-air missiles against them. The Joint Helmet Mounted Cueing System (JHMCS), a "look and shoot" head-mounted system, will, along with the AIM-9X, significantly enhance lethality in close-range aerial combat. Other modifications include improved engines, GPS equipment, and the Link 16 fighter data link.

#### F-15E Strike Eagle

**Brief:** A heavily modified, two-seat, dual-role variant of the original F-15, with weapons systems totally integrated for all-weather deep interdiction missions as well as air-to-air combat.

**Function:** Dual-role fighter.

**Operator:** ACC, AFMC, PACAF, USAFE.

**First Flight:** Dec. 11, 1986.

**Delivered:** April 1988-2004.

**IOC:** May 1989.

**Production:** 236.

**Inventory:** 222.

**Unit Location:** Eglin AFB, Fla., Elmendorf AFB, Alaska, Mountain Home AFB, Idaho, Nellis AFB, Nev., RAF Lakenheath, UK, Robins AFB, Ga., Seymour Johnson AFB, N.C.

**Contractor:** McDonnell Douglas (now Boeing); Raytheon.

**Power Plant:** two Pratt & Whitney F100-PW-220, each 25,000 lb thrust; or F100-PW-229 turbofans, each 29,000 lb thrust with max afterburner.

**Accommodation:** crew of two, on zero/zero ejection seats.

**Dimensions:** span 42.8 ft, length 63.8 ft, height 18.5 ft.

**Weight:** empty 45,000 lb, gross 81,000 lb.

**Ceiling:** 50,000 ft.

**Performance:** max level speed at altitude Mach 2.5, ferry range with CFTs 3,000 miles.

**Armament:** one internally mounted M61A1 20 mm six-barrel cannon; up to four AIM-9 Sidewinder and up to four AIM-7 Sparrow air-to-air missiles, or up to eight AIM-120 AMRAAMs; up to six AGM-65 Maverick air-to-surface missiles; AGM-130; EGBU-15 and GBU 10/12/15/24/28 guided munitions; CBU 87/89/97 unguided cluster munitions; unguided munitions; JSOW, JDAM, CBU-103/104/105 Wind-Corrected Munitions Dispenser (WCMD)-guided cluster munitions, and nuclear weapons.

#### COMMENTARY

**F-15E** has a strengthened airframe for increased gross weight at takeoff and maneuver at nine Gs through-

out the flight envelope. Cockpit controls and displays are improved, and a wide-field-of-view (WFOV) HUD is included.

During Desert Storm, 48 USAF F-15Es were deployed to the Persian Gulf where they operated mainly at night, hunting Scud missile launchers and artillery sites using the LANTIRN system; the ability to operate in conjunction with E-8 Joint STARS aircraft both then and in Iraqi Freedom proved critical to success.

Ten additional aircraft were authorized for delivery from FY02 through FY04. These new F-15Es include an upgrade to the programmable armament control set (PACS), software for delivery of JDAM, JSOW, and WCMD, and an enhanced night vision capability.

**Function:** Multirole fighter.

**Operator:** ACC, AETC, AFMC, PACAF, USAFE, ANG, AFRC.

**First Flight:** Dec. 8, 1976 (full-scale development).

**Delivered:** August 1978-2007 (planned).

**IOC:** October 1980, Hill AFB, Utah.

**Production:** 2,206.



**F-15E Strike Eagle** (MSgt. Shaun Withers)

**Inventory:** 1,346.

**Unit Location:** 13 active wings, 28 ANG, and five AFRC units (one associate).

**Contractor:** Lockheed Martin; Northrop Grumman.

**Power Plant:** one augmented turbofan. General Electric F110-GE-100 (27,600 lb thrust) and Pratt & Whitney F100-PW-220 (23,450 lb thrust) are alternative standard engines. Increased performance engines (IPEs) in aircraft delivered from late 1991: Block 50: F110-GE-129 (29,000 lb thrust); Block 52: F100-PW-229 (29,100 lb thrust).

**Accommodation:** pilot only, on zero/zero ejection seat.

**Dimensions:** wingspan with missiles 32.7 ft, length overall 49.4 ft, height 16.7 ft.

**Weight:** (F-16C) empty (F100-PW-229) 18,591 lb, (F110-GE-129) 18,917 lb; gross, with external load (Block 40/42) 42,000 lb.

**Ceiling:** 50,000 ft.

**Performance:** max speed Mach 2, radius of action: Block 40 with two 2,000-lb bombs, two AIM-9 missiles, and external fuel, hi-lo-lo-hi 852 miles; combat range 575 miles.

**Armament:** one M61A1 20 mm multibarrel cannon, with 511 rd, mounted in fuselage; wingtip-mounted missiles; seven other external stores stations for fuel tanks and a range of air-to-air and air-to-surface munitions.

#### COMMENTARY

The F-16 is the workhorse of the USAF fighter fleet, constituting more than 50 percent of its strength through at least 2010. The 200+ USAF F-16 multimission fighters deployed to the Persian Gulf Theater flew more sorties than any other type during Desert Storm, with 13,500 missions. In Iraqi Freedom, the F-16 flew hundreds of missions helping to destroy the unit cohesion of the Republican Guard.

**F-16A** (single-seat) and **F-16B** (two-seat) versions, which entered service with the 388th TFW, Hill AFB, Utah, incorporated advanced technologies from the start, making these aircraft two of the most maneuverable fighters built. Equipment includes a multimode radar with a clutter-free look-down capability, advanced radar warning receiver (RWR), HUD, internal chaff/flare dispensers, and a 500-rd 20 mm internal gun.

Production of the F-16A and B for USAF ended in 1985. Most now belong to ANG. A midlife update program, undertaken cooperatively by USAF and NATO



**F-16CJ Fighting Falcon** (Ted Carlson)



**F/A-22 Raptor** (MSgt. Michael Ammons)

operators, includes improvement to the radar, fire-control computer, stores-management computer, and avionics software, giving F-16A/Bs the ability to use next generation air-to-air and air-to-surface weapons.

Reliability and maintainability improvements include a ring-laser gyro INS and installation of the upgraded F100-PW-220E turbofan engine.

The Multinational Staged Improvement Program, implemented in 1980, ensured the aircraft could accept systems under development, thereby minimizing retrofit costs. All F-16s delivered since November 1981 have had built-in structural and wiring provisions and systems architecture that expand the single-seater's multirole flexibility to perform precision strike, night attack, and beyond-visual-range intercept missions.

**F-16C** (single-seat) and **F-16D** (two-seat) aircraft were introduced at production Block 25 with MSIP II improvements in the cockpit, airframe, and core avionics and an increased-range APG-68 radar. Block 30 and 40 aircraft incorporate the General Electric F110-GE-100 engine. Deliveries began in 1984. With the exception of AFMC, all of the active and many of the Guard and Reserve units have since converted to F-16C/Ds.

ANG and AFRC Block 25/30/32 F-16s are receiving upgrades aimed at increasing throughput and memory for new weapon capabilities, including the 500-lb JDAM, plus Advanced Identification Friend/Foe (AIFF) to reduce the risk of fratricide.

**F-16CG** Block 40/42 aircraft specialize in night attack operations with precision guided weapons. Follow-on improvements include ALE-47 improved defensive countermeasures, ALR-56M advanced RWR (Block 40 only), Very High Speed Integrated Circuit (VHSIC) technology in the APG-68(V5) fire-control radar, a ring-laser gyro INS, GPS, a LANTIRN nav/attack system, core avionics hardware, enhanced-envelope gunsight, digital flight controls, automatic terrain following, increased takeoff weight and maneuvering limits, an 8,000-hour airframe, IPES, and expanded envelope nine-G capability.

**F-16CJ** designated Block 50/52 aircraft are equipped with the High-speed Anti-Radiation Missile (HARM) targeting system (HTS) for suppression of enemy air defenses (SEAD). Block 50/52 F-16CJs have MSIP Stage III improvements, which also show up in selected retrofits of earlier F-16 blocks. These aircraft incorporate the General Electric F110 and Pratt & Whitney F100 increased performance engines (IPES), the latest cockpit control and display technology, including a wide-angle HUD. Weapons improvements include multi-shot AMRAAM compatibility, AGM-154 JSOW, and Wind-Corrected Munitions Dispenser (WCMD).

Block 50/52 aircraft, followed by Block 40/42 from 2006-10, are being retrofitted with a new modular mission computer being developed under an F-16 common configuration implementation program (CCIP), aimed at extending operational flexibility and maintenance commonality. This effort includes the participating European governments of the F-16 Multinational Fighter Program. CCIP also includes new color displays, Sniper XR targeting pod, JHMCS, AIM-9X, Link 16, and improved weapons capabilities. First delivery made January 2002. The Block 50/52 aircraft will have dual/alternate carriage of HARM targeting system (HTS) and Smart Targeting and Identification via Networked Geolocation (STING) and advanced targeting pods (ATP) in FY07. Planned future upgrades include enhanced GPS/INS (CG/CJ aircraft) and upgraded radar with SAR capability (CJ aircraft).

Under Falcon STAR (SStructural Augmentation Roadmap), all blocks of F-16 aircraft are undergoing a structural modification program to remedy fatigue problems caused by increased usage rates and heavier

than forecast gross weights. Delivery of modified aircraft started October 2004 and is scheduled to continue to 2014.

**F/A-22 Raptor**

**Brief:** High-technology follow-on for the F-15C. An all-weather, multirole fighter that combines an extremely maneuverable airframe with stealth technologies, supercruise, and integrated avionics to help it penetrate through advanced anti-air threats and achieve air dominance.

**Function:** Fighter.  
**Operator:** ACC, AETC, AFMC.  
**First Flight:** Sept. 7, 1997.  
**Delivery:** 2001 (first production representative aircraft).

**IOC:** December 2005 (planned).  
**Production:** stated requirement 381.  
**Inventory:** 27.

**Unit Location:** Langley AFB, Va. (designated first operational location), Edwards AFB, Calif., Nellis AFB, Nev., Tyndall AFB, Fla. (fighter training unit).

**Contractor:** Lockheed Martin; Boeing.  
**Power Plant:** two Pratt & Whitney F119-PW-100 turbofans, each in 35,000-lb thrust class.

**Accommodation:** pilot only, on zero/zero ejection seat.  
**Dimensions:** span 44.5 ft, length 62 ft, height 16.6 ft.  
**Weight:** gross 50,000 lb.

**Ceiling:** 50,000 ft.  
**Performance** (design target): max level speed at S/L 900+ mph, range more than 2,000 miles.

**Armament:** one internal M61A2 20 mm gun, two AIM-9 Sidewinders stored internally in the side weapons bays; six AIM-120 AMRAAMs in the main weapons bay; for ground attack two 1,000-lb JDAMs replace four AMRAAMs internally; up to eight Small Diameter Bombs (SDBs) can be carried in place of the two JDAMs (projected by 2009).

**COMMENTARY**

The F/A-22's unparalleled combination of stealth, supercruise (ability to cruise at supersonic speed without using its afterburners), maneuverability, and integrated avionics allows it to counter multiple anti-access threats. Integrated avionics and intraflight data link permit simultaneous engagement of multiple targets. The combination of flight controls, structural strength, and high-performance engines with thrust vectoring nozzles results in exceptional maneuverabil-

ity. The F/A-22 will lead the USAF's "kick down the door" force, day and night, across the spectrum of missions.

The F/A-22 entered engineering and manufacturing development (EMD) in August 1991. During this period, nine aircraft were built, three without avionics to explore flight characteristics, flutter, loads, propulsion, envelope expansion, and weapons separation. The first aircraft is no longer flying and was used for live fire testing after completion of its flight characteristics work. The remaining six were built with avionics to complete integration work, refine the pilot vehicle interface, and fly guided weapons launch tests. In addition, one static and one fatigue test airframe were built.

Initial operational test and evaluation (IOT&E) examining the Raptor's air dominance mission concluded mid-September 2004. JDAM capability was demonstrated that same month. Follow-on OT&E (FOT&E) is expected to start July 2005. The F/A-22 is planned to have air-to-air and air-to-ground attack capability when it reaches IOC at the end of 2005.

The F/A-22 is in low-rate initial production (Lots 1-5) with full-rate production approved in the spring of 2005. Production aircraft have been delivered to Nellis AFB, Nev., and to Tyndall AFB, Fla., where they are used to train F/A-22 pilots. Langley received its first Raptors in January 2005.

**F-35 Joint Strike Fighter**

**Brief:** An affordable, highly common family of next generation strike aircraft.

**Function:** Multirole fighter.  
**Operator:** ACC for USAF.

**First Flight:** Oct. 24, 2000 (concept demonstrator).  
**Delivery:** 2009 (anticipated first production aircraft).  
**IOC:** 2013 (USAF).

**Production:** planned: 1,763 total F-35A and F-35B (USAF), 680 total F-35B (USMC) and F-35C (USN), 150 (UK).

**Inventory:** TBD.  
**Unit Location:** TBD.

**Contractor:** Lockheed Martin, with Northrop Grumman and BAE Systems; Pratt & Whitney is propulsion contractor; General Electric is second source engine contractor for the production phase.

**Power Plant:** one Pratt & Whitney F135 or General Electric F136 turbofan (production), in 35,000-lb thrust class.

**Accommodation:** pilot only, on zero/zero ejection seat.  
**Dimensions:** TBD.

**Weight:** TBD.  
**Ceiling:** TBD.

**Performance** (design targets): mil power level speed at S/L, 600 miles knots calibrated airspeed (KCAS) for the F-35B short takeoff and vertical landing (STOVL) aircraft, 630 KCAS for the F-35 carrier variant (CV) and for the F-35A conventional takeoff and landing (CTOL) variant (Mach 1 max power for CTOL only), combat radius more than 590 miles for CTOL variant, 600 miles for CV, and 450 miles for STOVL.

**Armament:** (main weapons bay): CTOL: one internal gun, two AMRAAMs, and two 2,000-lb JDAMs. CV: two AMRAAMs and two 2,000-lb JDAMs. STOVL: two AMRAAMs and two 1,000-lb JDAMs. External carriage will also be available. (Note: Numerous other weapons capabilities will be added as system development continues.)

**COMMENTARY:** The F-35 Joint Strike Fighter is a multinational cooperative development program aimed at developing and fielding an affordable, highly common family of next generation strike fighters. For USAF, the F-35 will replace its current force of F-16 and A-10 aircraft with a stealthy multirole fighter that will comprise the bulk of USAF's fighter fleet for up to 50 years.



**F-35 Joint Strike Fighter** (Lockheed Martin photo/Tom Reynolds)

This advanced multimission fighter is designed to penetrate high-threat enemy airspace and engage all enemy targets in any conflict. In addition to its advanced stealth design, the F-35 incorporates maneuverability, long range, and highly advanced avionics to accomplish the bulk of USAF missions. Its fully integrated avionics and weapons systems will permit simultaneous engagement of multiple targets in enemy airspace. USAF has stated intent to buy approximately 250 **F-35B** STOVL variants.

The concept demonstration phase (CDP) of the program commenced November 1996, with competitive contract awards to Lockheed Martin (X-35A) and Boeing (X-32A). CDP concluded in fall 2001 with Lockheed Martin declared the winner. The system development and demonstration (SDD) phase, begun in October 2001, focuses on system development, test and evaluation, logistics support, and LRIP planning. Flight testing is projected to begin in 2006. The F-35 is powered by a derivative of the Pratt & Whitney F119 engine, called the F135. General Electric is developing a physically and functionally interchangeable power plant, the F136, for competition in production.

**F-117 Nighthawk**

**Brief:** World's first operational aircraft designed to exploit low observable (LO) stealth technology to expand the range of heavily defended critical targets that can be attacked.

**Function:** Attack aircraft.

**Operator:** ACC, AFMC.

**First Flight:** June 18, 1981.

**Delivered:** 1982-summer 1990.

**IOC:** October 1983.

**Production:** 59.

**Inventory:** 55 (52 F-117A; 3 YF-117).

**Unit Location:** Eglin AFB, Fla., Holloman AFB, N.M.

**Contractor:** Lockheed Martin; Raytheon.

**Power Plant:** two General Electric F404-GE-F1D2 nonafterburning turbojets, each 9,040 lb thrust.

**Accommodation:** pilot only, on zero/zero ejection seat.

**Dimensions:** span 43.3 ft, length 65.9 ft, height 12.4 ft.

**Weight:** empty (estimated) 29,500 lb, max gross 52,500 lb.

**Ceiling:** 35,000 ft.

**Performance:** high subsonic, top speed 646 mph (0.9 Mach), mission radius, unrefueled (5,000-lb weapons load) 656 miles.

flying to maintain secrecy. In 1992, they were transferred to the 49th FW at Holloman AFB, N.M.

To achieve the aircraft's minimal radar signature, the skin panels of the arrowhead-shaped airframe are divided into many small, perfectly flat surfaces (facets), which deflect at a variety of angles all signals from probing hostile ground or airborne radars. In addition, much of the aircraft's external surface is made of composites and radar-absorbent materials. The F-117A's dull black finish reflects little light, and the engine air intakes and exhaust nozzles are above the wings and rear fuselage, respectively, to shield them from IR seekers below. The two nonafterburning turbofans give the aircraft low noise signature and high subsonic performance.

Key features include a state-of-the-art digital avionics suite integrating sophisticated navigation and attack systems, complemented by a specially developed automated mission-planning system. A high-precision INS coupled to GPS is installed. An upgraded dual-turret IR targeting system, combined with boresight laser designators and autotracker, ensures precision attack.

Other improvements since 1989 have included upgraded cockpit display and instrumentation and adverse weather capability via advanced weapons. Current and ongoing modifications provide a single, fleet-wide, optimum LO configuration, upgraded avionics to Block 2 configuration, integration of new weapons including JDAM for all-weather strike capability, and replacement of obsolete components to sustain the fleet through its service life. The F-117 is expected to remain in USAF service into the 2020s.

**J-UCAS**

**Brief:** A joint DARPA/USAF/Navy program to develop the technical feasibility, military usefulness, and operational value of a networked system of affordable, sophisticated stealthy weaponized unmanned combat air vehicles (UCAVs) capable of performing SEAD, strike, and electronic attack for the Air Force (X-45) and intelligence-surveillance-reconnaissance (ISR) missions for the Navy (X-47).

**Function:** Concept demonstrator UCAVs for SEAD/strike/electronic attack/reconnaissance missions.

**First Flight:** May 22, 2002.

**Delivered:** TBD.

**Contractor:** X-45: Boeing; X-47: Northrop Grumman.

**Production:** TBD.

**Inventory:** TBD.

**Unit Location:** TBD.

**Power Plant:** X-45A Honeywell F124-GA-100 turbofan.

**Dimensions:** X-45A: span 33.8 ft, height 3.7 ft, length 26.5 ft. X-45C: span approx 48 ft; length 36 ft.

**Weight:** X-45C: approx 35,000 lb.

**COMMENTARY**

Under the Joint Unmanned Combat Air System (J-UCAS) program, the Defense Advanced Research Projects Agency (DARPA) is developing carrier-capable UCAV technology for the Navy (X-47) and a USAF system (X-45) for the SEAD, strike, and electronic attack mission. Key to the program is the use of a common operating system to facilitate the integration of subsystems such as sensors, weapons, and communications, allowing USAF and Navy UCAVs to work together seamlessly. Additionally, the system architecture will ensure interoperability with manned aircraft, command and control centers, and space assets. The UCAV may be made air refuelable for self-deployment.

USAF will become lead service in October 2005.

**X-45A.** The initial version, this Y-shaped vehicle bears little resemblance to the operational version USAF plans to field.

**X-45B.** Canceled.

**X-45C** more closely resembles the objective UCAV system. This flying-wing-design variant will feature a new, larger airframe with dual internal weapons bays capable of carrying two 2,000-lb JDAMs or eight-plus Small Diameter Bombs and will demonstrate stealth characteristics. Block 2 flight testing includes multivehicle flights and release of an internally carried guided weapon. First prototype flight is expected in 2006.

**YAL-1A Attack Airborne Laser**

**Brief:** The prototype YAL-1A, using a modified 747-400F platform, will be the world's first operational airborne high-energy laser weapon system.

**Function:** Airborne laser.

**Operator:** ACC.

**First Flight:** July 18, 2002 (Block 04 test bed).

**Delivered:** First aircraft undergoing testing of beam control system; separate testing of COIL system, installation of laser system.

**IOC:** FY12 (planned).

**Production:** TBD.

**Inventory:** TBD.

**Unit Location:** TBD.

**Contractor:** Boeing (ABL platform; battle management (BM) system); TRW (now Northrop Grumman) (COIL and subsystems); Lockheed Martin (beam control system).

**Power Plant:** four GE CF6-80 turbofans, each 61,500 lb thrust.

**Accommodation:** flight crew of two, plus four mission specialists.

**Dimensions:** span 211.4 ft, length 228.8 ft, height 63.7 ft.

**Weight:** empty 423,882 lb, gross 800,000 lb.

**Ceiling:** 45,000 ft.

**Performance:** max operating speed Mach 0.83, max laser weapon range hundreds of miles, unrefueled endurance at 40,000 ft with operational laser weapon load approx six hr. Chemical fuel carried on board will enable more than 20 shots.

**COMMENTARY**

The Airborne Laser (ABL) will become the first directed energy weapon in the US arsenal. The Missile Defense Agency (MDA) assumed overall direction and budget authority for the program in summer 2001. USAF continues to man and develop the program through its Airborne



**F-117 Nighthawk** (SSgt. Derrick C. Goode)

**Armament:** full internal carriage of a variety of tactical weapons, incl laser- and GPS-guided 2,000-lb munitions, unguided general-purpose bombs, and cluster munitions. JDAM capability being introduced.

**COMMENTARY**

F-117 is the Air Force's primary attack aircraft for penetrating high-threat target areas with precision weapons. Its small radar signature, LO technologies, and advanced targeting system allow the aircraft to penetrate dense threat environments and to deliver precision weapons against heavily defended, high-value targets with pinpoint accuracy. Primary missions include precision attack, air interdiction, SEAD, and special operations.

Acknowledged publicly in November 1988, the F-117's first operational deployment was to Panama in 1989 for Just Cause.

**F-117A** development and manufacture began simultaneously in November 1978 within a highly classified environment, using many parts either transferred or modified from existing aircraft. The F-117As were deployed with the 4450th Tactical Group (redesignated 37th TFW in 1989) at Tonopah Test Range Airfield, Nev., where operations were restricted mainly to night



**J-UCAS: X-45A UCAV concept demonstrator** (DARPA photo)

Laser System Program Office at Kirtland AFB, N.M.

Air Combat Command will have operational responsibility and currently plans to base the attack laser in CONUS but could deploy the ABL with minimal airlift support to any region of the world. It will arrive in theater with its crew, laser fuel, and initial spares ready to fight. Operational concepts call for ABLs to fly continuous patrols over deployed US forces, at an altitude of 40,000 ft. The aircraft will detect and shoot down any ballistic missiles launched at US forces or nearby allied nations. The ABL will also have the capability of determining hostile launch locations and passing that information to other US assets. As US forces achieve air superiority, ABL will be able to move closer to enemy territory. Once the decision is made to proceed with full production, USAF's acquisition community will assume responsibility for procurement; fleet size has not been determined.

It will employ a Chemical-Oxygen Iodine Laser (COIL) system, running down the interior of the aircraft. Laser fire will emerge through a large ball turret in the nose. Intended targets are ballistic missiles in their boost, or very earliest, phase of flight. ABLs represent the only near-term boost-phase missile defense. The system will track ballistic missiles and maintain laser focus on their skin, which, when sufficiently heated, will cause the pressurized fuel within to explode. The ABL can target ballistic missiles hundreds of miles away and thus can remain over friendly territory to kill ballistic missiles as they are launched.

The lightweight, megawatt-class COIL technology can deliver high energy over a great distance largely because of its IR wavelength. In addition to the COIL, the ABL houses three other lasers: the active ranger system, which provides preliminary tracking data; the track illuminator laser, which produces more refined data; and the beacon illuminator laser, which measures atmospheric disturbance.

Following a two-year structural modification, the ABL Boeing's first flight took place July 18, 2002, from Boeing's Wichita, Kan., facility. A 10-month laser module test was completed in 2002, and, in late 2002, the platform was flown to Edwards AFB, Calif. While YAL-1A is in the hangar, tests are being conducted independently on the ABL optical system and the six laser modules that make up the complete COIL system. All six modules were successfully tested on Nov. 10, 2004. Tests will continue for several months. Once proved effective, they will be installed on the aircraft in preparation for a rigorous series of ground and air tests of the entire ABL configuration. Initial tests are expected to culminate in a test destruction of a boost- ing ballistic missile over the Pacific.

## Reconnaissance and Surveillance Aircraft

### E-3 Sentry

**Brief:** Modified Boeing 707, fitted with a rotating radar dome 30 ft wide and 6 ft thick, which provides all-weather air surveillance and command, control, and communications for tactical and air defense forces.

**Function:** Airborne early warning, BM, C3 aircraft.

**Operator:** ACC, PACAF, AFRC (assoc.).

**First Flight:** Oct. 31, 1975 (full avionics).

**Delivered:** March 1977-84.

**IOC:** 1977.

**Production:** 34.

**Inventory:** 32.

**Unit Location:** Elmendorf AFB, Alaska, Kadena AB, Japan, Tinker AFB, Okla. AFRC: (assoc.) Tinker AFB, Okla.

**Contractor:** Boeing; Northrop Grumman (radar); Lockheed Martin (computer).

**Power Plant:** four Pratt & Whitney TF33-PW-100/100A turbofans, each 21,000 lb thrust.

**Accommodation:** flight crew of four; 13-19 mission specialists.

**Dimensions:** span 145.8 ft, length 152.9 ft, height 41.5 ft.

**Weight:** gross 347,000 lb.

**Ceiling:** 38,000 ft.

**Performance:** optimum cruise Mach 0.78, endurance eight hr unrefueled.

### COMMENTARY

A critical component of the USAF inventory, the E-3 Airborne Warning and Control System (AWACS) aircraft is capable of surveillance from Earth's surface up to the stratosphere, over land or water, at more than 200 miles. During conflict it will coordinate the actions of hundreds of strike, support, and cargo aircraft.

**E-3A.** Of the 24 built for USAF in standard production configuration, 22 were later upgraded.

An improved US/NATO Standard E-3A configuration



**E-3C Sentry** (SSgt. Matthew Hannen)

was initiated with the 25th USAF Sentry, delivered in December 1981, with a larger-memory computer and a maritime detection capability. Nine were built new for USAF, and one of the original E-3As was upgraded.

**E-3B** is the upgraded earliest version E-3A. Twenty-two production models and two prototypes were produced. Improvements include much-enhanced computer capabilities, jam-resistant communications, austere maritime surveillance capability, additional radio communications, and five additional display consoles.

**E-3C** is an upgrade to the original 10 US/NATO Standard E-3A aircraft, with additional radio, console, and radar capabilities. Redelivered 1984.

A series of major sustainability, reliability, and availability upgrades for USAF E-3s has been undertaken to support the continuing demands on the system. Upgrades include new passive detection systems, known as electronic support measures (ESM), that complement the active beaming radar, enabling the aircraft to detect signals emitted by both hostile and friendly targets, improved Joint Tactical Information Distribution System (JTIDS), jam-resistant communications, increased computer capacity, and GPS capability. Radar system improvements permit AWACS aircraft operating in the pulse-Doppler mode to detect smaller, stealthier targets. A single, long-term contract awarded in 2001 provides for further improvement and management support.

### E-8 Joint STARS

**Brief:** A modified Boeing 707 equipped with a large, canoe-shaped radome mounted under the forward part of the fuselage, housing long-range, air-to-ground radar capable of locating, classifying, and tracking vehicles moving on Earth's surface out to distances in excess of 124 miles. Such data are then transmitted via data link to ground stations or other aircraft.

**Function:** Ground surveillance, battle management (BM), C2 aircraft.

**Operator:** ACC and ANG, as the blended 116th Air Control Wing.

**First Flight:** December 1988.

**Delivered:** May 1996-present

**IOC:** Dec. 18, 1997.

**Production:** 17.

**Inventory:** 17.

**Unit Location:** Robins AFB, Ga.



**E-8C Joint STARS** (TSgt. Mary Smith)



capable Block 20 aircraft, equipped with more powerful computers and an Internet protocol local area network. The first E-8C became operational in 1996, and the airframes are expected to remain airworthy until at least 2034. System improvements under way include Link 16 upgrade for data transmission to attack aircraft; enhanced radar modes; new satellite communications radios; upgrades to allow Joint STARS to assume the Airborne Battlefield Command and Control Center (ABCCC) mission of attack support to ground force commanders; and communications navigation surveillance air traffic management upgrades to permit use of optimum altitudes and flight routes in increasingly congested commercial airspace in response to new stringent international navigation standards.

**E-10**

**Brief:** A multisensor command and control aircraft (MC2A) that will provide ground surveillance and cruise missile defense as well as battlefield management command and control (BMC2).

**Function:** Ground surveillance, cruise missile defense, and BMC2 aircraft.

**Production:** five planned.



**MQ-1 Predator** (SSgt. Suzanne M. Jenkins)

**Inventory:** TBD.

**Unit Location:** TBD.

**Contractor:** Boeing (airframe).

**Power Plant:** four Pratt & Whitney PW4062 turbofans or four General Electric CF6-80C2B8F turbofans. **Accommodation:** mission crew of between 30 and 50, depending on mission.

**Dimensions:** span 170.3 ft, length 201.3 ft, tail height 55.3 ft.

**Weight:** TBD.

**Ceiling:** TBD.

**Performance:** TBD.

**COMMENTARY**

The **E-10A** is intended to be the central platform in USAF's new Command and Control Constellation, initially supplementing the E-8 Joint STARS aircraft and, possibly, assuming missions currently performed by other aircraft such as the RC-135 Rivet Joint and E-3 AWACS aircraft. The Command and Control Constellation is to be a fully connected system of sensors (land, air, and space) that will relay information automatically, using common standards and communications protocols.

USAF has ordered the first of five planned E-10As, which are based on the Boeing 767-400ER airframe, to serve as the program flying test bed. In May 2003, a team comprising Northrop Grumman, Boeing, and Raytheon was awarded a presystem development and demonstration contract for weapons system integration on the initial E-10A. Development of the demonstration radar system was awarded to Northrop Grumman in April 2004.

**E-10B** is slated to provide cruise missile defense and advanced airborne ground surveillance and targeting capability via Northrop Grumman/Raytheon's new AESA, developed under the Multiprogram Radar Technology Insertion Program (MP-RTIP), and an advanced BMC2 subsystem.

The shape of **E-10C**, which includes provision of an airborne moving target indicator with a 360-degree scan, will depend on the decision whether to co-host the airborne early warning and control (AEW&C) system on the same platform or to create a dedicated AEW&C platform.

**MQ-1 Predator**

**Brief:** A medium-altitude, long-endurance unmanned aerial vehicle (UAV), flown remotely. Joint force com-

mander multimission asset, combining imagery sensors with strike capability.

**Function:** Unmanned reconnaissance and strike aircraft.

**Operator:** ACC.

**First Flight:** July 1994.

**Delivered:** July 1994 (USAF from 1996)-present.

**IOC:** 2003.

**Production:** 100 air vehicles—ongoing.

**Inventory:** six (one MQ-1, five RQ-1).

**Unit Location:** Eglin AFB, Fla.; Indian Springs AFAF, Nev.; Nellis AFB, Nev.

**Contractor:** General Atomics Aeronautical Systems.

**Power Plant:** one Rotax 914 turbocharged engine.

**Accommodation:** unmanned system.

**Dimensions:** length 27 ft, height 7.2 ft, span 48.7 ft.

**Weight:** empty 950 lb, gross 2,250 lb.

**Ceiling:** 25,000 ft.

**Performance:** cruise speed 80 mph, up to 138 mph, endurance 24 hr (460 miles with 16 hr on station).

**Armament:** Two Hellfire missiles on multispectral targeting system (MTS)-equipped vehicles.

**COMMENTARY**

Operated by the 11th, 15th, and 17th RSs, the

**Unit Location:** Eglin AFB, Fla.; Indian Springs AFAF, Nev.

**Contractor:** General Atomics Aeronautical Systems. **Power Plant:** one Honeywell TPE-331-10T turbo-prop engine or Williams FJ44-2A turbojet engine.

**Accommodation:** unmanned system.

**Dimensions:** length 36.2 ft, span 64 ft.

**Weight:** empty 6,000 lb, gross 10,000 lb.

**Ceiling:** 50,000+ ft.

**Performance:** cruise speed 172 mph, up to 230 mph, endurance 30+ hours.

**Armament:** various air-to-surface and, possibly, air-to-air weapons.

**COMMENTARY**

Developed initially under an internal company research and development effort, USAF acquired two 7,500-lb gross UAV prototypes (known by General Atomics as Predator B) in October 2001 to evaluate their capability as a weapons platform and to carry an enhanced sensor payload. In June 2002, USAF issued a contract for a 10,000-lb prototype, based on the earlier prototypes. USAF has additionally ordered three more 10,000-lb UAVs, with the designation **MQ-9**. First preproduction version flew Oct. 17, 2003.

The MQ-9 hunter-killer UAV flies higher, faster, and has significantly greater payload capacity than the MQ-1. With its 750-lb internal payload capacity, the MQ-9 will be able to carry simultaneously numerous payloads such as a larger, more capable camera system, SAR, MTS, and other detection systems. Its 3,000-lb external payload capacity will enable it to carry a combination of munitions. USAF is exploring various weapons mixes and a possible air-to-air role.

**OC-135 Open Skies**

**Brief:** A modified C-135 aircraft that flies unarmed observation and verification flights over nations that are parties to the 1992 Open Skies Treaty.

**Function:** Reconnaissance aircraft.

**Operator:** ACC.

**First Flight:** June 1993.

**Delivered:** October 1993-96.

**IOC:** October 1993.

**Production:** three.

**Inventory:** two.

**Unit Location:** Offutt AFB, Neb.

**Contractor:** Boeing.

**Power Plant:** four Pratt & Whitney TF33-P-5 turbofans, each 16,050 lb thrust.

**Accommodation:** seating for 38.

**Dimensions:** span 131 ft, length 135 ft, height 42 ft.

**Weight:** gross 297,000 lb.

**Ceiling:** 50,000 ft (basic C-135).

**Performance:** speed: 500+ mph, unrefueled range 3,900 miles.

**COMMENTARY**

A modified version of the WC-135, used for specialized arms control treaty observation and imagery collection missions with vertical-looking and panoramic optical cameras installed in the rear of the aircraft.

**OC-135B** modifications include one vertical and two oblique KS-87E framing cameras, used for photography approximately 5,000 ft above the ground, and one KA-91C panoramic camera, which pans from side to side to provide a wide sweep for each picture, used for high-altitude photography up to approximately 35,000 ft. Data is processed and recorded by a recording and annotation system.

**RC-135**

**Brief:** Specially configured variant of the Boeing C-135 Stratolifter, having an elongated nose and cheeks containing highly advanced electronic signal collection systems. Used to acquire real-time electronic intelligence (Elint) data for theater and tactical commanders.

**Function:** Electronic reconnaissance aircraft.

**Operator:** ACC.

**First Flight:** not available.

**Delivered:** circa 1973-99.

**IOC:** circa 1973 (Rivet Joint).

**Production:** (converted).

**Inventory:** 21.

**Unit Location:** Offutt AFB, Neb.

**Contractor:** Boeing (airframe); Raytheon; Textron.

**Power Plant:** four Pratt & Whitney TF33-P-5/9 turbofans, each 18,000 lb thrust. (Replaced with CFM International CFM-56s in one W version.)

**Accommodation:** flight crew of four; 25-35 mission crew.

**Dimensions:** (Cobra Ball) span 131 ft, length 140 ft, height 42 ft; (Cobra Sent) span 135 ft, length 136 ft; (Rivet Joint) height 38 ft.

**Weight:** max gross 299,000 lb.

**Ceiling:** 35,000 ft.

**Performance:** speed 500+ mph, range, with air refueling, unlimited.

**COMMENTARY**

The 55th Wing at Offutt AFB, Neb., operates a highly specialized fleet for worldwide reconnaissance mis-

sions. All will be re-engined and are subject to ongoing modernization, with upgrade of avionics and primary mission equipment to expand capability and maintain effectiveness.

**RC-135S Cobra Ball (CB).** Three aircraft. Cobra Ball collects measurement and signature intelligence (Masint) data, providing the capability to monitor missile-associated signal activity and to track missiles during boost and re-entry phases of flight. Cobra Ball can deploy anywhere in the world in 24 hours and provide on-scene EO reconnaissance for treaty verification and theater ballistic missile proliferation. Equipment includes wide-area IR sensors, long-range optical cameras, and an advanced communications suite.

**RC-135U Combat Sent (CS).** Two aircraft. Each Combat Sent aircraft has a specifically designed signals intelligence (Sigint) suite used primarily to collect scientific and technical (S&T) electronic intelligence (Elint) data against air-, land-, and sea-based emitter systems. The accuracy of CS data is critical to the effective design, programming, and reprogramming of radar warning receivers as well as jammers, decoys, and anti-radiation missiles and to the development of effective threat simulators.



**U-2 Dragon Lady** (TSgt. Erik Gudmundson)



**RQ-4 Global Hawk** (USAF photo/Mike Charlie)

**RC-135V/W Rivet Joint (RJ).** Sixteen aircraft. Rivet Joint is a self-contained standoff airborne signals intelligence (Sigint) collection system. Its primary role is to exploit the "electronic" battlefield and deliver near-real time (NRT) intelligence-surveillance-reconnaissance (ISR) information to tactical forces, unified commanders, and national command authorities across the full spectrum of conflict. Onboard collection capabilities encompass rapid search, detection, measurement, identification, demodulation, geolocation, and fusion of data from potentially thousands of electronic emitters.

**TC-135S/W.** Used for training purposes.

**RQ-4 Global Hawk**

**Brief:** A high-altitude, long-range, long-endurance UAV.

**Function:** Unmanned reconnaissance aircraft.

**Operator:** ACC.

**First Flight:** Feb. 28, 1998.

**Delivered:** seven advanced concept technology demonstrators; two production vehicles.

**IOC:** Used operationally in Afghanistan and Iraq while still in development phase. Operational status achieved October 2004.

**Production:** LRIP. (Plans call for nine production RQ-4As before switching to the larger, more capable RQ-4B version.)

**Inventory:** six.

**Unit Location:** Beale AFB, Calif.; Eglin AFB, Fla.

**Contractor:** Northrop Grumman (prime); Raytheon.

**Power Plant:** one Rolls Royce-Allison AE 3007H turbofan, 7,600 lb thrust.

**Accommodation:** unmanned system.

**Dimensions:** length 44 ft, height 15.2 ft, span 116 ft.

**Weight:** empty 9,200 lb, gross 25,600 lb.

**Ceiling:** 65,000+ ft.

**Performance:** objective endurance up to 40 hr at a cruise speed of 400 mph and at an altitude of 65,000 ft allowing loiter on station 1,380 miles from base for 24 hr. Combat range 15,525 miles.

**Armament:** none.

**COMMENTARY**

The RQ-4A is a high-altitude endurance UAV carrying a 1,960-lb payload, incorporating EO/IR and SAR sensors that permit switching among radar, IR, and visible wavelengths as required. The objective of the RQ-4B system is to increase available payload up to 3,000 lb for future sensors/capabilities. Navigation is by GPS/INS. Global Hawk flies autonomously from

takeoff to landing, providing near-real time imagery products for tactical and theater commanders. Vehicle ground track and mission plan can be updated in real time to respond to changing air traffic control needs and/or mission collection needs.

Global Hawk began as an advanced concept technology demonstrator in 1995. Engineering and manufacturing development (EMD) was approved in March 2001. While still a development system, Global Hawk deployed operationally to support Enduring Freedom in Afghanistan in November 2001, flying more than 50 missions and 1,000 combat hours.

Global Hawk provides continuous, all-weather, day/night, wide area surveillance. It will operate in low-to-moderate air defense threat environments with the ability to fly above or stand off from enemy defenses. The Navy is purchasing two Global Hawks for a maritime demonstration.

**U-2 Dragon Lady**

**Brief:** Single-seat, single-engine, high-altitude endurance reconnaissance aircraft carrying a wide variety of sensors and cameras, providing continuous day or night, high-altitude, all-weather area surveillance in direct support of US forces.

**Function:** High-altitude reconnaissance.

**Operator:** ACC.

**First Flight:** August 1955 (U-2); 1967 (U-2R); October 1994 (U-2S).

**Delivered:** 1955-October 1989.

**IOC:** circa 1956.

**Production:** 35 (U-2S/ST).

**Inventory:** 34.

**Unit Location:** Beale AFB, Calif.

**Contractor:** Lockheed Martin.

**Power Plant:** F118-GE-101 turbojet.

**Accommodation:** one (two for trainer).

**Dimensions:** span 103 ft, length 63 ft, height 16 ft.

**Weight:** gross 40,000 lb.

**Ceiling:** above 70,000 ft.

**Performance:** speed 475 mph; range more than 4,500 miles; max endurance 10+ hr.

**COMMENTARY**

The U-2 is the Air Force's premier high-altitude reconnaissance platform, capable of carrying multi-int sensors simultaneously, making it USAF's only truly operational multi-intelligence platform and a key performer in combat operations.

Although the U-2 was designed initially in the 1950s, current aircraft were produced primarily in the 1980s, when the production line was reopened to produce the TR-1, a significantly larger and more capable version than the earlier aircraft. Deliveries ended in October 1989.

**U-2R** (single-seat) and **U-2RT** (two-seat) aircraft. In 1992, all existing U-2s and tactical TR-1s were consolidated under the designation U-2R.

**U-2S** (single-seat) and **U-2ST** (two-seat). The current designations of all 34 aircraft (29 U-2S mission aircraft, five U-2ST trainers) in the inventory. Conversion to S model configuration began in October 1994. Included in the on-going \$1.5 billion improvement program are new F118-GE-101 engines, a complete electrical system replacement, a new glass cockpit using multifunction displays (MFDs), a digital autopilot, an electro-optical view sight, and a new electronic warfare system. Sensor upgrades include the ASARS-2A radar sensor, which provides enhanced imaging modes and improves geo-location accuracy; the SYERS-2 EO imagery system, which provides multispectral and IR capability; enhanced RF-intelligence capability; and new data links enabling the U-2 to connect in near real time with network-centric hubs as well as line of sight ground stations, airborne data relays, and beyond line of sight satellite data relays.

NASA has two ER-2 versions of the U-2 used for high-altitude scientific experiments and atmospheric research, including investigation of global ozone depletion.

**WC-130 Hercules**

**Brief:** A high-wing, medium-range aircraft flown by AFRC for weather reconnaissance missions. It flies into the eye of tropical cyclones or hurricanes, collecting weather data from within the storm's environment.

**Function:** Weather reconnaissance aircraft.

**Operator:** AFRC.

**First Flight:** circa 1959.

**Delivered:** October 1999-2002.

**IOC:** 1959.

**Production:** no new-build WC-130H; 10 WC-130J.

**Inventory:** 20 (10 H, 10 J).

**Unit Location:** AFRC: Keesler AFB, Miss.

**Contractor:** Lockheed Martin.

**Power Plant:** WC-130J: four Rolls Royce AE2100D3 turboprops, each 4,500 shp.

**Accommodation:** six.

**Dimensions:** WC-130J: span 132.6 ft, length 97.8 ft, height 38.9 ft.

**Weight:** WC-130J: gross 175,000 lb.

**Ceiling:** WC-130J: 30,500 ft.

**Performance:** speed 374 mph at 20,000 ft.

**COMMENTARY**

The WC-130 is flown by AFRC organizations known as the Hurricane Hunters. The hurricane reconnaissance area includes the Atlantic Ocean, Caribbean Sea, Gulf of Mexico, and central Pacific Ocean areas.

**WC-130B/E.** Earlier version C-130 modifications used for weather reconnaissance. Now retired.

**WC-130H.** Improved version, operated by the 53rd WRS for weather reconnaissance duties, including penetration of tropical storms, to obtain data for forecasting storm movements. Equipment includes two external 1,400-gallon fuel tanks, an internal 1,800-gallon fuel tank, and updated Allison T56-A-15 turboprops, each 4,910 shp. WC-130H aircraft are being converted to HC-130Ps.

**WC-130J.** Weather-reconnaissance version of the latest C-130 model, featuring improved radar, four Rolls Royce AE2100D3 turboprops, and Dowty 391 six-bladed composite propellers. First of 10 aircraft replacing the WC-130H was delivered Oct. 12, 1999.

An average weather reconnaissance mission might

last 11 hours and cover almost 3,500 miles while the crew collects and reports weather data every minute. Results are transmitted via satellite to the National Hurricane Center, Miami.

## Special Duty Aircraft

### E-4B National Airborne Operations Center

**Brief:** A four-engine, swept-wing, long-range, high-altitude airplane providing a highly survivable C3 center allowing national/defense leaders to direct US forces, execute emergency war orders, and coordinate actions by civil authorities.

**Function:** Airborne operations center.

**Operator:** ACC.

**First Flight:** June 13, 1973 (E-4A); June 10, 1978 (E-4B).

**Delivered:** December 1974-85.

**IOC:** December 1974 (E-4A); January 1980 (E-4B).

**Production:** four.

**Inventory:** four.

**Unit Location:** Offutt AFB, Neb.

**Contractor:** Boeing; Rockwell; Raytheon E-Systems.

**Power Plant:** four General Electric CF6-50E2 turbofans, each 52,500 lb thrust.

**Accommodation:** up to 114 (63 crew/battle staff; 51 passengers).

**Dimensions:** span 195.7 ft, length 231.3 ft, height 63.4 ft.

**Weight:** gross 800,000 lb.

**Ceiling:** above 40,000 ft.

**Performance:** 6,900+ miles; unrefueled endurance in excess of 12 hr; with aerial refueling up to 72 hr.

#### COMMENTARY

A militarized version of the Boeing 747-200, E-4B aircraft perform the National Airborne Operations Center (NAOC) mission. The E-4B fleet provides a survivable C3 platform throughout the full threat spectrum, including sustained operations in a nuclear environment. First operational mission was flown in March 1980.

E-4Bs are hardened against the effects of nuclear

the E-4B aircraft will effectively execute its NAOC mission, providing C3 in the homeland security environment and beyond for the foreseeable future.

### EC-130E/J

**Brief:** A heavily modified C-130 with variants used for battlefield command, EW, and electronic combat.

**Function:** C2; psychological warfare.

**Operator:** ANG.

**First Flight:** January 1990.

**Delivered:** March 1990.

**IOC:** December 1990.

**Production:** (no USAF new-build EC-130Es); five (J).

**Inventory:** seven (two E, five J).

**Unit Location:** ANG: Harrisburg Arpt., Pa.

**Contractor:** Lockheed Martin; Raytheon; General Dynamics.

**Power Plant:** four Allison T56-A-15 turboprops, each 4,910 shp; (EC-130E) T-56-A-1S turboprops, each 4,200 shp; (EC-130J) four Rolls Royce-Allison AE2100D turboprops, each 4,591 shp.

**Accommodation:** five flight crew, six mission.

**Dimensions:** EC-130J: span 132.6 ft, length 97.8 ft, height 38.9 ft.

**Weight:** EC-130J: gross 175,000 lb.

**Ceiling:** EC-130J: 30,500 ft.

**Performance:** speed 299 mph, range in excess of 2,100 miles; (C-130J) 393 mph, range 4,140 miles.

#### COMMENTARY

**EC-130E ABCCC** Airborne Battlefield Command and Control Center. Seven aircraft were updated by Unisys to ABCCC III standard. The advanced JTIDS received data transmitted by AWACS aircraft and other systems, enabling the crew to see a real-time picture of air operations over a combat area. Now retired.

**EC-130E Commando Solo.** Version used by the ANG as a broadcasting station for psychological warfare operations. Specialized modifications include enhanced navigation systems, self-protection equipment, and worldwide color television configuration.

**EC-130J Commando Solo II.** Five specialized versions of the latest-model C-130 aircraft, ordered to replace now-retired Es, with current mission equipment transferred from the older aircraft. Entered service mid-2003 with the 193rd SOW (ANG).

Commando Solo aircraft have been used in numerous military operations, including Iraqi Freedom. They also have a role in civil emergencies. Secondary mission is electronic attack in the military frequency spectrum.

### EC-130H Compass Call

**Brief:** A heavily modified C-130 for electronic combat.

**Function:** Electronic warfare.

**Operator:** ACC.

**First Flight:** 1981.

**Delivered:** 1982.

**IOC:** 1983; (Block 30) February 1999.

**Production:** (converted).

**Inventory:** 14.

**Unit Location:** Davis-Monthan AFB, Ariz.

**Contractor:** Lockheed Martin.

**Power Plant:** four Allison T56-A-15 turboprops, each 4,910 shp.

**Accommodation:** standard crew 13.

**Dimensions:** span 132.6 ft, length 99 ft, height 38 ft.

**Weight:** 155,000 lb.

**Ceiling:** 25,000 ft.

**Performance:** speed 374 mph at 20,000 ft.

#### COMMENTARY

A variant used as an airborne communications jamming and information warfare platform. Modifications include ECM system and air refueling capability. Further upgrades, including an updated receiver subsystem, will improve reliability and expand the EC-130H's offensive counterinformation (OCI) capability against modern C2 systems. Completion expected FY10.

## Tanker Aircraft

### HC-130N/P

**Brief:** An extended-range, combat search and rescue (CSAR)-configured C-130 that extends the range of rescue helicopters through in-flight refueling and performs tactical delivery of pararescue jumper (PJ) specialists and/or equipment in hostile environments.

**Function:** Aerial refueling/transport.

**Operator:** AETC, AFSOC, ANG, AFRC.

**First Flight:** Dec. 8, 1964 (as HC-130H).

**Delivered:** from 1965.

**IOC:** 1986.

**Production:** (converted).

**Inventory:** 32.

**Unit Location:** Active: Davis-Monthan AFB, Ariz., Kirtland AFB, N.M., Moody AFB, Ga. ANG: Francis S. Gabreski Arpt., N.Y., Kulis ANGB, Alaska. AFRC: Patrick AFB, Fla.

**Contractor:** Lockheed (now Lockheed Martin).

**Power Plant:** four Allison T56-A-15 turboprops, each 4,910 shp.

**Accommodation:** four flight crew, plus mission crew.

**Dimensions:** span 132.6 ft, length 98.8 ft, height 38.5 ft.

**Weight:** gross 155,000 lb.

**Ceiling:** 33,000 ft.

**Performance:** speed 289 mph, range more than 4,000 miles.

#### COMMENTARY

The HC-130 can perform extended visual/electronic searches over land or water and operate from unimproved airfields. A three-man PJ team, trained in emergency trauma medicine, harsh environment survival, and assisted evasion, is part of the normal mission crew complement.

Combat air forces' HC-130 aircraft are equipped with



EC-130J Commando Solo II (SrA. Matt Schwartz)

explosions, including electromagnetic pulse, and have in-flight refueling capability. A 1,200-kVA electrical system supports advanced system electronics as well as state-of-the-art communications and data processing equipment such as EHF Milstar satellite terminals and six-channel International Maritime Satellite (Inmarsat). A triband radome also houses the E-4B's superhigh frequency (SHF) frequency division multiple access (FDMA) communications antenna, the only such system on an airborne platform.

The E-4B system is capable of linking with commercial telephone and radio networks and could be used for radio broadcasts to the general population. E-4Bs also support the Federal Emergency Management Agency (FEMA).

In early 2000, the E-4B entered the SDD phase of a modernization program aimed at updating the electronic infrastructure supporting the aircraft's primary mission equipment and increasing the bandwidth of external communications and onboard data transfer. These updates, along with changes to the aircraft's interior configuration, internal noise reduction modifications, BM improvements, and Global Air Traffic Management (GATM) avionics modifications, ensure



KC-135R Stratotanker (MSgt. Mark Bucher)



**KC-130P Combat Shadow** (MSgt. Michael Farris)

an integrated GPS/INS navigation package, radar/mis-  
sile warning receivers, and chaff/flare countermea-  
sures dispensers. Some aircraft have FLIR systems  
and personnel locating systems (PLS) compatible with  
aircrew survival radios. Additional modifications in-  
clude an improved digital low-power color radar, inte-  
grated satellite communications radio, NVG-compat-  
ible interior/exterior lighting, and cockpit armor. The  
C-130 avionics modernization program (AMP) provides  
for complete update of the HC-130 avionics. Four  
retired EC-130E ABCCC and 10 WC-130H aircraft are  
converting to HC-130 standard.

**KC-10 Extender**

**Brief:** A modified McDonnell Douglas DC-10 that  
combines in a single aircraft the operations of aerial  
refueling and long-range cargo transport.

**Function:** Aerial refueling/transport.

**Operator:** AMC, AFRC (assoc.).

**First Flight:** April 1980.

**Delivered:** March 1981-April 1990.

**IOC:** August 1982.

**Production:** 60.

**Inventory:** 59.

**Unit Location:** McGuire AFB, N.J., Travis AFB, Cal-  
if., AFRC: (assoc.) Travis AFB, Calif., McGuire AFB,  
N.J.

**Contractor:** McDonnell Douglas (now Boeing).

**Power Plant:** three General Electric CF6-50C2 turbo-  
fans, each 52,500 lb thrust.

**Accommodation:** crew of four; additional seating  
possible for up to 75 persons with 17 pallets; max 27  
pallets; max cargo payload 169,409 lb.

**Dimensions:** span 165.4 ft, length 181.6 ft, height  
58.1 ft.

**Weight:** gross 593,000 lb.

**Ceiling:** 42,000 ft.

**Performance:** cruising speed Mach 0.825, range  
with max cargo 4,400 miles.

**COMMENTARY**

The KC-10 combines the tasks of tanker and cargo  
aircraft in a single unit, enabling it to support worldwide  
fighter deployments, strategic airlift, strategic recon-  
naissance, and conventional operations.

The KC-10 can be air refueled by a KC-135 or an-  
other KC-10, increasing its range and diminishing the  
need for forward bases, leaving vital fuel supplies in  
the theater of operations untouched.

**KC-10A** is a DC-10 Series 30CF, modified to include  
fuselage fuel cells, an air refueling operator's station,  
aerial refueling boom and integral hose reel/drogue  
unit, a receiver refueling receptacle, and military avi-  
onics. Wing-mounted pods enhance the aircraft's ca-  
pabilities. Other modifications include the addition of  
communications, navigation, and surveillance equip-  
ment to meet civil air traffic control requirements.

Because it has both types of tanker refueling equip-  
ment installed, the KC-10A can service USAF, USN,  
USMC, and allied aircraft on the same mission. Special  
lighting permits night operations.

**KC-135 Stratotanker**

**Brief:** A short- to medium-range tanker aircraft, meet-  
ing the air refueling needs of USAF bomber, fighter,  
cargo, and reconnaissance forces. It also supports  
USN, USMC, and allied aircraft.

**Function:** Aerial refueling/airlift.

**Operator:** AETC, AFMC, AMC, PACAF, USAFE,  
ANG, AFRC.

**First Flight:** August 1956.

**Delivered:** January 1957-66.

**IOC:** June 1957, Castle AFB, Calif.

**Production:** 732.

**Inventory:** 534.

**Unit Location:** Altus AFB, Okla., Fairchild AFB, Wash.,  
Grand Forks AFB, N.D., Kadena AB, Japan, MacDill  
AFB, Fla., McConnell AFB, Kan., RAF Mildenhall, UK,  
Robins AFB, Ga. ANG: 21 units. AFRC: nine units.

**Contractor:** Boeing.

**Power Plant:** KC-135R/T: four CFM International  
F108-CF-100 turbofans, each 22,224 lb thrust; KC-  
135E: four Pratt & Whitney TF33-PW-102 turbofans,  
each 18,000 lb thrust.

**Accommodation:** crew of four; up to 80 passengers.  
**Dimensions:** span 130.8 ft, length 136.2 ft, height  
38.3 ft.

**Weight:** empty 119,231 lb, gross 322,500 lb (KC-  
135E 301,600 lb).

**Ceiling:** 50,000 ft.

**Performance:** max speed at 30,000 ft 610 mph,  
range with max fuel 11,015 miles.

**COMMENTARY**

Mainstay of the USAF tanker fleet, the long-serving  
KC-135 is similar in size and appearance to commercial  
707 aircraft but was designed to military specifications,  
incorporating different structural details and materials.  
The KC-135 fuel tanks are located in the "wet wings" and  
in fuel tanks below the floor in the fuselage.

**KC-135A.** Original version with J57 turbojets. USAF  
built 732, since modified to other standards.

**KC-135E/D.** The JT3D re-engining program upgraded  
USAF, AFRC and ANG KC-135As to KC-135E stan-  
dard with JT3D turbofans and related components  
removed from surplus commercial 707s; fuel carrying  
capacity increased by 20 percent. One hundred and  
fifteen KC-135Es remain in service with the ANG and  
AFRC, representing some of the oldest aircraft in the  
USAF inventory. Four KC-135Ds are similar but have  
minor configuration differences as they were converted  
from RC-135A aircraft.

**KC-135R/T.** Designation of re-engined KC-135A/Es  
with F108 turbofans. They embody modifications to 25  
major systems and subsystems and not only carry  
more fuel farther but have reduced maintenance costs,  
are able to use shorter runways, and meet Stage III  
requirements. The first KC-135R flight was in October  
1982, and redeliveries began in July 1984. KC-135T  
aircraft (formerly KC-135Q) were capable of refueling  
the now-retired SR-71s and retain the capability to

carry different fuels in the wing and body tanks. Eight  
KC-135Rs are air refuelable. Twenty KC-135Rs have  
wing-mounted refueling pods for enhanced refueling of  
USN and NATO aircraft.

Ongoing modifications are extending the capability  
and operational utility of the KC-135. The Pacer CRAG  
avionics modernization program installed a new com-  
pass, radar, and GPS navigation systems, a traffic alert  
and collision avoidance system (TCAS), and new digi-  
tal multifunctional cockpit displays. The Global Air  
Traffic Management (GATM) modification further im-  
proves the avionics, ensuring future access into pre-  
mium airspace. Forty KC-135R/T aircraft are outfitted  
with the capability to relay Link 16 tactical information  
beyond other aircrafts' line of sight. USAF began a full  
assessment of the entire KC-135 fleet in late 2004.

**MC-130P Combat Shadow**

**Brief:** Aircraft that flies clandestine or low-visibility,  
low-level missions into denied areas to provide air refu-  
eling for special operations forces (SOF) helicopters or  
to air-drop small special operations teams, small bundles,  
and zodiac and combat rubber raiding craft.

**Function:** Air refueling for SOF helicopters/airdrop.

**Operator:** AETC, AFSOC, ANG, AFRC.

**First Flight:** Dec. 8, 1964 (as HC-130H).

**Delivered:** from 1965.

**IOC:** 1986.

**Production:** (converted).

**Inventory:** 27.

**Unit Location:** Active: Eglin AFB, Fla., Kadena AB,  
Japan, Kirtland AFB, N.M., RAF Mildenhall, UK. ANG:  
Kulis ANGB, Alaska, Moffett Federal Airfield, Calif.  
AFRC: Duke Field, Fla.

**Contractor:** Lockheed Martin (airframe); Boeing.

**Power Plant:** four Allison T56-A-15 turboprops, each  
4,910 shp.

**Accommodation:** four flight crew, plus four mission  
crew.

**Dimensions:** span 132.6 ft, length 98.8 ft, height  
38.5 ft.

**Weight:** gross 155,000 lb.

**Ceiling:** 33,000 ft.

**Performance:** speed 289 mph, range more than  
4,000 miles.

**COMMENTARY**

**MC-130P Combat Shadow** aircraft are currently tasked  
with clandestine formation or single-ship intrusion of  
hostile territory to provide aerial refueling of special  
operations helicopters and the infiltration, exfiltration,  
and resupply of SOF by airdrop or air-land operations.  
To perform these missions, depending upon the enemy  
threat, crews navigate using both visual and electronic  
means or visual means only. Primary emphasis is on  
NVG operations.

Modifications include improved secure communi-  
cations, advanced integrated navigation equipment, in-  
cluding digital scan radar, ring-laser gyro INS, FLIR,  
GPS, and dual nav stations, and missile warning sys-  
tems and countermeasures for refueling missions in  
hostile environments. Some aircraft have been mod-  
ified with an in-flight refueling system allowing them to  
be air refuelable.

**Strategic  
Transports**

**C-5 Galaxy**

**Brief:** A heavy-lift, air refuelable cargo transport for



**C-5 Galaxy** (MSgt. Val Gempis)

massive strategic airlift over long ranges, including outside cargo. Supports special operations missions.

**Function:** Cargo and troop transport.

**Operator:** AETC, AFMC, AMC, ANG, AFRC.

**First Flight:** June 30, 1968.

**Delivered:** October 1969-April 1989.

**IOC:** September 1970.

**Production:** 131.

**Inventory:** 118.

**Unit Location:** Active: Altus AFB, Okla., Dover AFB, Del., Travis AFB, Calif. ANG: Stewart Arpt., N.Y. AFRC: Dover AFB, Del., Lackland AFB, Tex., Travis AFB, Calif., Westover ARB, Mass.

**Contractor:** Lockheed.

**Power Plant:** four General Electric TF39-GE-1C turbofans, each 41,000 lb thrust.

**Accommodation:** normal crew of six (two pilots, two engineers, and two loadmasters), plus rest area for 15 (relief crew, etc.) and seating for 73. There is no piece of Army combat equipment the C-5 can't carry. Possible loads: six Apache helicopters, two M1 main battle tanks (each weighing 135,400 lb), six Bradley vehicles, three CH-47 helicopters, the 74-ton mobile bridge, a quarter-million pounds of relief supplies, or a maximum of 340 passengers in an airbus configuration. Airdrop capability for single platforms weighing up to 42,000 lb.

**Dimensions:** span 222.8 ft, length 247.9 ft, height 65.1 ft.

**Weight:** empty 374,000 lb, gross 769,000 (wartime 840,000) lb.

**Ceiling:** 45,000 ft.

**Performance:** max speed at 25,000 ft 571 mph, 35,750 ft, T-O run at S/L 8,300 ft, landing run, max landing weight at S/L 2,380 ft, range with max payload 3,434 miles, range with max fuel 7,245 miles. Normal cruising speed at altitude 518 mph (Mach 0.77), unlimited range with in-flight air refueling.

upgraded aircraft flew December 2002. Additionally, the Air Force has established a C-5M reliability enhancement and re-engining program (RERP) and contracted an SDD for a 112 C-5A/B/C aircraft to take advantage of an estimated service life through 2040. Three production representative C-5Ms will be completed in 2006, flight test will continue through FY07, with OT&E completing in FY08. Program completion with all 112 aircraft is expected 2018. To enhance force protection, a number of C-5Bs have been equipped with a missile defense system.

#### C-17 Globemaster III

**Brief:** A heavy-lift, air refuelable cargo transport for intertheater (strategic) and intratheater (tactical) direct delivery airlift of all classes of military cargo, including outside items.

**Function:** Cargo and troop transport.

**Operator:** AETC, AFMC, AMC, ANG, AFRC.

**First Flight:** Sept. 15, 1991.

**Delivered:** June 1993-July 2008 (contractual).

**IOC:** Jan. 17, 1995.

**Production:** 180 (contractual).

**Inventory:** 126.

**Unit Location:** Active: Altus AFB, Okla., Charleston AFB, S.C., Edwards AFB, Calif., McChord AFB, Wash., McGuire AFB, N.J. AFRC (assoc.): Charleston AFB, S.C., McChord AFB, Wash., McGuire AFB, N.J. ANG: Jackson, Miss. Planned: Active/AFRC-assoc.: Dover AFB, Del., Elmendorf AFB, Alaska. Travis AFB, Calif. Active/ANG-assoc.: Hickam AFB, Hawaii. AFRC: March ARB, Calif.

**Contractor:** Boeing.

**Power Plant:** four Pratt & Whitney F117-PW-100 turbofans, each 40,440 lb thrust.

**Accommodation:** normal flight crew of three (two pilots plus loadmaster); additional pilot may be carried. Provisions for full range of military airlift missions, incl

ously delivered aircraft. In October 2002, the C-17 assumed the special operations low level (SOLL) mission previously supported by the C-141. Enhancements include SOLL II communications suites and carry-on radio suites. C-17s have flown numerous operational and humanitarian missions since entering operational service, including peacekeeping operations in Bosnia. The C-17 was the only aircraft capable of delivering outside cargo into austere operations in Afghanistan and Iraq. C-17s performed their first operational strategic brigade airdrop in March 2003, when a formation of 15 aircraft delivered a US Army brigade, complete with equipment, directly into northern Iraq. Block 15 aircraft were delivered in 2004, Block 16 are scheduled in 2005, and Block 17 in 2006, which marks the last block upgrade for the 180-aircraft fleet. Full retrofit up to Block 17 of previously delivered aircraft is scheduled to begin in 2007 and will take approximately 10 years.

#### C-141 Starlifter

**Brief:** Workhorse of the US airlift force for 40 years, the Starlifter can project combat forces over long distances, inject those forces and their equipment either by air-land or airdrop, resupply these employed forces, and extract the sick and wounded from the hostile area to advanced medical facilities. Primary strategic special operations and airdrop platform.

**Function:** Long-range, air refuelable troop and cargo airlift.

**Operator:** AFRC.

**First Flight:** Dec. 17, 1963.

**Delivered:** October 1964-June 1982.

**IOC:** May 1965.

**Production:** 285.

**Inventory:** 20.

**Unit Location:** March ARB, Calif., McGuire AFB, N.J., Wright-Patterson AFB, Ohio.

**Contractor:** Lockheed Martin.

**Power Plant:** four Pratt & Whitney TF33-P-7 turbofans, each 21,000 lb thrust.

**Accommodation:** crew of five; cargo on 13 standard 463L pallets. Alternative freight or vehicle payloads, 200 fully equipped troops, 155 paratroops, or 103 litter patients plus attendants.

**Dimensions:** span 159.9 ft, length 168.3 ft, height 39.2 ft.

**Weight:** operating payload 38,000 lb; max payload 68,725 lb normal, 89,000 lb emergency war planning; gross 325,000 lb normal, 344,000 lb emergency war planning.

**Ceiling:** 45,000 ft.

**Performance:** max cruising speed 466 mph, range 5,290 miles without air refueling.

#### COMMENTARY

Longtime mainstay of USAF's airlift fleet, the C-141 was the first jet aircraft designed to meet military standards as a troop and cargo carrier. The last active duty C-141 retired in September 2004, and with the continuing deployment of C-17 aircraft, all will be retired by 2006.

**C-141A** entered service with MAC in April 1965; 285 were built, some of which were structurally modified to accommodate the Minuteman ICBM.

**C-141B** is a stretched C-141A with in-flight refueling capability. All C-141As (except four AFMC aircraft used for test purposes) were lengthened by 23 ft 4 in to expand lift capacity. First C-141B flew March 1977 and redeliveries took place between December 1979 and June 1982. The modification gave USAF the equivalent of 90 additional C-141A aircraft. Subsequent improvements include structural upgrades, a state-of-the-art autopilot and all-weather landing system, and improved airdrop systems. Modification of 13 C-141Bs increased their SOLL capability and survivability.

**C-141C** is a C-141B modified with computerized glass-cockpit instrumentation and digital flight-management system, with integrated GPS data for navigation and modern navigation safety equipment. The first version, which rolled out at Warner Robins ALC, Ga., Oct. 1, 1997, was assigned to AFRC's 452nd AMW.



C-17 Globemaster III (TSgt. Scott F. Reed)

#### COMMENTARY

One of the world's largest aircraft, the C-5 is able to carry unusually large and heavy cargo for intercontinental ranges at jet speeds. It can take off and land in relatively short distances and taxi on substandard surfaces during emergency operations. Front and rear cargo openings permit simultaneous drive-through loading and off-loading.

**C-5A.** USAF took delivery of 81 of these basic models between December 1969 and May 1973. A major wing modification was subsequently undertaken, extending the aircraft's service life by 30,000 flight hours. Additionally, the avionics subsystems developed for the C-5B have been incorporated into the C-5A fleet. One ANG and two AFRC squadrons are C-5A-equipped. The reliability and maintainability of the C-5A version is under assessment. A total of 14 C-5As, including the 11 oldest, are to be retired by end of 2005.

**C-5B.** Generally similar to the C-5A but embodies all the improvements introduced since completion of C-5A production, including the strengthened wings, improved turbofans, and updated avionics, with color weather radar and triple INS. The first C-5B flew for the first time in September 1985 and was delivered to Altus AFB, Okla., in January 1986.

**C-5C.** Two C-5As assigned to Travis AFB, Calif., were modified to carry outside space cargo for NASA by extending the cargo bay and modifying the aft doors.

All USAF Galaxies are undergoing a complete avionics modernization program (AMP) that will install a state-of-the-art cockpit and ensure global access navigation safety compliance by the end of 2006; first

capacity for up to 189 passengers, 102 paratroops, or 36 litters; range of military cargo incl tanks and up to three AH-64A helicopters; three Bradley vehicles; one M1A2 main battle tank with other equipment; airdrop capability for single platforms weighing up to 60,000 lb; palletized passenger seats.

**Dimensions:** span over winglet tips 169.8 ft, length 173.9 ft, height 55.1 ft.

**Weight:** empty 277,000 lb, max payload 170,900 lb, gross 585,000 lb (extended range).

**Ceiling:** 45,000 ft.

**Performance:** normal cruising speed 484 mph at 35,000 ft or 518 mph (Mach .77) at 28,000 ft, unrefueled range with 160,000-lb payload 2,760 miles, additional 690 miles with extended-range fuel containment system (ERFCS), unlimited with refueling.

#### COMMENTARY

Developed to meet US force projection requirements, the C-17 is able to operate routinely into small, austere airfields (3,000 ft x 90 ft) previously restricted to C-130s and provides the first capability to air-land or air-drop outside cargo directly to the tactical environment.

**C-17A** is the first military transport to feature a full digital fly-by-wire control system and two-person cockpit, with two full-time, all-function HUDs and four multi-function electronic displays. Block 12 aircraft, delivered from 2001, have the ERFCS upgrade. Other C-17 improvements include a terrain awareness warning system (TAWS) and video integrated processor (VIP). Defensive systems include laser for IR missile jamming and flare systems. Ongoing retrofit/modernizations include adding TAWS and upgrades to GATM to previ-

## Theater and Special Use Transports

#### C-9 Nightingale

**Brief:** A twin-engine, medium-range, swept-wing jet aircraft used for DV duties.

**Function:** DV duties.

**Operator:** AMC, USAFE, AFRC.

**First Flight:** August 1968.

**Delivered:** August 1968-February 1975.

**IOC:** circa 1968.

**Production:** 24.

**Inventory:** eight.

**Unit Location:** Andrews AFB, Md., Ramstein AB, Germany. AFRC: (assoc.) Scott AFB, Ill.

**Contractor:** Boeing (McDonnell Douglas).

**Power Plant:** two Pratt & Whitney JT8D-9A turbofans, each 14,500 lb thrust.

**Accommodation:** crew of three.

**Dimensions:** span 93.2 ft, length 119.2 ft, height 27.4 ft.

**Weight:** gross 108,000 lb.

**Ceiling:** 35,000 ft.

**Performance:** max cruising speed at 25,000 ft 565 mph, range 2,500 miles.

**COMMENTARY**

**C-9A.** A derivative of the DC-9 Series 30 commercial airliner, the C-9A was the only USAF aircraft modified specifically for the aeromedical evacuation mission, a role now undertaken by C-130, C-141, and C-17 aircraft. The one remaining C-9A provides distinguished visitor (DV) airlift in Europe. Because of the critical nature of its mission, the aircraft carries a flight mechanic and a small supply of spares.

**C-9C.** Three specially configured C-9s were delivered to Andrews AFB, Md., in 1975 for the special air mission (SAM) supporting the President and other US government officials. Upgrades include improvements to the passenger communications equipment, GATM, TAWS, and vertical separation equipment.

**C-12 Huron**

**Brief:** Aircraft to provide airlift support for attache and military advisory groups worldwide.

**Function:** Special airlift.

**Operator:** AFMC, PACAF.

**First Flight:** Oct. 27, 1972 (Super King Air 200).

**Delivered:** 1974-late 1980s.

**IOC:** circa 1974.

**Production:** 88.

**Inventory:** 28.

**Unit Location:** Elmendorf AFB, Alaska, Osan AB, South Korea, various overseas embassies.

**Contractor:** Beech.

**Power Plant:** (C-12J) two Pratt & Whitney Canada PT6A-65B turboprops, each 1,100 shp.

**Accommodation:** crew of two; C-12C: up to eight passengers; C-12J: up to 19 passengers.

**Dimensions:** (C-12J) span 54.5 ft, length 43.8 ft, height 15 ft.

**Weight:** (C-12J) empty 9,850 lb, gross 16,600 lb.

**Ceiling:** (C-12J) 25,000 ft.

**Performance:** (C-12J) max cruising speed at 16,000 ft 307 mph, range with 10 passengers 1,806 miles.

**COMMENTARY**

**C-12C.** Re-engined C-12As, with PT6A-41 turboprops, deployed to overseas embassies.

**C-12D.** Similar to C model and also deployed to overseas embassies.

**C-12F.** With updated PT6A-42 engines, can support medical airlift.

**C-12J.** A military version of the larger Beechcraft Model 1900, operated by PACAF.

**C-20 Gulfstream**

**Brief:** A twin-engine turboprop aircraft acquired to provide airlift for high-ranking government and DOD officials.

**Function:** Operational support airlift; special air missions.

**Operator:** AMC, USAFE.

**First Flight:** December 1979.

**Delivered:** September 1983-89.

**IOC:** circa 1983.

**Production:** not available.

**Inventory:** 10.

**Unit Location:** Andrews AFB, Md., Ramstein AB, Germany.

**Contractor:** Gulfstream.

**Power Plant:** C-20A/B: two Rolls Royce-Spey MK511-8 turboprops, each 11,400 lb thrust; C-20H: two Rolls Royce-Tay MK611-8 turboprops, each 13,850 lb thrust.

**Accommodation:** crew of five; 12 passengers.

**Dimensions:** span 77.8 ft; length (C-20A/B) 83.1 ft, (C-20H) 88.3 ft; height 24.3 ft.

**Weight:** C-20A/B gross 69,700 lb; C-20H gross 74,600 lb.

**Ceiling:** 45,000 ft.

**Performance:** max cruising speed 576 mph, range 4,800 miles.

**COMMENTARY**

**C-20A.** Three Gulfstream III transports were acquired to replace aging C-140B aircraft. They provided USAFE's operational support airlift fleet with intercontinental range and ability to operate from short runways. Retired in September 2002.

**C-20B.** Seven C-20B versions, with advanced mission communications equipment and revised interior, were acquired in the late 1980s. Two C-20B aircraft have been retired.

**C-20H.** Two Gulfstream IV SP aircraft, with advanced-technology flight-management systems and upgraded Rolls Royce engines, were acquired by USAF to meet

expanding SAM requirements. The two C-20H aircraft were reassigned to USAFE to replace retired C-20As.

Upgrade for C-20B/H aircraft includes GPS, vertical separation equipment, GATM, and TCAS.

**C-21**

**Brief:** Aircraft designed to provide cargo and passenger airlift and transport litters during medical evacuations.

**Function:** Pilot seasoning, passenger and cargo airlift.

**Operator:** AETC, AMC, PACAF, USAFE, ANG.

**First Flight:** January 1973.

**Delivered:** April 1984-October 1985.

**IOC:** April 1984.

**Production:** 84.

**Inventory:** 77.

**Unit Location:** Andrews AFB, Md., Keesler AFB, Miss., Langley AFB, Va., Maxwell AFB, Ala., Offutt AFB, Neb., Peterson AFB, Colo., Ramstein AB, Germany, Randolph AFB, Tex., Scott AFB, Ill., Stuttgart, Germany, Wright-Patterson AFB, Ohio, Yokota AB, Japan.

**Contractor:** Gates Learjet.

**Power Plant:** two AlliedSignal TFE731-2 turbofans, each 3,500 lb thrust.

**Accommodation:** crew of two and up to eight passengers or 3,153 lb cargo. Convertible to aeromedical evacuation configuration.

**Dimensions:** span 39.5 ft, length 48.6 ft, height 12.2 ft.

**Weight:** empty, equipped 10,119 lb, gross 18,300 lb.

**Ceiling:** 51,000 ft.

**Performance:** max level speed at 25,000 ft 542 mph, range with max passenger load 2,306 miles, with max cargo load 1,653 miles.

**COMMENTARY**

**C-21A** aircraft provide operational support airlift for time-sensitive movement of people and cargo throughout the US and the Pacific and European Theaters, including aeromedical missions if required. Upgrades include GATM and TCAS.

**C-32**

**Brief:** A modified Boeing 757-200 used to provide transportation for the vice president, Cabinet, Congressional members, and other high-ranking US and foreign officials.

**Function:** VIP air transport.

**Operator:** AMC.

**First Flight:** Feb. 19, 1982 (USAF Feb. 11, 1998).

**Delivery:** June-December 1998.

**IOC:** 1998.

**Production:** six.

**Inventory:** four.

**Unit Location:** Andrews AFB, Md.

**Contractor:** Boeing.

**Power Plant:** two Pratt & Whitney PW2040 turbofans, each 41,700 lb thrust.

**Accommodation:** 16 crew and 45 passengers.

**Dimensions:** span 124.8 ft, length 155.2 ft, height 44.5 ft.

**Weight:** empty 127,800 lb, gross 255,000 lb.

**Ceiling:** 41,000 ft.

**Performance:** cruise speed Mach 0.8-0.86 (530 mph), range 5,750 miles.

**COMMENTARY**

A military version of the commercial Boeing 757-200, four new C-32As were purchased as replacements for C-137B/C aircraft. The commercial DV interior includes a crew rest area, DV stateroom, conference area, and general passenger area. The passenger communications system provides worldwide clear and secure voice and data communications. Modern flight deck avionics allow operations to any suitable airfield in the world and provide an upgrade path as new capabilities become available. Upgrades include installation of a digital communications management system and broadband data transmit and receive, providing an office-in-the-sky capability.

**C-37A**

**Brief:** A modified Gulfstream V utilized as part of the executive fleet, providing transportation for the vice president, Cabinet, Congressional members, Secretary of Defense, service Secretaries, and other prominent US and foreign officials.

**Function:** VIP air transport.

**Operator:** AMC, PACAF.

**First Flight:** USAF October 1998.

**Delivery:** October 1998-present.

**IOC:** Dec. 9, 1998.

**Production:** 10.

**Inventory:** nine.

**Unit Location:** Andrews AFB, Md., Chievres, Belgium, Hickam AFB, Hawaii, MacDill AFB, Fla.

**Contractor:** Gulfstream.

**Power Plant:** two BMW-Rolls Royce BR710A1-10 turbofans, each 14,750 lb thrust.

**Accommodation:** five crew and 12 passengers.

**Dimensions:** span 93.5 ft, length 96.4 ft, height 25.8 ft.

**Weight:** empty 47,601 lb, gross 90,500 lb.

**Ceiling:** 51,000 ft.

**Performance:** cruise speed Mach 0.8 (530 mph), range 6,095 miles.

**COMMENTARY**

The C-37A is a military version of the Gulfstream V. Two C-37As, along with the C-32s, were purchased as replacements for the VC-137B/C aircraft. The interior includes separate DV and passenger areas and a communications system capable of worldwide clear and secure voice and data. Aircraft are capable of operations at any suitable civilian or military airfield worldwide. A third C-37A was purchased for combatant commander support airlift and was based at Chievres, Belgium. It has since been reassigned to Andrews AFB, Md. Two more C-37s were purchased for crisis response support. Five C-37As are being leased from Gulfstream Aerospace as combatant commander support aircraft; three are assigned to MacDill AFB, Fla.; one to Chievres; and one to Hickam AFB, Hawaii. Upgrades include GATM and continuing passenger communications system upgrades to the Andrews-based aircraft.

**C-38A**

**Brief:** A twin-engine transcontinental aircraft used to provide transportation for DVs such as Congressional or high-ranking military members. It can also be configured for medevac and a wide range of special missions including C3 in time of war.

**Function:** VIP air transport and operational support.

**Operator:** ANG.

**First Flight:** 1998.

**Delivered:** April-May 1998.

**IOC:** 1998.

**Production:** two.

**Inventory:** two.

**Unit Location:** Andrews AFB, Md.

**Contractor:** Tracor (Israel Aircraft Industries Ltd).

**Power Plant:** two AlliedSignal TFE731-40R-200G, each 4,250 lb thrust.

**Accommodation:** typically two crew and eight passengers. In medevac role: two Spectrum 500 Life Support Units and two medical attendants. All seats removable for cargo.

**Dimensions:** span 54.6 ft, length 55.6 ft, height 18.2 ft.

**Weight:** gross 24,800 lb.

**Ceiling:** cruise, 33,000 ft.

**Performance:** cruise speed Mach 0.87.

**COMMENTARY**

The C-38A is a military version of the Astra SPX produced by IAI and supported worldwide by Galaxy Aerospace. Two aircraft are operated by ANG's 201st AS replacing Learjet C-21As. Equipment includes the most up-to-date navigation, communication, vertical separation, and safety equipment as well as state-of-the-art avionics. The contract includes an option for two additional aircraft.

**C-40**

**Brief:** A Boeing 727-700 used by ANG as its primary medium-range aircraft for airlift of personnel.

**Function:** Passenger transportation.

**Operator:** ANG.

**First Flight:** USN C-40A: April 14, 1999.

**Delivered:** 2002.

**Production:** seven.

**Inventory:** five.

**Unit Location:** Andrews AFB, Md., Hickam AFB, Hawaii.

**Contractor:** Boeing.

**Power Plant:** two General Electric CFM56-7 turbofans, each 24,000 lb thrust.

**Accommodation:** flight crew of four, plus three or four cabin crew; up to 89 passengers.

**Dimensions:** span 112 ft 7 in, length 110 ft 4 in, height 41 ft 2 in.

**Weight:** gross 171,000 lb.

**Ceiling:** 41,000 ft.

**Performance:** cruise speed 0.78-0.82 Mach, range 3,450 miles.

**COMMENTARY**

The C-40 is the military version of the commercial Boeing 737-700 increased gross weight aircraft. C-40s are used for SAM and support of combatant commanders.

**C-40B.** The B model is equipped with a DV suite, staff work area, conference area, and worldwide secure communications and data capability. USAF purchased two C-40Bs for delivery to Andrews AFB, Md., and Hickam AFB, Hawaii, in FY03 to support combatant commanders. One additional C-40B has been purchased and one leased for SAM missions and are assigned to Andrews.

**C-40C.** The C model has a DV seating area, general passenger seating area, and secure communications capability. Three leased C-40Cs operate from Andrews.

**C-130 Hercules**

**Brief:** A rugged aircraft capable of operating from



**C-130 Hercules** (SSgt. Suzanne M. Jenkins)

rough dirt strips to provide theater airlift and paratropping of troops and equipment into hostile areas.

**Function:** Inter- and intratheater airlift.  
**Operator:** AETC, AMC, PACAF, USAF, ANG, AFRC.  
**First Flight:** August 1954 (C-130A).  
**Delivered:** December 1956-present (C-130J).  
**IOC:** circa 1958.  
**Production:** more than 2,200; (C/CC-130J) 168 planned, though possible cap after end of 2005.  
**Inventory:** 507: 193 (E), 293 (H), 21 (J).  
**Unit Location:** Active: Dyess AFB, Tex., Elmendorf AFB, Alaska, Little Rock AFB, Ark., Pope AFB, N.C., Ramstein AB, Germany, Yokota AB, Japan. ANG: 23 units. AFRC: 10 units.

**Contractor:** Lockheed Martin.  
**Power Plant:** (C-130H) four Rolls Royce-Allison T56-A-15 turboprops, each 4,300 shp. (C-130J) four Rolls Royce-Allison AE2100D3 turboprops, each 4,591 shp.  
**Accommodation:** (C-130H) crew of five; up to 92 ground troops, 64 paratroops, 74 litter patients plus attendants, 54 passengers on palletized seating, or up to five 463L standard freight pallets, etc.; max load, 45,000 lb.  
**Dimensions:** span 132.6 ft, length 97.8 ft, height 38.1 ft.  
**Weight:** C-130H: empty 81,000 lb, fuel/cargo max gross 155,000 lb; C-130J: gross 175,000 lb.  
**Ceiling:** 33,000 ft at 100,000 lb T-O weight.  
**Performance:** (C-130H) max cruising speed 430 mph, T-O run 3,585 ft, landing run (at 130,000 lb) 1,700 ft, range with 40,000-lb payload 2,240 miles; range 3,450 miles.

**COMMENTARY**  
 First flown 48 years ago, the C-130 Hercules transport continues in production and has been delivered to more than 60 countries. Basic and specialized versions operate throughout USAF, performing diverse roles in both peace and war situations, including airlift support, Arctic ice cap resupply, aeromedical missions, aerial spray missions (AFRC), fire-fighting duties (AFRC and ANG) for the US Forest Service, and natural disaster and humanitarian relief missions.

**C-130A, B, and D.** Early versions, now retired. The initial production C-130A had four Allison T56-A-11 or -9 turboprop engines. USAF ordered a total of 219. The C-130B had improved range and higher weights and introduced Allison T56-A-7 turboprops; 134 were produced, with delivery from April 1959. Twelve were modified beginning 1961 as **JC-130Bs** for air-snatch satellite recovery together with three early H models. Twelve C-130Ds were modified As for Arctic operations.

**C-130E** is an extended-range development of the C-130B, with large under-wing fuel tanks; 389 were ordered, with deliveries beginning in April 1962. A wing modification to correct fatigue and corrosion extended the life of the aircraft well into this century. Other modifications include a self-contained navigation system, with an integrated communications/navigation management suite, GPS capability, and a state-of-the-art autopilot that incorporates a ground collision avoidance system.

**C-130H** is generally similar to the E model but has updated turboprops, a redesigned outer wing, and improved pneumatic systems; delivery began in July 1974. Subsequent improvements include updated avionics, improved low-power color radar, and other minor modifications. Night vision instrumentation system was introduced from 1993, TCAS II in new aircraft from 1994. ANG **LC-130H** aircraft are modified with wheel-ski gear to support Arctic and Antarctic operations. Two **DC-130Hs** were modified for UAV control duties.

A major AMP scheduled for the C-130E/H includes digital displays, flight-management systems, multifunc-

tion radar, new communications systems, and a single air data computer. Planned completion is for 2016. The AMP upgrade includes all C-130 models (LC/EC/MC/AC/HC) except the C-130J-30.

**C-130J.** This newest model features a three-crew flight operation system, 6,000 shp Rolls Royce-Allison AE2100D3 engines, all composite six-blade Dowty Aerospace R391 propeller system, digital avionics, and mission computers. Compared to earlier production C-130Es, its speed is up 21 percent, cruising altitude is 40 percent higher, and range 40 percent longer. The J also features improved reliability and maintainability. ANG and AFRC units began receiving J models in 1999. First active duty unit, the 48th AS at Little Rock AFB, Ark., received its first C-130J aircraft in March



**CV-22** (USAF photo/Jim Haseltine)

2004. First wartime deployment occurred December 2004. The future of C-130J acquisition is subject to the current budget review.

**C-130J-30.** USAF is acquiring a stretched version of the C-130J, with an additional 15 ft to the fuselage, capable of carrying up to 128 ground troops or 92 paratroops, to replace its oldest 1960s-vintage C-130Es. ANG received three in 2001 and two in 2002. Of the five on contract for 2004 delivery, one was slated for active duty; ANG, three; AFRC, one. USAF awarded a multiyear contract in 2002 with deliveries from 2005-09.

**CV-22**  
**Brief:** A tilt-rotor, multimission transport aircraft designed to have the maneuverability and lift capability of a helicopter and the speed of a fixed-wing aircraft.  
**Function:** Multimission airlift.  
**Operator:** AFSOC.  
**First Flight:** March 19, 1989 (V-22).  
**Delivery:** 2006 (planned).  
**IOC:** 2009 (planned).  
**Production:** 50 (planned).  
**Inventory:** 50 (planned).  
**Unit Location:** Hurlburt Field, Fla., Kirtland AFB, N.M.  
**Contractor:** Bell Boeing; Raytheon.  
**Power Plant:** two Rolls Royce-Allison AE1107C turboshafts, each 6,200 shp.  
**Accommodation:** four (two pilots, two flight engineers); additional pilot for extended duration missions; up to 18 troops or 8,000 lb internal cargo.

**Dimensions:** proprotor diameter 38 ft, width, rotors turning 84.6 ft, fuselage length 57.3 ft, height 22 ft.  
**Weight:** gross weight 34,900 lb, max VTO 52,870 lb; STO 57,000 lb, self-deploy T-O 60,500 lb.  
**Ceiling:** 26,000 ft.  
**Performance:** typically will carry troops or cargo over a 500-mile combat radius at 265 mph. Self-deployment range with one air refueling 2,417 miles.

**COMMENTARY**  
**CV-22** is the designation for the US Special Operations Command variant of the V-22 Osprey. The CV-22 is a multi-engine, dual-piloted, self-deployable, medium-lift vertical takeoff and landing (VTOL) tilt-rotor aircraft for the conduct of special operations, including nuclear, biological, and chemical (NBC) warfare conditions. It will operate from land bases and austere forward operating locations, as well as air capable ships without reconfiguration or modification. An in-flight refueling capability extends combat mission range when required, and the aircraft will be self-supporting to the maximum practical extent. The CV-22's mission is long-range clandestine penetration of denied areas in adverse weather and low visibility to infiltrate, exfiltrate, and resupply SOF.

CV-22 avionics include a fully integrated precision navigation suite, with GPS and INS; a digital cockpit management system oriented around four multifunction displays (MFDs); FLIR; an integrated NVG HUD; terrain-following/terrain-avoidance (TF/TA) radar; and digital map system. Additionally, it is equipped with robust self-defensive avionics and secure antijam, redundant communications compatible with current and planned systems used by command and control agencies and ground forces. The CV-22 unrefueled combat range satisfies current and emergent major theater war (MTW) requirements, as well as national mission tasking. The aircraft is capable of completing most assigned missions during one period of darkness.

A third aircraft joined the two test aircraft based at Edwards AFB, Calif., in February 2005. Initial operational test and evaluation is planned to begin in summer 2006.

Initial training capability is scheduled for early 2007 at Kirtland AFB, N.M., and IOC for early 2009 at Hurlburt Field, Fla. USAF may place detachments of CV-22s in US European Command and US Pacific Command theaters.

**MC-130E/H Combat Talon**  
**Brief:** A modified C-130 able to provide global, day, night, and adverse weather capability to air-drop personnel and to deliver personnel and equipment to support US and allied SOF.  
**Function:** SOF infiltration, exfiltration, and resupply.  
**Operator:** AETC, AFSOC, AFRC.  
**First Flight:** circa 1965 (E); January 1990 (H).  
**Delivered:** initially 1966.  
**IOC:** 1966 (E); June 1991 (H).  
**Production:** 22 new-build Hs.  
**Inventory:** 14 (E); 22 (H).  
**Unit Location:** Active (assoc.) and AFRC MC-130Es at Duke Field, Fla. Active: MC-130H at Hurlburt Field, Fla., Kadena AB, Japan, Kirtland AFB, N.M., RAF Mildenhall, UK.  
**Contractor:** Lockheed Martin (airframe); Boeing integrated weapons system support.  
**Power Plant:** four Allison T56-A-15 turboprops, each 4,910 shp.  
**Accommodation:** E: crew of nine; 53 troops or 26 paratroops; H: crew of seven; 77 troops, 52 paratroops, or 57 litters.  
**Dimensions:** span 132.7 ft, height 38.6 ft, length 100.8 ft (E), 99.8 ft (H).

**Weight:** empty 72,892 lb, gross 155,000 lb.

**Ceiling:** 30,000 ft.

**Performance:** max speed 289 mph, range 3,110 miles, unlimited with refueling.

**COMMENTARY**

MC-130 Combat Talon aircraft are equipped with terrain following radars, precision navigation systems using INS/GPS, and electronic and infrared countermeasures for self-protection. Both aircraft are capable of in-flight refueling, are NVG-compatible and have a high-speed aerial delivery system. The primary mission of the aircraft is to conduct infiltration, resupply, and exfiltration of special operations forces (SOF). They are also capable of supporting psychological operations. Combat Talons are able to air-drop or to land on austere unmarked landing or drop zones.

**MC-130E Combat Talon I.** Fourteen modified C-130E aircraft are additionally equipped with a pod-based system to air refuel SOF helicopters. Two units are MC-130E-equipped, the 8th and the 711th SOS.

**MC-130H Combat Talon II.** Twenty-four new-built MC-130Hs modified with an integrated glass cockpit were acquired in the early 1990s to supplement the Combat Talon Is. All are currently being modified with a state-of-the-art pod-based aerial refueling system to augment the MC-130E and MC-130P aerial refueling fleet. The 1st, 7th, and 15th SOSs provide support to SOF in Europe, the Pacific, and CONUS, respectively. The 58th SOS at Kirtland AFB, N.M., is responsible for MC-130H mission qualification training.

**VC-25 Air Force One**

**Brief:** A specially configured Boeing 747-200B used for air transport of the President and his entourage. When the President is aboard, it has the radio call sign "Air Force One."

**Function:** Air transport of the President.

**Operator:** AMC.

**First Flight:** first flown as Air Force One Sept. 6, 1990.

**Delivered:** August-December 1990.

**IOC:** circa 1990.

**Production:** two.

**Inventory:** two.

**Unit Location:** Andrews AFB, Md.

**Contractor:** Boeing.

**Power Plant:** four General Electric CF6 turbofans, each 56,700 lb thrust.

**Accommodation:** crew of 26; up to 76 passengers.

**Dimensions:** span 195.7 ft, length 231.8 ft, height 63.4 ft.

**Weight:** long-range mission T-O weight 803,700 lb., gross 833,000 lb.

**Ceiling:** 45,000 ft.

**Performance:** speed 630 mph (Mach 0.92), normal cruising speed Mach 0.84, unrefueled range 7,820 miles.

**COMMENTARY**

Based on the Boeing 747-200B airframe, two VC-25As assigned to Andrews AFB, Md., support the President. Aircraft are equipped with staff work areas, a conference room, a general seating area, and an executive office. Communications capability includes worldwide secure and clear communications equipment. Upgrades include GATM and installation of a broadband data transmit and receive capability to provide video teleconferencing and office-in-the-sky capability.

## Trainer Aircraft

**T-1A Jayhawk**

**Brief:** A medium-range, twin-engine jet trainer version of the Beechcraft 400A. It is used by the Air Force to train student pilots to fly airlift and tanker aircraft.

**Function:** Advanced pilot training.

**Operator:** AETC, AFRC.

**First Flight:** Sept. 22, 1989 (Beechcraft 400A).

**Delivered:** Jan. 17, 1992-July 1997.

**IOC:** January 1993.

**Production:** 180.

**Inventory:** 179.

**Unit Location:** Active: Columbus AFB, Miss., Laughlin and Randolph AFBs, Tex., Vance AFB, Okla., NAS, Pensacola, Fla. (forward operating station). AFRC: (assoc.) Randolph AFB, Tex.

**Contractor:** Raytheon.

**Power Plant:** two Pratt & Whitney Canada JT15D-5B turbofans, each 2,900 lb thrust.

**Accommodation:** two, side by side, and one to the rear; rails are fitted to accommodate an extra four seats to permit transport of maintenance teams.

**Dimensions:** span 43.5 ft, length 48.4 ft, height 13.9 ft.

**Weight:** empty 5,200 lb, gross 16,100 lb.

**Ceiling:** 41,000 ft.

**Performance:** max speed at 27,000 ft 538 mph, range 2,400 miles.

**COMMENTARY**

The swept-wing T-1A Jayhawk is a military version of



MC-130H Combat Talon II (A1C Kimberly Gilligan)

the Beech 400A used in the advanced phase of joint specialized undergraduate pilot training (JSUPT) for students selected to go on to fly transports such as the C-5 and C-17 or tankers such as the KC-10 and KC-135. It has cockpit seating for an instructor and two students. Special mission equipment includes GPS, an electronic flight instrument system (EFIS) avionics system, a single-point refueling system, an additional fuselage fuel tank, and increased bird-strike protection in the windshield and leading edges for sustained low-level operation. T-1As typically log 100,000 flying hours a year, supporting all-weather training operations at high and low altitudes.

**T-6A Texan II**

**Brief:** A single-engine turboprop aircraft used for training student pilots, navigators, and naval flight officers in fundamentals of aircraft handling and instrument, formation, and night flying.

**Function:** Primary trainer.

**Operator:** AETC, AFRC, USN.

**First Flight:** July 15, 1998.

**Delivery:** May 2000-present (operational aircraft).

**IOC:** November 2001.

**Production:** USAF 372 (ordered), USN 328 (planned).

**Inventory:** 159 (USAF).

**Unit Location:** USAF: Active: Laughlin and Randolph AFBs, Tex., Moody AFB, Ga. Planned: Columbus AFB, Miss., Sheppard AFB, Tex., Vance AFB, Okla. Navy: NAS Corpus Christi, Tex., NASs Pensacola and Whiting, Fla.

**Contractor:** Raytheon.

**Power Plant:** one Pratt & Whitney Canada PT6A-68 turboprop, 1,100 shp.

**Accommodation:** two, in tandem, on zero/zero ejection seats.

**Dimensions:** span 33.5 ft, length 33.4 ft, height 10.7 ft.

**Weight:** empty (approx) 4,707 lb; gross 6,500 lb.

**Ceiling:** 31,000 ft.

**Performance:** max speed 368 mph, range 920 miles.

**COMMENTARY**

The Joint Primary Aircraft Training System (JPATS) T-6A Texan II is based on the Swiss Pilatus PC-9 aircraft, modified to include a strengthened fuselage, zero/zero ejection seats, increased aircrew accommodation, upgraded engine, increased fuel capacity, pres-

surized cockpit, larger, bird-resistant canopy, and new digital avionics. The JPATS replaces USAF's T-37Bs and USN's T-34Cs in primary pilot training, as well as supporting undergraduate naval flight officer and USAF navigator training.

**T-37 Tweet**

**Brief:** A twin-engine jet used for training undergraduate pilots and undergraduate navigator and tactical navigator students in fundamentals of aircraft handling and instrument, navigation, formation, and night flying.

**Function:** Primary trainer.

**Operator:** AETC, AFRC.

**First Flight:** September 1955.

**Delivered:** December 1956-68.

**IOC:** 1957.

**Production:** 985.

**Inventory:** 283.

**Unit Location:** Active: Columbus AFB, Miss., Randolph, and Sheppard AFBs, Tex., Vance AFB, Okla. AFRC: (assoc.) Randolph AFB, Tex.

**Contractor:** Cessna.

**Power Plant:** two Continental J69-T-25 turbojets, each 1,025 lb thrust.

**Accommodation:** two, side by side, on ejection seats.

**Dimensions:** span 33.7 ft, length 29.2 ft, height 9.1 ft.

**Weight:** empty 3,870 lb, gross 6,625 lb.

**Ceiling:** 35,000 ft.

**Performance:** max speed at S/L 315 mph, range 460 miles.

**COMMENTARY**

USAF's first purpose-built jet trainer, the T-37 has been AETC's standard two-seat primary trainer for several decades. Its distinctive blue-and-white finish is intended to help formation training and ease maintenance.

**T-37A,** with J69-T-9 turbojets; all have been modified to T-37B standards.

**T-37B.** The original T-37A was superseded in November 1959 by the T-37B, with improved radio navigational equipment, UHF radio, and upgraded instruments. Kits were subsequently produced to extend the capability of the T-37 by modifying or replacing critical structural components. AETC began replacing the T-37B with the T-6A Texan II in 2000.



T-6A Texan II (MSgt. David Richards)



### T-38 Talon

**Brief:** A twin-engine, high-altitude, supersonic jet trainer used in a variety of roles, primarily for undergraduate pilot and pilot instructor training.

**Function:** Trainer.

**Operator:** ACC, AETC, AFMC, AFRC.

**First Flight:** April 1959.

**Delivered:** 1961-72.

**IOC:** March 1961.

**Production:** more than 1,100.

**Inventory:** T-38: 453, AT-38: 31.

**Unit Location:** Active: Beale and Edwards AFBs, Calif., Columbus AFB, Miss., Holloman AFB, N.M., Laughlin, Randolph, and Sheppard AFBs, Tex., Moody AFB, Ga., Vance AFB, Okla., Whiteman AFB, Mo. AFRC: (assoc.) Randolph AFB, Tex.

**Contractor:** Northrop Grumman.

**Power Plant:** two General Electric J85-GE-5A turbojets, each 2,680 lb thrust dry, 2,900 lb thrust with afterburning.

**Accommodation:** two, in tandem, on ejection seats.

**Dimensions:** span 25.3 ft, length 46.3 ft, height 12.8 ft.

**Weight:** empty 7,164 lb, gross 12,500 lb.

**Ceiling:** above 55,000 ft.

**Performance:** max level speed 812 mph, range 1,000 miles.

#### COMMENTARY

Most of the T-38s in service are used by AETC for advanced bomber-fighter training track in JSUPT. Capabilities are being enhanced through an ongoing program of modifications and structural renewal, including a full avionics upgrade with a HUD and integrated GPS/INS, and a propulsion modernization. As a result of the reduction in the T-38's workload through introduction of the T-1A and JSUPT, the service life of the T-38s should extend well beyond 2020.

**T-38A.** Close in structure to the F-5A export tactical fighter, the T-38A was the world's first supersonic trainer aircraft. It is used to teach supersonic techniques, aerobatics, formation, night and instrument flying, and cross-country and low-level navigation. The aircraft is also used by AFMC to train test pilots and flight-test engineers at Edwards AFB, Calif., in experimental techniques, and by ACC to maintain pilot proficiency.

**AT-38B.** A slightly different version, with a gunsight and practice bomb dispenser, the AT-38B is used by AETC for Introduction to Fighter Fundamentals.

**T-38C.** All T-38A and AT-38B airframes will be redesignated as C models upon modification of the avionics systems begun in 2000. The first T-38C was received late summer 2002; planned program completion is 2008. The propulsion system is also being upgraded to improve performance and reliability. In addition, an Escape System Upgrade program is under way to further improve safety and sustainability of the aircraft and increase aircrew accommodation. Installations are scheduled to begin in FY06.

### T-41 Mescalero

**Brief:** Short-range, high-wing trainer used primarily for aerodynamic and navigation courses.

**Function:** Training, support.

**Operator:** US Air Force Academy.

**Delivered:** 1969.

**Inventory:** four.

**Unit Location:** USAFA, Colo.

**Contractor:** Cessna.

**Power Plant:** one Continental IO-360-DB piston engine, 210 hp thrust.

**Accommodation:** two, side by side.

**Dimensions:** span 36.1 ft, length 26.5 ft, height 8.9 ft.

**Weight:** gross 2,550 lb.

**Ceiling:** 16,000 ft.

**Performance:** speed 182 mph, range 690 miles.

#### COMMENTARY

The T-41D, a military version of the Cessna 172, is an all-metal, strut-braced high-wing monoplane. The aircraft is equipped with modern avionics, GPS, and other equipment appropriate to its mission. It is used for Aero 456 flight testing, USAFA flying team support, and orientation flights.

### T-43

**Brief:** A medium-range, swept-wing jet aircraft equipped with navigation and communications equipment to train navigators for strategic and tactical aircraft.

**Function:** Navigation trainer.

**Operator:** AETC.

**First Flight:** April 1973.

**Delivered:** September 1973-July 1974.

**IOC:** 1974.

**Production:** 19.

**Inventory:** nine.

**Unit Location:** Randolph AFB, Tex.

**Contractor:** Boeing.

**Power Plant:** two Pratt & Whitney JT8D-9 turbofans, each 14,500 lb thrust.

**Accommodation:** crew of two; 12 students and six instructors.

**Dimensions:** span 93 ft, length 100 ft, height 37 ft.



T-38 Talon (SrA. Matthew C. Simpson)

**Weight:** gross 115,500 lb.

**Ceiling:** 37,000 ft.

**Performance:** econ cruising speed 535 mph (Mach 0.7), operational range 2,995 miles.

#### COMMENTARY

**T-43A.** The T-43A was derived from the commercial Boeing Model 737-200 and was equipped with the same onboard avionics as most USAF operational aircraft, including mapping radar, VHF omnidirectional radio and Tacan radio systems, INS, radar altimeter, all required communications equipment, and celestial navigation capability. A number of T-43s are configured for passengers and provide operational support to assigned commands.

### TG-10B Merlin

**Brief:** Two-seat medium-performance sailplane used for introductory glider training, instructor upgrade training, spin training, and basic cross-country soaring training.

**Function:** Trainer.

**Operator:** USAFA.

**Delivered:** May 2002.

**IOC:** December 2002.

**Production:** 12.

**Inventory:** 12.

**Unit Location:** USAFA, Colo.

**Contractor:** Blanik.

**Accommodation:** two.

**Dimensions:** span 55.4 ft, length 27.9 ft, height 6.2 ft.

**Weight:** 1,168 lb.

**Performance:** speed 142.6 mph, glide ratio 28:1.

#### COMMENTARY

The TG-10B is an L-23 Super Blanik dual sailplane, produced in the Czech Republic and used by USAFA to introduce cadets to flight through the Basic Soaring program.

### TG-10C Kestrel

**Brief:** Two-seat medium-performance sailplane used for spin and aerobatic training.

**Function:** Trainer.

**Operator:** USAFA.

**Delivered:** May 2002.

**IOC:** December 2002.

**Production:** five.

**Inventory:** five.

**Unit Location:** USAFA, Colo.

**Contractor:** Blanik.

**Accommodation:** two.

**Dimensions:** span 46.6 ft, length 27.6 ft, height 6.9 ft.

**Weight:** 1,100 lb.

**Performance:** speed 146.1 mph, glide ratio 26:1.

#### COMMENTARY

The TG-10C is an L-13AC Blanik dual sailplane, produced in the Czech Republic and used primarily for spin and aerobatic training.

### TG-10D Peregrine

**Brief:** Single-seat medium-performance sailplane used for cross-country soaring training and high-altitude wave flight.

**Function:** Trainer.

**Operator:** USAFA.

**Delivered:** May 2002.

**IOC:** December 2002.

**Production:** four.

**Inventory:** four.

**Unit Location:** USAFA, Colo.

**Contractor:** Blanik.

**Accommodation:** single.

**Dimensions:** span 46.3 ft, length 21.7 ft, height 4.7 ft.

**Weight:** 750 lb.

**Performance:** speed 149.5 mph, glide ratio 33:1.

#### COMMENTARY

The TG-10D is an L-33 Solo Blanik sailplane produced in the Czech Republic. It is a medium performance sailplane that allows students to master basic flight maneuvers while solo, before progressing to a more advanced sailplane. It is primarily used for cross-country training and high-altitude wave flight.

### TG-14A

**Brief:** A two-place, side-by-side motorized glider for use by USAFA in its Introductory Flight Training Program (IFTP) flight screening/primary training program.

**Function:** Trainer.

**Operator:** USAFA.

**Delivered:** September 2002.

**IOC:** December 2002.

**Production:** 14.

**Inventory:** 14.

**Unit Location:** USAFA, Colo.

**Contractor:** Grupo Aeromot, Brazil.

**Power Plant:** one Rotax 912A, 81 hp engine.



TG-14A (USAF photo)

**Accommodation:** two, side by side.  
**Dimensions:** span 57.3 ft, length 26.4 ft, height 6.3 ft.  
**Weight:** gross 1,874 lb.  
**Performance:** cruise speed 110 mph, glide ratio 31:1, range 690 miles at high-speed cruise, max endurance seven hr.

**COMMENTARY**

The **TG-14A** is a version of the Ximango AMT-200S Sport Grupo Aeromot selected for use at USAFA in IFTP, replacing the Enhanced Flight Screening Program performed by civilian flying schools since the grounding of the T-3A Firefly in 1997. Cockpit and avionics are arranged for military use. Students use it to practice multiple pattern, aerial maneuvers, and landing procedures, reducing by half the number of sorties needed to achieve a solo flight.

**TG-15A**

**Brief:** A two-seat high-performance advanced training/cross-country sailplane for use by USAFA cadets in support of glider competition events nationwide.

**Function:** Trainer/cross-country competition sailplane.  
**Operator:** USAFA.

**Unit Location:** USAFA, Colo.  
**Inventory:** two.

**Contractor:** Schempp-Hirth, Germany.  
**Accommodation:** two-seat.

**Dimensions:** span 65.6 ft, length 28.3 ft.  
**Weight:** gross 1,543 lb.

**Performance:** max permitted speed 155 mph, aspect ratio 24:4.

**COMMENTARY**

The **TG15A** is a high-performance advanced training/cross-country sailplane manufactured by Schempp-Hirth of Germany under the civilian designation Duo Discus. This world-class competition glider is dual seated and will be used nationwide by USAFA cadets for glider competition events.

**TG-15B**

**Brief:** A single-seat high-performance advanced training/cross-country sailplane for use by USAFA cadets for glider competition events nationwide.

**Function:** Trainer/cross-country competition sailplane.  
**Operator:** USAFA.

**Unit Location:** USAFA, Colo.  
**Inventory:** three.

**Contractor:** Schempp-Hirth, Germany.  
**Accommodation:** single seat.

**Dimensions:** span 49.2 ft, length 32.3 ft.  
**Weight:** gross 1,157 lb.

**Performance:** max permitted speed 155 mph, aspect ratio 22:2.

**COMMENTARY**

The **TG15B** is a high-performance advanced training/cross-country sailplane manufactured by Schempp-Hirth of Germany under the civilian designation Discus 2b. This world-class competition glider is single seated and will be used nationwide by USAFA cadets for glider competition events.

**UV-18 Twin Otter**

**Brief:** Modified utility transport used for parachute jump training.

**Function:** Paratroop.  
**Operator:** USAFA.

**First Flight:** May 1965 (commercial version).  
**Delivered:** 1977.

**IOC:** 1977.  
**Production:** three.

**Inventory:** three.

**Unit Location:** USAFA, Colo.  
**Contractor:** de Havilland Aircraft of Canada.

**Power Plant:** two Pratt & Whitney Canada PT6A-27 turboprops, each 620 ehp.

**Accommodation:** crew of two and up to 20 passengers.  
**Dimensions:** span 65 ft, length 51.8 ft, height 19.5 ft.

**Weight:** gross 12,500 lb.  
**Ceiling:** 26,700 ft.

**Performance:** max cruising speed 210 mph, range with 2,500 lb payload 806 miles.

**COMMENTARY**

The UV-18B is a military version of the DHC-6 Twin Otter STOL utility transport used for parachute jump training at USAFA.

## Helicopters

**HH-60G Pave Hawk**

**Brief:** Specially modified helicopters used for SAR and support missions.

**Function:** SOF heavy-lift helicopter.

**Operator:** ACC, AETC, AFMC, AFSOC, PACAF, USAF, ANG, AFRC.

**First Flight:** October 1974.  
**Delivered:** from 1982.

**IOC:** circa 1982.



**HH-60G Pave Hawk** with MC-130P Combat Shadow (TSgt. Justin D. Pyle)

**Production:** 105.

**Inventory:** 104.

**Unit Location:** Davis-Monthan AFB, Ariz., Eglin AFB, Fla., Kadena AB, Japan, Kirtland AFB, N.M., Moody AFB, Ga., NAS Keflavik, Iceland, Nellis AFB, Nev., Robins AFB, Ga. ANG: Francis S. Gabreski Arpt., N.Y., Kulis ANGB, Alaska, Moffett Federal Airfield, Calif. AFRC: Davis-Monthan AFB, Ariz., Patrick AFB, Fla.

**Contractor:** Sikorsky.

**Power Plant:** two General Electric T700-GE-700/701C turboshafts, each 1,620 (continuous) shp.

**Accommodation:** crew of three or four; 11-14 troops, up to six litters, or internal or external cargo.

**Dimensions:** rotor diameter 53.6 ft, length of fuselage 64.7 ft, height 16.7 ft.

**Weight:** empty 12,330 lb, max gross 22,000 lb.  
**Ceiling:** 14,200 ft.

**Performance:** max speed 173 mph, max range 373 miles (internal fuel), 500 miles (auxiliary tank).

**Armament:** two 7.62 mm miniguns, with provision for two .50-caliber machine guns in cabin doors.

**COMMENTARY**

Black Hawk helicopters were modified to **HH-60G** Pave Hawk configuration for use by active duty, ANG, and AFRC air rescue units for CSAR and mission activities worldwide. The Pave Hawk is a highly modified version of the Army Black Hawk helicopter, featuring an upgraded communications/navigation suite that includes INS/GPS/Doppler navigation systems, satellite communications (SATCOM), secure/antijam communications, and a PLS that provides range/steering data to compatible survivor radios.

Further modifications include an automatic flight-control system, NVG lighting, FLIR, color weather radar, engine/rotor blade anti-ice system, retractable in-flight refueling probe, internal auxiliary fuel tanks, and an integral rescue hoist. Combat enhancements include RWR, IR jammer, flare and chaff countermeasures dispensing system, and two 7.62 mm or .50-caliber machine guns.

**MH-53 Pave Low**

**Brief:** Specially outfitted heavy-lift helicopters used by Air Force special operations forces for infiltration/exfiltration as well as CSAR missions.

**Function:** SOF heavy-lift helicopter.

**Operator:** AETC, AFSOC.

**First Flight:** March 1967.

**Delivered:** from July 1987 (MH-53J).

**IOC:** 1988 (MH-53J).

**Production:** not available.

**Inventory:** 33.

**Unit Location:** AETC: Kirtland AFB, N.M. AFSOC: Hurlburt Field, Fla., RAF Mildenhall, UK.

**Contractor:** Sikorsky; Texas Instruments.

**Power Plant:** two General Electric T64-GE-100 turboshafts, each 4,330 shp.

**Accommodation:** crew of six; up to 38 troops.

**Dimensions:** rotor diameter 72.2 ft, length of fuselage (without refueling probe) 67.2 ft, height 25 ft.

**Weight:** gross 50,000 lb.

**Ceiling:** 16,000 ft.

**Performance:** speed 164 mph, max range 630 miles, unlimited with air refueling.

**Armament:** mounts for any combination of three 7.62 miniguns and .50-caliber machine guns.

**COMMENTARY**

**MH-53H.** Older version of the helicopter, all of which, together with all HH/CH-53B/Cs, were upgraded to MH-53J Pave Low III "Enhanced" standard from 1986.

**MH-53J.** A long-range deep penetration helicopter, adverse weather capable and equipped for extended operations when air refueled. Equipped with a nose-mounted FLIR, an integrated digital avionics suite that includes TF/TA radar, Kalman filtered navigation suite (GPS, INS, Doppler), projected map display, secure UHF, VHF, FM, HF communications, PLS, SATCOM, hover coupler, rescue hoist, mission commander's C2 panel, armor plating, and an ECM suite with radar and IR missile jammers, flare/chaff dispensers, RWR, and missile launch detectors.

A service life extension program (SLEP) upgraded the aircraft's hydraulics, wiring, and basic airframe structure for increased gross weight, and an automated blade/pylon fold system optimized for shipboard compatibility. All aircraft modified to support aircrew eye/respiratory protection system.

**MH-53M.** MH-53J helicopters upgraded to Pave Low IV standard, delivered from 1999. Upgrades include the interactive defensive avionics suite/multimission advanced tactical terminal capability which integrates onboard EW systems with off-board, over-the-horizon, near-real-time intelligence, and mission software improvements. Cockpit modifications include three MFDs,



**MH-53J Pave Low III** (TSgt. Scott Reed)

integrated digital map, and mission commander situation awareness panel in the cabin area.

#### UH-1 Iroquois

**Brief:** Modified Bell helicopter used to support Air Force ICBM facilities and for administrative airlift.

**Function:** Utility helicopter.

**Operator:** AETC, AFMC, AFSOC, AFSPC, AMC, PACAF.

**First Flight:** circa 1956.

**Delivered:** from September 1970.

**IOC:** circa 1970.

**Production:** 79 (USAF).

**Inventory:** 89.

**Unit Location:** Andrews AFB, Md., Fairchild AFB, Wash., F.E. Warren AFB, Wyo., Hurlburt Field, Fla., Kirtland AFB, N.M., Malmstrom AFB, Mont., Minot AFB, N.D., Robins AFB, Ga., Vandenberg AFB, Calif., Yokota AB, Japan.

**Contractor:** Bell.

**Power Plant:** Pratt & Whitney Canada T400-CP-400 Turbo "Twin-Pac," 1,290 shp.

**Accommodation:** two pilots and 14 passengers or cargo, or external load of 4,000 lb.

**Dimensions:** rotor diameter (with tracking tips) 48.1 ft, fuselage length 42.3 ft, height 14.3 ft.

**Weight:** gross and mission weight 11,200 lb.

**Ceiling:** 13,000 ft.

**Performance:** max cruising speed at S/L 115 mph, max range, no reserves, 261 miles.

**Armament:** (optional) two General Electric 7.62 mm miniguns or two 40 mm grenade launchers; two seven-tube 2.75-in rocket launchers.

#### COMMENTARY

**UH-1N** is a twin-engine version of the UH-1 utility helicopter (Bell Model 212), most of which are allocated for AFSPC missile site support and for administrative/DV airlift. The UH-1N is also used by AETC's 58th SOW, Kirtland AFB, N.M., for training purposes and by the 336th TG, Fairchild AFB, Wash., for aircrew survival training. Two UH-1N helicopters are maintained by AFSOC for aviation advisory aircrew flight proficiency.

## Strategic Missiles

#### AGM-86 Air Launched Cruise Missile

**Brief:** A small, subsonic, winged air vehicle, deployed on B-52H aircraft, which can be equipped with either a nuclear or conventional warhead and can be used to help dilute air defenses and complicate an enemy's air defense task.

**Function:** Strategic air-to-surface cruise missile.

**Operator:** ACC.

**First Flight:** June 1979 (full-scale development).

**Delivered:** from 1981.

**IOC:** December 1982, Griffiss AFB, N.Y.

**Production:** 1,700+.

**Unit Location:** Barksdale AFB, La., Minot AFB, N.D.

**Contractor:** Boeing.

**Power Plant:** Williams/Teledyne CAE F107-WR-10 turbofan, 600 lb thrust.

**Guidance:** AGM-86B: inertial plus Terrain Contour Matching (TERCOM); AGM-86C: inertial plus GPS.

**Warhead:** AGM-86B: W80-1 nuclear; AGM-86C: blast/fragmentation conventional; AGM-86D: hard target penetrating warhead.

**Dimensions:** length 20.8 ft, body diameter 2 ft, wingspan 12 ft.

**Weight:** 3,150 lb (B), 3,277 lb (C).

**Performance** (approx): speed 550 mph (Mach 0.6), range 1,500+ miles (AGM-86B).

#### COMMENTARY

**AGM-86A.** A prototype cruise missile, developed in the mid-1970s. Slightly smaller than the later versions, it never entered production.

**AGM-86B.** First production version, the B is programmed for strategic attack on surface targets. Small radar signature and low-level flight capability enhance the missile's effectiveness. The last of 1,715 production models was delivered in October 1986. Undergoing SLEP to extend life to FY30.

**AGM-86C.** A conventional warhead version, developed from June 1986, the Conventional Air Launched Cruise Missile (CALCM) was first used operationally during Gulf War I and has since been used widely in combat operations. CALCM provides the warfighter with an adverse weather, day/night, air-to-surface, accurate, standoff outside theater defenses strike capability, with a range greater than 500 miles and a 3,000-lb class warhead. CALCM is equally effective for stand-alone, clandestine/punitive strikes and fully integrated theater warfare. From 1986, Boeing converted 622 Bs to the conventional configuration, the first of which was delivered in December 1987. The remaining CALCMs have Block 1A enhancements with improved accuracy and increased immunity to electronic jamming. Since Iraqi Freedom, few CALCMs remain.

**AGM-86D.** CALCM penetrator version with a Lockheed Martin AUP-3(M) warhead. The CALCM penetrator provides the warfighter with a cost-effective, standoff outside theater defenses capability against a wide range of hardened, deeply buried targets. The CALCM penetrator was used with success in Iraqi Freedom.

#### AGM-129 Advanced Cruise Missile

**Brief:** A stealthy, long-range, winged air vehicle equipped with a nuclear warhead and designed to evade enemy air and ground-based defenses in order to strike hard, heavily defended targets at standoff distances.

**Function:** Strategic air-to-surface cruise missile.

**Operator:** ACC.

**First Flight:** July 1985.

**Delivered:** June 1990-August 1993.

**IOC:** circa 1991.

**Production:** 461.

**Unit Location:** Barksdale AFB, La., Minot AFB, N.D.

**Contractor:** General Dynamics (now Raytheon); McDonnell Douglas (now Boeing).

**Power Plant:** Williams International F112-WR-100 turbofan.

**Guidance:** inertial, with TERCOM update.

**Warhead:** W80-1 nuclear.

**Dimensions:** length 20.8 ft, body width 2.2 ft, wing-span 10.2 ft.

**Weight:** 3,700 lb.

**Performance** (approx): range 2,300+ miles, speed 550 mph.

#### COMMENTARY

**AGM-129A.** Embodying stealth technology, the AGM-129A is an air-launched strategic cruise missile with significant improvements over the AGM-86B in range, accuracy, and survivability. Armed with a W-80 warhead, it is designed to evade air- and ground-based



LGM-30 Minuteman (USAF photo)

defense systems in order to strike heavily defended, hardened targets at any location within an enemy's territory. Developed by General Dynamics, McDonnell Douglas was certified as second source for this advanced system, which is carried externally on B-52H aircraft. The ACM is undergoing modification to extend its service life to 2030.

#### LG-118 Peacekeeper

**Brief:** A solid-fuel ICBM capable of delivering a thermonuclear payload of 10 warheads with high accuracy over great distances.

**Function:** Strategic surface-to-surface ballistic missile.

**Operator:** AFSPC.

**First Flight:** June 17, 1983.

**Delivered:** June 1986-December 1988.

**IOC:** December 1986, F.E. Warren AFB, Wyo.

**Production:** 50.

**Unit Location:** F.E. Warren AFB, Wyo.

**Contractor:** Lockheed Martin.

**Power Plant:** first three stages: solid propellant; fourth stage: storable liquid; by Thiokol, Aerojet, Hercules, and Rocketdyne, respectively.

**Guidance:** inertial guidance system.

**Warheads:** 10 Avco Mk 21 multiple independently targetable re-entry vehicles (MIRVs).

**Dimensions:** length 71 ft, diameter 7.7 ft.

**Weight:** approx 195,000 lb.

#### COMMENTARY

**LG-118A.** Developed initially in response to an increased Soviet strategic threat, deployment was capped at 50 in FY90 in response to the changing international political climate.

Housed in converted Minuteman III silos, Peacekeeper is a four-stage ICBM that carries up to 10 independently targetable re-entry vehicles. It is more accurate and has a greater payload and range than the Minuteman III. Its greater resistance to nuclear effects and its more capable guidance system provide a greatly improved ability to destroy very hard targets. These attributes, combined with its prompt response, provide a decisive deterrent.

On Oct. 3, 2002, USAF began deactivation of Peacekeeper ICBMs, scheduled for retirement under nuclear force structure reductions. Final decommissioning is expected September 2005.

#### LGM-30 Minuteman

**Brief:** A solid-fuel ICBM capable of being fired from silo launchers and delivering a thermonuclear payload of one to three warheads with high accuracy over great distances.

**Function:** Strategic surface-to-surface ballistic missile.

**Operator:** AFSPC.

**First Flight:** February 1961.

**Delivered:** 1962-December 1978.

**IOC:** December 1962, Malmstrom AFB, Mont.

**Production:** 1,800.

**Unit Location:** F.E. Warren AFB, Wyo., Malmstrom AFB, Mont., Minot AFB, N.D.

**Contractor:** Boeing.

**Power Plant:** stage 1: Thiokol M-55 solid-propellant motor, 210,000 lb thrust; stage 2: Aerojet General SR19-AJ-1 solid-propellant motor, 60,300 lb thrust; stage 3: Thiokol SR73-AJ-1 solid-propellant motor, 34,400 lb thrust.

**Guidance:** inertial guidance system.

**Warheads:** one-three Mk 12/12A MIRVs (downloaded to one).

**Dimensions:** length 59.8 ft, diameter of first stage 5.5 ft.

**Weight:** launch weight (approx) 78,000 lb.

**Performance:** speed at burnout more than 15,000 mph, highest point of trajectory approx 700 miles, range with max operational load more than 6,000 miles.

#### COMMENTARY

A key element in the US strategic deterrent posture, Minuteman is a three-stage, solid-propellant ICBM, housed in an underground silo.

**LGM-30A/B.** Minuteman I version deployed in the early 1960s. The last Minuteman I missile was removed from its silo at Malmstrom AFB, Mont., in February 1969. USAF had deployed 150 A and 650 B models in 16 squadrons.

**LGM-30F.** Minuteman II version incorporated a larger second stage, an improved guidance package, greater range and payload capability, and hardening against the effects of nuclear blast. IOC was reached in October 1965 at Grand Forks AFB, N.D. USAF deployed 450 in nine squadrons.

**LGM-30G.** The Minuteman III became operational in June 1970, providing improved range, rapid retargeting, and the capability to place three MIRVs on three targets with a high degree of accuracy. USAF initially deployed 550 in 11 squadrons.

A single re-entry vehicle configuration for some missiles has been demonstrated, planned for, and is being worked in accordance with strategic arms control negotiations. Currently a total of 500 Minuteman IIIs are based at Minot AFB, N.D.; F.E. Warren AFB, Wyo.; and Malmstrom.

An extensive life extension program is ensuring Minuteman's viability to 2020. Major upgrades include refurbishment of liquid propulsion post-boost rocket engine, remanufacture of the solid-propellant rocket motors, replacement of the environmental control system, repair of launch facilities, installation of updated, survivable communications equipment, and a C2 sustainment program.

## Tactical Missiles and Weapons

#### AGM-65 Maverick

**Brief:** A tactical, TV- or imaging infrared (IIR)-guided air-to-surface missile carried by fighters and designed for use in CAS, interdiction, and defense suppression missions, having standoff capability and high probability



**AGM-88 HARM** (MSgt. Michael Ammons)

ity of strike against a wide range of targets.

**Function:** Air-to-surface guided missile.

**First Flight:** August 1969.

**Delivered:** from August 1972.

**IOC:** February 1973.

**Production:** sustainment phase.

**Contractor:** Raytheon.

**Power Plant:** Thiokol TX-481 solid-propellant rocket motor.

**Guidance:** self-homing, EO guidance system (IIR on D and G models).

**Warhead:** AGM-65A/B/D/H 125-lb high-explosive, shaped charge; AGM-65G/K 298-lb blast fragmentation.

**Dimensions:** length 8.2 ft, body diameter 1 ft, wingspan 2.3 ft.

**Weight:** launch weight (AGM-65A) 462 lb, (AGM-65G) 670 lb.

**Performance:** range about 9.2 miles.

**COMMENTARY**

Maverick missiles have a long and distinguished combat record. They were first employed by USAF in Vietnam and were used extensively during Gulf War I and II. They currently equip A-10, F-15E, and F-16 aircraft for use against tanks and columns of vehicles and in the SEAD role.

**AGM-65A.** The basic Maverick is a launch-and-leave, TV-guided air-to-surface missile that enables the pilot of the launch aircraft to seek other targets or leave the target area once the missile has been launched. Production was initiated in 1971, following successful test launches over distances ranging from a few thousand feet to many miles and from high altitudes to treetop level.

**AGM-65B.** A version with a "scene magnification" TV seeker that enables the pilot to identify and lock on to smaller or more distant targets.

**AGM-65D.** System developed to overcome limitations of the TV Maverick, which can be used only in daylight and clear-weather conditions. This version has an IIR seeker as well as a lower-smoke motor. IIR Maverick became operational in February 1986 on A-10 aircraft.

**AGM-65G.** Uses the IIR seeker with an alternate 298-lb blast fragmentation warhead for use against hardened targets. Software is modified to include options for targeting ships and large land targets as well as mobile armor. This version also has a digital autopilot and a pneumatic, rather than hydraulic, actuation system. USAF received its first G model in 1989.

**AGM-65H.** AGM-65B modified with an upgraded TV seeker providing significant reliability, maintainability, and performance improvements over the AGM-65B seeker and double the standoff range.

**AGM-65K.** AGM-65G modified with the same upgraded TV seeker as in the AGM-65H to provide a TV-guided version of the Maverick with the 298-lb blast fragmentation warhead.

**AGM-84 Harpoon**

**Brief:** An adverse weather capable, sea-skimming, active radar-guided, antiship cruise missile system capable of being fired from B-52H aircraft, ships, and submarines.

**Function:** Air-to-surface antiship missile.

**First Flight:** March 1974 (for USN).

**Delivered:** from 1977 (USN).

**IOC:** circa 1985 (USAF).

**Production:** sustainment phase.

**Contractor:** Boeing (McDonnell Douglas).

**Power Plant:** Teledyne CAE J402-CA-400 turbojet, 660 lb thrust.

**Guidance:** sea-skimming cruise monitored by radar altimeter, active radar terminal homing.

**Warhead:** penetration high-explosive blast type, weighing 500 lb.

**Dimensions:** length 12.6 ft, body diameter 1.1 ft, wingspan 3 ft.

**Weight:** 1,172 lb.

**Performance:** speed high subsonic, range more than 57 miles.

**COMMENTARY**

Harpoon and its launch control equipment provide USAF the capability to interdict ships at ranges well beyond those of other aircraft. Originally acquired to equip two squadrons of now-retired B-52G aircraft for maritime antisurface operations, the Harpoon all-weather antiship missile currently arms conventional-mission B-52Hs.

**AGM-84D** is a variant of the USN Harpoon that has been adapted for use on B-52 bombers which can carry eight missiles.

**AGM-88 HARM**

**Brief:** An air-to-surface tactical missile designed to seek and destroy enemy radar-equipped air defense systems, using an advanced guidance system that senses and homes in on enemy radar emissions.

**Function:** Air-to-surface antiradiation missile.

**First Flight:** April 1979.

**Delivered:** 1982-98.

**IOC:** circa 1984.

**Production:** sustainment phase.

**Contractor:** Raytheon.

**Power Plant:** Thiokol smokeless, dual-thrust, solid-propellant rocket motor.

**Guidance:** passive homing guidance system, using seeker head that homes on enemy radar emissions.

**Warhead:** high-explosive fragmentation, weighing 145 lb.

**Dimensions:** length 13.7 ft, body diameter 10 in, wingspan 3.7 ft.

**Weight:** 795 lb.

**Performance:** cruising speed supersonic, altitude limits S/L to 40,000 ft, range more than 10 miles.

**COMMENTARY**

The High-speed Anti-Radiation Missile (HARM) exhibits great velocity along with an ability to cover a wide range of frequency spectrums through the use of programmable digital processors in both the carrier aircraft's avionics equipment and in the missile. The combina-

tion gives this second generation anti-radiation missile (ARM) greatly improved capability over first-generation Shrikes and Standard ARMs. The AGM-88 proved highly effective against enemy ground radar in Gulf War I and in subsequent operations. HARMs equip F-16 Block 50/52s (F-16CJ) dedicated to the SEAD mission.

**AGM-88A.** A factory-programmed version used to equip the now-retired F-4G Wild Weasel to increase its lethality in electronic combat. No longer operational.

**AGM-88B.** Incorporated erasable electronically programmable read-only memory, permitting changes to missile memory in the field. Older versions of the AGM-88B have software upgrades to satisfy current-standard capability requirements.

**AGM-88C.** This current production version has a more lethal warhead, containing tungsten alloy cubes, rather than steel, and the enhanced-capability AGM-88C-1 guidance head.

Upgrade initiatives are aimed at increasing capability of both B and C versions against target shutdown, blanking, and blinking and at reducing potential damage to friendly radars in the target area. Further upgrades being evaluated include GPS precision navigation capability through a modification of the control section known as the HARM Destruction of Enemy Air Defenses (DEAD) Attack Module, or HDAM.

**AGM-130**

**Brief:** A powered TV- or IIR-guided air-to-surface missile, carried by the F-15E and designed for high- and low-altitude strikes at standoff ranges against heavily defended targets.

**Function:** Air-to-surface guided and powered bomb.

**First Flight:** 1984.

**Delivered:** November 1992-FY00.

**IOC:** 1994.

**Production:** sustainment phase.

**Contractor:** Boeing.

**Guidance:** TV or IIR seeker, or distance measuring equipment (DME) transponder.

**Warhead:** Mk 84 bomb (2,000-lb unitary) or BLU-109.

**Dimensions:** length 12.8 ft, body diameter 1.5 ft, wingspan 4.9 ft.

**Weight:** launch weight 2,917 lb.

**Performance:** cruising speed subsonic, ceiling in excess of 30,000 ft, range greater than 34.5 miles, circular error probable (CEP) about 10 ft.

**COMMENTARY**

AGM-130 is a product improvement to the GBU-15 glide bomb, with a guidance system designed to give pinpoint accuracy from low or medium altitudes. The AGM-130 adds a rocket motor, radar altimeter, and digital control system, providing it with double the standoff range of the GBU-15.

Upgrades include a new solid-state TV seeker, an improved IR seeker, and INS/GPS guidance that permit operation in adverse weather and improve target acquisition.

AGM-130s have been used extensively in recent operations.

**AGM-130A,** with the Mk 84 warhead.

**AGM-130C,** with the BLU-109/B penetrating warhead.

**AGM-154 Joint Standoff Weapon**

**Brief:** First in a joint USAF and Navy family of low-cost, highly lethal glide weapons with a standoff capability, usable against heavily defended targets.

**Function:** Air-to-surface guided missile.

**First Flight:** December 1994.

**Delivered:** 2000-present.



**AGM-130** (Jim Haseltine)

**IOC:** 2000 (USAF).

**Production:** 6,114 (originally planned).

**Contractor:** Raytheon.

**Guidance:** INS/GPS.

**Dimensions:** length 13.3 ft.

**Weight:** 1,065-1,500 lb.

**Performance:** range: low-altitude launch 17 miles, high-altitude launch 40+ miles.

#### COMMENTARY

A medium-range, INS/GPS-guided, standoff air-to-ground weapon designed to attack a variety of soft and armored area targets (fixed, relocatable, and mobile) during day/night/adverse weather conditions. JSOW enhances aircraft survivability by providing the capability for launch aircraft to stand off outside the range of enemy point defenses. JSOW accuracy and launch-and-leave capability allows several target kills per aircraft sortie. JSOW arms B-1, B-2, B-52, F-15E, and F-16 aircraft. Last planned USAF buy was in FY04.

**AGM-154A.** The baseline BLU-97 variant for use against area targets; in full-rate production.

**AGM-154B.** The BLU-108 variant providing anti-armor capability; development complete, production deferred.

**AGM-154C.** The third variant (used by Navy only), JSOW/Unitary integrates an IIR terminal seeker and a 500-lb unitary warhead.

#### AGM-158A Joint Air-to-Surface Standoff Missile

**Brief:** An advanced weapon designed to attack heavily defended targets with high precision at great standoff range.

**Function:** Air-to-surface guided weapon.

**First Flight:** April 8, 1999.

**Delivered:** through FY17 (planned).

**IOC:** September 2003.

**Production:** 2,853, plus 1,426 JASSM-ER (planned).

**Contractor:** Lockheed Martin; Raytheon; Honeywell.

**Guidance:** INS, GPS, and IIR terminal seeker.

**Power Plant:** Teledyne Continental Motors.

**Dimensions:** length 14 ft.

**Weight:** 2,250 lb.

**Performance:** 1,000-lb class penetrator and blast-fragmentation warheads; standoff range greater than 200 miles.

#### COMMENTARY

JASSM is a next generation missile that enables Air Force and Navy fighters and bombers to destroy the enemy's war-sustaining capabilities from outside the ranges of enemy air defenses. This autonomous precision strike weapon has a range greater than 200 miles and can attack both fixed and relocatable targets, ranging from nonhardened above ground to moderately hardened buried targets. JASSM is equipped with INS/GPS guidance, an IIR terminal seeker, and a stealthy LO airframe. The system also offers low operational support costs. Testing has been accomplished for B-52H and F-16 threshold aircraft as well as B-1B and B-2 objective aircraft. The B-1B is the only aircraft capable of redirecting JASSM in flight. Integration planning for the F/A-18E/F is ongoing. Other potential JASSM integration efforts include the F-15E, F-117, and P-3C aircraft. An extended-range version (**JASSM-ER**), with a range of more than 500 miles, began development in FY03 and is scheduled to enter production in 2006.

#### AIM-7 Sparrow

**Brief:** A supersonic, medium-range, semiactive radar-guided air-to-air missile with all-weather, all-altitude, and all-aspect offensive capability and a high-explosive warhead, carried by fighter aircraft.

**Function:** Air-to-air guided missile.

**First Flight:** December 1983 (AIM-7M).

**Delivered:** from 1956.



**AIM-9 Sidewinder** (SMSgt. David H. Lipp)

**IOC:** April 1976 (AIM-7F).

**Production:** sustainment phase.

**Contractor:** Hughes and General Dynamics (now Raytheon).

**Power Plant:** Hercules Mk 58 Mod 0 4.5 sec boost-11 sec sustain rocket motor.

**Guidance:** AIM-7M: monopulse semiactive radar.

**Warhead:** high-explosive, blast fragmentation, weighing 86 lb.

**Dimensions:** length 12 ft, body diameter 8 in, wingspan 3.3 ft.

**Weight:** launch weight 504 lb.

**Performance** (estimated): max speed more than 2,660 mph (Mach 3.5), range more than 34 miles.

#### COMMENTARY

**Early versions.** Production of Sparrow has been under way for more than 40 years. Approximately 34,000 early models (AIM-7A/B/C/D/E) were produced. Compared to the earlier versions, the advanced solid-state AIM-7F, introduced into USAF service in 1976, had a larger motor, Doppler guidance, improved ECM, and better capability over both medium and "dogfight" ranges. USAF produced approximately 5,000, but none are now in USAF service.

**AIM-7M.** A joint Navy-USAF project aimed at producing a monopulse version of Sparrow at reduced cost and with improved performance in the ECM and look-down clutter regions. It began operational service in FY83. This version provides all-weather, all-altitude, all-aspect capability and equips USAF F-15s and F-16s (ADF) and Navy F-14s and F-18s.

**AIM-7P.** Block 1 retrofit to AIM-7M guidance and control sections (GCSs), providing low-altitude guidance and fuzing capability. Block 2 provides new-build for AIM-7P GCSs.

#### AIM-9 Sidewinder

**Brief:** A supersonic, short-range, IR-guided air-to-air missile carried by fighter aircraft, having a high-explosive warhead.

**Function:** Air-to-air missile.

**First Flight:** September 1953.

**Delivered:** 1957-present. First production AIM-9X delivered May 1, 2002.

**IOC:** circa 1983 (AIM-9M).

**Production:** sustainment phase (AIM-9M); LRIP from November 2000 (AIM-9X).

**Contractor:** Raytheon; Loral.

**Power Plant:** Thiokol Mk 36 Mod 11 solid-propellant rocket motor.

**Guidance:** solid-state IR homing guidance.

**Warhead:** high-explosive, weighing 20.8 lb.

**Dimensions:** length 9.4 ft, body diameter 5 in, finspan 2.1 ft.

**Weight:** launch weight 190 lb.

**Performance:** max speed Mach 2+, range 10+ miles.

#### COMMENTARY

**Early versions.** AIM-9A was the prototype version. The AIM-9B, initial production version, entered the inventory in 1957 and was effective only at close range during day. These shortcomings were eliminated on subsequent AIM-9E/H/J/P versions. The third generation Sidewinder, AIM-9L, added a more powerful solid-propellant rocket motor as well as tracking maneuvering ability. Production and delivery began in 1976; production ended in 1981.

**AIM-9M.** A joint Navy-USAF project aimed at producing an improved version of AIM-9L with all-altitude, all-aspect, launch-and-leave intercept capability. Can equip: A-10, F-14, F-15, F-16, F-16 ADF, and F-18 aircraft. This version has increased infrared countermeasures (IRCCM) capability, improved background discrimination, and a reduced-smoke rocket motor. First flight of prototype was in February 1978. Full production began in FY81.

**AIM-9M-9.** A modification to improve IRCCM capability of early missiles. Complete.

**AIM-9X.** Deriving from a jointly funded Navy-USAF project, the AIM-9X entered LRIP in November 2000. USAF's F-15-equipped 12th and 19th FS, part of the 3rd Wing at Elmendorf AFB, Alaska, became the first operational units to receive AIM-9Xs in November 2003. The first full-rate production contract was signed in November 2004. USAF plans to buy 5,097 missiles.

The AIM-9X incorporates advanced technologies such as a focal plane array imaging seeker, high off-boresight sensor (HOBS), and a highly maneuverable jet-vane control system. The missile utilizes the existing AIM-9M rocket motor, warhead, and fuze. It will be integrated with the JHMCS to maximize its HOBS capability. Intended carrier aircraft include the F-15, F-16, F-35, F/A-18, and F/A-22.

#### AIM-120 AMRAAM

**Brief:** A new generation supersonic, medium-range, active radar-guided air-to-air missile with a high-explosive warhead.

**Function:** Air-to-air guided missile.

**First Flight:** December 1984.

**Delivered:** 1988-July 2010 (planned).

**IOC:** September 1991.

**Production:** 10,917+ planned for USAF/USN.

**Contractor:** Raytheon.

**Power Plant:** Alliant boost-sustain solid-propellant rocket motor.

**Guidance:** inertial/command, inertial with active radar terminal homing.

**Warhead:** high-explosive directed fragmentation weighing 48 lb.

**Dimensions:** (A/B models) length 12 ft, body diameter 7 in, span of tail control fins 2.1 ft.

**Weight:** 335 lb.

**Performance:** cruising speed approx Mach 4, range more than 23 miles.

#### COMMENTARY

A joint project between the Navy and USAF, the AIM-120 Advanced Medium-Range Air-to-Air Missile (AMRAAM) is a replacement for the AIM-7 Sparrow. The AIM-120 equips F-15, F-16, F/A-18, F/A-22, and F-35 fighters. Inertial and command inertial guidance and active radar terminal homing provide launch-and-



**AIM-120 AMRAAM** (SMSgt. Chris Drudge)

maneuver capability. Significant improvements in operational effectiveness over the AIM-7 include increased average velocity, reduced miss distance, improved fuzing, increased warhead lethality, multiple target engagement capability, improved clutter rejection in low-altitude environments, enhanced electronic protection capability, increased maximum launch range, a reduced-smoke motor, and improved maintenance and handling.

**AIM-120A** was the first production version, delivered by Hughes in 1988 to the 33rd TFW at Eglin AFB, Fla.

**AIM-120B/C/D** are upgraded, reprogrammable variants of the AIM-120. The AIM-120C currently in production has smaller, clipped control surfaces to provide for internal carriage capability in the F/A-22 and F-35, with HOBBS launch capability. The latest development effort (AMRAAM Phase 4) adds GPS to improve navigational accuracy and enhanced data link capabilities in the AIM-120D version, due to enter production in 2006.

#### **CBU-87/103/113 Combined Effects Munition**

**Brief:** The CBU-87 CEM is an area cluster munition effective against light armor, materiel, and personnel and used by USAF and Navy fighters and bombers for interdiction.

**Function:** Area cluster munition.

**Production:** sustainment phase.

**Contractor:** Aerojet General; Honeywell; Alliant Tech.

**Guidance:** none (CBU-87).

**Dimensions:** length 7.7 ft; diameter 1.3 ft.

**Weight:** 949 lb.

**Performance:** dispenses 202 BLU-97 combined effects bomblets over an area roughly 800 ft by 400 ft.

#### **COMMENTARY**

The CBU-87 Combined Effects Munition dispenses 202 BLU-97 shaped charge antipersonnel/antimateriel fragmentary/incendiary bomblets over the target in a rectangular pattern. It is currently delivered by USAF and Navy aircraft as an unguided gravity weapon. Density and size of the area covered depends on release parameters and spin rates.

**CBU-103.** USAF is retrofitting a portion of its inventory of unguided CBU-87 CEMs with the Wind-Corrected Munitions Dispenser (WCMD) tail kit. The WCMD improves the munitions delivery accuracy when released from medium to high altitude.

**CBU-113.** USAF plans to retrofit a portion of its inventory of unguided CBU-87 CEMs with a WCMD-ER wing and tail kit. The WCMD-ER provides increased accuracy and standoff capability from outside point defense ranges.

#### **CBU-89/104 Gator**

**Brief:** The CBU-89 Gator is an anti-armor/antipersonnel mine dispenser used by USAF and Navy fighters and bombers for interdiction.

**Function:** Scatterable mines.

**Production:** sustainment phase.

**Contractor:** Honeywell; Aerojet General; Olan; Alliant Tech.

**Guidance:** none (CBU-89).

**Dimensions:** length 7.7 ft; diameter 1.3 ft.

**Weight:** 705 lb.

**Performance:** dispenses 72 BLU-91 anti-armor and 22 BLU-92 antipersonnel mines.

#### **COMMENTARY**

The CBU-89 Gator dispenser holds 94 mines, of which 72 are antitank and 22 are antipersonnel. The mines are dispersed over the target in a circular pattern. The antitank mines, which can be fuzed for three different time delay settings, have a magnetic influence fuze to sense armor.

**CBU-104.** USAF is retrofitting a portion of its inventory of Gators with the Wind-Corrected Munitions Dispenser (WCMD) tail kit, which improves the munitions delivery accuracy when released from medium to high altitude.

#### **CBU-97/105/115 Sensor Fuzed Weapon**

**Brief:** The CBU-97 SFW is an anti-armor cluster munition used by fighters and bombers for multiple kills per pass against moving and stationary land combat vehicles.

**Function:** Wide-area cluster munition.

**First Flight:** circa 1990.

**Delivered:** 1994-2007 (planned).

**IOC:** 1997.

**Production:** 3,937 (planned).

**Contractor:** Textron Systems.

**Guidance:** IR sensors in each warhead search for targets, then detonate over them.

**Dimensions:** length 7.7 ft; diameter 1.3 ft.

**Weight:** 920 lb.

**Performance:** delivers 40 lethal projectiles over an area of about 500 ft by 1,200 ft.

#### **COMMENTARY**

The **CBU-97** Sensor Fuzed Weapon (SFW) comprises an SUU-66/B tactical munitions dispenser with an FZU-39 fuze and a payload of 10 BLU-108 submunitions. Each tactical munitions dispenser contains 10

BLU-108 submunitions, and each submunition contains four "sneet" projectiles that, upon being thrown out, seek out their target and deliver an explosively formed penetrator. Each SFW can deliver a total of 40 lethal projectiles. The sneet IR sensors can detect a vehicle's IR signature; if no target is detected, the warhead detonates after a preset time. The SFW's primary targets are massed tanks, armored personnel carriers, and self-propelled targets. It also provides direct attack capability and interdiction against C2 centers.

The CBU-97 SFW is delivered as an unguided gravity weapon from the A-10, B-1, B-2, B-52H, F-15E, and F-16. The initial baseline SFW systems contained the BLU-108/B and BLU-108A/B submunition. A preplanned product improvement SFW variant P31 submunition, the BLU-108B/B, is in full-scale production, incorporating improvements such as an active laser sensor, multimission warhead, and increased footprint.

**CBU-105.** Designation of an unguided CBU-97 equipped with a Wind-Corrected Munitions Dispenser (WCMD) tail kit. The CBU-105 can be accurately delivered from high altitude and in adverse weather from the B-1, B-52H, F-15E, and F-16. Combat debut for the CBU-105 occurred April 2003, during Iraqi Freedom, from a B-52H.

**CBU-115.** USAF plans to install WCMD-ER wing and tail kits on SFW P31 weapons beginning FY06. The WCMD-ER provides increased accuracy and standoff capability from outside point defense ranges.

#### **CBU-107 Passive Attack Weapon**

**Brief:** The CBU-107 Passive Attack Weapon (PAW) provides the capability to attack non-hardened surface targets, with a minimum of collateral and environmental damage.

**Function:** Wide-area cluster munition.

**First Flight:** 2002.

**Delivered:** 2002-03.

**IOC:** December 2002.

**Production:** not available, but completed March 2003.

**Contractor:** General Dynamics (kinetic energy penetrator payload and canister); Lockheed Martin (WCMD); Textron (tactical munition dispenser kit).

**Guidance:** via WCMD.

**Dimensions:** length 7.7 ft; diameter 1.3 ft.

**Weight:** 1,000 lb.

**Performance:** delivers a high-speed volley of 3,000+ metal "arrows" projected from a single canister; three types of projectiles: 350 x 15 in-long rods, 1,000 x 7 in-long rods, and 2,400 small-nail size.

#### **COMMENTARY**

The CBU-107 Passive Attack Weapon (PAW) was developed from September 2002 to provide USAF aircraft with a new weapon that destroys targets with kinetic energy rods rather than explosives, thereby minimizing collateral and environmental damage. Following release from an aircraft, the WCMD-equipped weapon glides toward its target. Before impact, the inner chamber containing the rods begins to rotate and the "arrows" are ejected in rapid succession by centrifugal force, penetrating a target within a 200-ft radius. Two CBU-107s were used during Iraqi Freedom. CBU-107s are intended for use on F-16, F-15E, and B-52 aircraft.

#### **GBU-10 Paveway II**

**Brief:** An unpowered laser guided bomb (LGB) used to destroy high-value enemy targets from short standoff distances.

**Function:** Air-to-surface guided munition.

**First Flight:** early 1970s.

**Delivered:** from 1976.

**IOC:** 1976.

**Production:** 10,000; continuing.

**Contractor:** Lockheed Martin; Raytheon.

**Guidance:** semiactive laser.

**Warhead:** GBU-10C/D/E/F: Mk 84 bomb (2,000-lb unitary); GBU-10G/H/J: BLU-109.

**Dimensions:** length GBU-10C/D/E/F: 14.1 ft; GBU-10G/H/J: 14 ft, body diameter GBU-10C/D/E/F: 1.5 ft; GBU-10G/H/J: 1.2 ft, wingspan 5.5 ft.

**Weight:** 1,985 lb.

**Performance:** circular error probable (CEP) 29.7 ft; range 9.2 miles.

#### **COMMENTARY**

Folding-wing Paveway II weapons are improved versions of the earlier fixed-wing Paveway I. The GBU-10 is used primarily for precision bombing against non-hardened targets but is capable of greater penetration than previous version. It can operate in cloud ceilings down to 2,500 ft. GBU-10 platforms include A-10, B-52, F-15E, F-16, and F-117 aircraft.

#### **GBU-12 Paveway II**

**Brief:** An unpowered LGB used to destroy high-value enemy targets from short standoff distances.

**Function:** Air-to-surface guided munition.

**First Flight:** early 1970s.

**IOC:** 1976.

**Production:** about 30,000; continuing.

**Contractor:** Lockheed Martin; Raytheon.

**Guidance:** semiactive laser.

**Warhead:** Mk 82 (500 lb) blast/fragmentation bomb.

**Dimensions:** length 10.9 ft, body diameter 10.7 in, wingspan 4.4 ft.

**Weight:** 603 lb.

**Performance:** CEP 29.7 ft; range about 6 miles.

#### **COMMENTARY**

Folding-wing Paveway II weapons are improved versions of the earlier fixed-wing Paveway I. The LGB is used primarily to strike fixed armor. It can operate in cloud ceilings down to 2,500 ft. GBU-12 platforms include A-10, B-52, F-15E, F-16, and F-117 aircraft.

#### **GBU-15**

**Brief:** An unpowered bomb carried by the F-15E and used to destroy high-value enemy targets from short standoff distances.

**Function:** Air-to-surface guided munition.

**First Flight:** 1975.

**Delivered:** 1983-complete.

**IOC:** 1983.

**Production:** more than 2,000.

**Contractor:** Boeing; Raytheon.

**Guidance:** TV or IIR seeker.

**Warhead:** Mk 84 bomb (2,000-lb unitary) or BLU-109.

**Dimensions:** length 12.8 ft, body diameter 1.5 ft, wingspan 4.9 ft.

**Weight:** 2,500 lb.

**Performance:** cruising speed subsonic; range about 17 miles; CEP about 10 ft.

#### **COMMENTARY**

GBU-15 is an air-launched, cruciform-wing glide bomb fitted with a guidance system designed to give it pinpoint accuracy from low or medium altitudes. It also has a standoff capability. Development began in 1974, based on experience gained in Vietnam with the earlier Paveway Strike GBU-8 modular weapon program. The GBU-15 is intended for tactical use to suppress enemy defenses and to destroy heavily defended targets. The target-detecting device is carried on the front of the warhead. The control module, with autopilot and data link module, attaches to the rear.

The weapon has two modes of attack. In direct attack, the weapon is locked on to the target before launch and flies a near-line of sight profile to impact. In the indirect mode, the seeker can be locked on to the target after launch, or the operator can fly the weapon manually to impact, using guidance updates provided through the data link. A "buddy" system may be operated whereby the weapon is launched from one aircraft and controlled by another. The GBU-15 is deployed with the F-15E.

**GBU-15(V)1/B.** A TV-guided variant, qualified for operational service in 1983 (production complete).

**GBU-15(V)2/B.** IIR version entered service in 1987.

**GBU-15-I.** Combines accuracy of GBU-15 with the penetration capability of the improved 2,000-lb BLU-109/B penetrator bomb.

**EGBU-15.** GPS-guided variant, allowing pilot to select either TV, IR, or GPS guidance over the target, depending on weather and/or threat conditions. USAF had 100 initially produced for Allied Force, with field-level upgrade of over 1,200 existing GBU-15s.

#### **GBU-16 Paveway II**

**Brief:** An unpowered LGB used to destroy high-value enemy targets from short standoff distances.

**Function:** Air-to-surface glide munition.

**First Flight:** early 1970s.

**IOC:** 1976.

**Production:** not available.

**Contractor:** Lockheed Martin; Raytheon.

**Guidance:** semiactive laser.

**Warhead:** Mk 83 (1,000 lb) bomb.

**Dimensions:** length 12.1 ft, body diameter 1.2 ft, wingspan 5.5 ft.

**Weight:** approx 1,000 lb.

**Performance:** CEP about 29 ft; range 9.2 miles.

#### **COMMENTARY**

Folding-wing Paveway II weapons are improved versions of the earlier fixed-wing Paveway I. The GBU-16 LGB is used primarily to strike fixed armor. Its platforms include A-10, F-15E, and F-16 aircraft.

#### **GBU-24 Paveway III**

**Brief:** A precise air-to-ground low-level LGB (LLLGB) equipped with an advanced guidance kit.

**Function:** Air-to-surface penetrating glide bomb.

**First Flight:** GBU-24A/B (USAF) in service May 1985; GBU-24B/B (Navy) June 1992.

**Delivered:** from 1986.

**IOC:** 1986.

**Production:** USAF 14,000; Navy 12,000.

**Contractor:** Raytheon.

**Guidance:** semiactive laser.

**Warhead:** BLU-109.

**Dimensions:** length 14.2 ft.  
**Weight:** 2,350 lb.  
**Performance:** range more than 11.5 miles.

**COMMENTARY**

**GBU-24A/B.** An air-to-ground weapon equipped with the third generation Paveway III guidance kit, integrated with a BLU-109 penetrating warhead. The kit consists of an advanced guidance section and high-lift airframe. It is extremely precise and highly effective against a broad range of high-value hard targets. The system can be employed from low, medium, and high altitudes, providing operational flexibility through the use of an adaptive digital autopilot and large field-of-regard, highly sensitive scanning seeker. The GBU-24A/B was highly successful during Desert Storm.

The GBU-24 adapts to conditions of release, flies an appropriate midcourse, and provides trajectory shaping for enhanced warhead effectiveness. The weapon is deployed on USAF F-15E, F-16, and F-117 and Navy F-14 and F/A-18.

**GBU-27**

**Brief:** A precise air-to-ground penetrating LGB equipped with an advanced guidance kit.

**Function:** Air-to-surface guided glide bomb.

**First Flight:** not available.

**Delivered:** from 1988.

**IOC:** 1988 (unconfirmed).

**Production:** approx 3,000.

**Contractor:** Raytheon.

**Guidance:** semiactive laser.

**Dimensions:** span 5.5 ft, length 13.9 ft.

**Weight:** 2,170 lb.

**Performance:** range more than 11.5 miles.

**COMMENTARY**

To meet the unique requirements of the F-117A, the GBU-24A/B was adapted to GBU-27 standard, incorporating specific guidance features to accomplish this mission. The GBU-27 is extremely precise and was used to great effect in Desert Storm.

**EGBU-27.** Integrates GPS/INS guidance into the existing GBU-27 laser seeker to provide adverse weather capability and improved target location. Entered production in FY98. First operational use was in Iraqi Freedom.

**GBU-28**

**Brief:** A large 5,000-lb class air-to-ground penetrating LGB equipped with an advanced laser guidance kit, used for striking and destroying hard underground targets.

**Function:** Air-to-surface guided glide bomb.

**First Flight:** February 1991.

**Delivered:** circa 1991.

**IOC:** 1991.

**Production:** approx 500.

**Contractor:** Raytheon.

**Guidance:** laser.

**Dimensions:** length 19.2 ft, diameter 1.2 ft.

**Weight:** 4,676 lb.

**Performance:** range more than 5.75 miles.

**COMMENTARY**

Under USAF's rapid-response program, the GBU-28 bunker-busting LGB was developed for Desert Storm for use against deeply buried, hardened C2 facilities. Four of the GBU-28 weapons were used during the war: two for testing and two by F-111Fs against a bunker complex Feb. 27, 1991. Guidance is by a modified GBU-27 system.

**EGBU-28.** Integrates GPS/INS guidance into the existing GBU-28 guidance control unit to provide adverse weather capability and improved target location. Entered production in FY99.

**GBU-31/32/38 Joint Direct Attack Munition**

**Brief:** A joint USAF-Navy INS/GPS-guided weapon, carried by fighters and bombers, that provides highly accurate, autonomous, all-weather conventional bombing capability.

**Function:** Air-to-surface guided bomb.

**First Flight:** Oct. 22, 1996.

**Delivered:** 1998-2009 (planned).

**IOC:** 1998.

**Production:** 240,882 (planned).

**Contractor:** Boeing; Textron; Honeywell.

**Guidance:** INS/GPS.

**Dimensions:** Mk 84 with JDAM 12.8 ft; BLU-109 with JDAM 12.4 ft; Mk 83 with JDAM 10 ft.

**Weight:** Mk 84 2,036/2,056 lb (USAF/USN); BLU-109 2,115/2,135 lb; Mk 83 1,013/1,028 lb.

**Performance:** range up to 17 miles, CEP with GPS 42.9 ft; CEP with INS only 99 ft.

**COMMENTARY**

JDAM upgrades the existing inventory of general-purpose bombs by integrating them with a GPS/INS guidance kit to provide accurate all-weather attack from medium/high altitudes. While still aboard the launch aircraft, JDAM is passed target information through the aircraft's avionics system. Once released,

the inertial guidance kit takes over and, with periodic GPS updates to the INS, guides the weapon to its target. JDAM is intended for AV-8B, B-1, B-2, B-52, F-14, F-15E, F-16, F-35, F-117A, F/A-18C/D/E/F, and F/A-22 aircraft.

**GBU-31.** Variant that adds an INS/GPS guidance kit to the 2,000-lb general-purpose Mk 84 bomb or the 2,000-lb BLU-109 penetrator. First used in combat March 24, 1999.

**GBU-32.** Variant that adds an INS/GPS guidance kit to the 1,000-lb general-purpose Mk 83 bomb or the 1,000-lb BLU-110 penetrator.

**GBU-38.** Variant that adds an INS/GPS guidance kit to the 500-lb general-purpose Mk 82 bomb. First production deliveries were in 2004 for the B-2.

Planned upgrades include an anti-spoofing GPS receiver and low-cost antijam antenna.

**Massive Ordnance Air Blast (MOAB) Bomb**

**Brief:** A massive precision guided munition (PGM) designed to be dropped by B-1, B-2, or B-52 bombers.

**Function:** Massive bomb.

**Guidance:** GPS/INS.

**Warhead:** 18,000 lb, high explosive.

**Dimensions:** length 30 ft, diameter 3.3 ft.

**Weight:** 21,500 lb.

**COMMENTARY**

On March 11, 2003, USAF live-tested the largest PGM developed to date. Unlike the earlier unguided "Daisy Cutter" bomb, the MOAB does not require a parachute. Testing continues.

**Small Diameter Bomb**

**Brief:** Extended range all-weather, day/night 250-lb class near-precision guided munition. Provides increased loadout to achieve multiple kills per sortie and decreases collateral damage.

**Function:** Air-to-surface guided munition.

**First Flight:** May 23, 2003 (guided).

**Delivered:** from FY06 (planned).

**IOC:** FY06.

**Production:** 24,000 munitions and 2,000 carriages (planned).

**Contractor:** Boeing.

**Guidance:** GPS/INS augmented by Differential GPS.

**Dimensions:** length 70.8 in (munition); 126.4 in (carriage); 143.1 in (carriage with four munitions).

**Weight:** 285 lb (munition); 320 lb (carriage); 1,460 lb (carriage with four munitions).

**Performance:** near-precision capability at standoff range up to 46 miles.

**COMMENTARY**

The Small Diameter Bomb (SDB) system employs a BRU-61/A smart carriage capable of carrying four 250-lb class GBU-39/B near-precision guided air-to-surface munitions. It is capable of destroying high-priority fixed and stationary relocatable targets from both fighters and bombers in internal bays or on external hardpoints. SDBs can be targeted and released against single or multiple targets. Target coordinates are loaded in the weapon prior to release either on the ground or in the air by aircrew. Once the weapon is released, it relies on GPS/INS augmented by Differential GPS to self-navigate to the impact point. SDB increases loadout, decreases collateral damage, and improves aircraft sortie generation times. Threshold aircraft for SDB is the F-15E. Objective aircraft include the A-10, B-1, B-2, B-52, F-16, F-35, F-117, F/A-22, J-UCAS, and MQ-9. Boeing was awarded the contract to develop the SDB in October 2003.

**Wind-Corrected Munitions Dispenser (WCMD)**

**Brief:** A tail kit fitted to CEM/Gator/SFW (CBU-87/

89/97) and CBU-107 PAW dispenser weapons. When dropped from high altitude, its inertial guidance system corrects for launch transients and wind effects to enhance accuracy.

**Function:** Guidance tail kit.

**First Flight:** February 1996.

**Delivered:** from 2000.

**IOC:** FY00.

**Production:** 27,700 (planned), with 19,730 delivered as of Oct. 29, 2004.

**Contractor:** Lockheed Martin.

**Dimensions:** length 1.4 ft, diameter 1.3 ft.

**Weight:** 100 lb.

**Performance:** range about eight miles.

**COMMENTARY**

USAF is modifying standard SUU-64/65/66 tactical munition dispensers with guidance kits to compensate for wind drift on downward flight from high altitudes. The combat-proven WCMD kits include an INS guidance unit, movable tail fins that pop out in flight, and a signal processor. The kits when fitted on CBU-87/89/97 inventory cluster weapons are designated: CEM (CBU-103), Gator (CBU-104), SFW (CBU-105), and PAW (CBU-107). Successful flight testing began in February 1996; WCMDs are now operational on B-1, B-52, F-15E, and F-16 aircraft. Objective aircraft are A-10, B-2, F-35, and F-117.

**Wind-Corrected Munitions Dispenser-Extended Range (WCMD-ER)**

**Brief:** A WCMD tail and wing kit fitted to CEM/SFW (CBU-87/97) dispenser weapons. Augments WCMD baseline capability by adding GPS guidance and a wing kit for increased accuracy and standoff capability from outside point defense ranges.

**Function:** GPS guidance tail and wing kit.

**First Flight:** April 2005 (planned).

**Delivered:** 2006 (planned).

**IOC:** FY06.

**Production:** 7,500.

**Contractor:** Lockheed Martin.

**Dimensions:** wing kit: length (wings stowed) 7 ft, width 1.3 ft, height 5 in.

**Weight:** less than 200 lb.

**Performance:** standoff range about 40.25 miles.

**COMMENTARY**

USAF is developing a wing kit and incorporating GPS guidance into the WCMD tail kit to provide highly accurate delivery and standoff capability from outside point defense ranges for CBU-87/97 dispenser weapons. However, acquisition is subject to the current budget review.

## Satellite Systems

**Advanced EHF (AEHF)**

**Brief:** Joint service satellite communications system that provides global, secure, protected, and jam-resistant communications for high priority air, ground, and sea assets.

**Function:** near-worldwide, secure, survivable satellite communications.

**Operator:** AFSPC.

**First Launch:** April 2008 (planned).

**IOC:** 2010 (planned).

**Constellation:** three satellites.

**Design Life:** 14 years.

**Launch Vehicle:** Evolved Expendable Launch Vehicle (EELV).

**Unit Location:** Schriever AFB, Colo.



**GBU-31 Joint Direct Attack Munition** (MSgt. Glenn Wilkewitz)

**Orbit Altitude:** 22,000+ miles (geosynchronous).  
**Contractor:** Lockheed Martin, Northrop Grumman team for system development and demonstration.  
**Dimensions:** length 32 ft (across payload axis), width 75.8 ft (across solar array axis).

**Weight:** approx 13,500 lb at launch, 9,000 lb on orbit.  
**Performance:** five times the capability of the Milstar Block II satellite.

#### COMMENTARY

The Advanced Extremely High Frequency (AEHF) system comprises three satellites in geosynchronous orbit that provide at least five times the capacity of the 1990s-era Milstar Block II satellites. Advanced EHF allows the President, Secretary of Defense, and combat forces to control their tactical and strategic forces at all levels of conflict through general nuclear war and supports the attainment of information superiority. AEHF will provide connectivity across the spectrum of mission areas, including air, land, and naval warfare; special operations; strategic nuclear operations; strategic defense; theater missile defense; and space operations and intelligence.

#### Defense Meteorological Satellite Program

**Brief:** Satellites that collect air, land, sea, and space environmental data to support worldwide strategic and tactical military operations.

**Function:** Environmental monitoring satellite.

**Operator:** National Polar-orbiting Operational Environmental Satellite System (NPOESS) program office.  
**First Launch:** May 23, 1962.

**IOC:** classified but in use during Vietnam War.

**Constellation/on-orbit:** two.

**Design Life:** 48 months (Block 5D-2); 54 months (Block 5D-3).

**Launch Vehicle:** Titan II.

**Unit Location:** Suitland, Md.

**Orbit Altitude:** approx 575 miles.

**Contractor:** Lockheed Martin; Northrop Grumman.  
**Power Plant:** solar arrays generating 1,200-1,300 watts.

**Dimensions:** length 20.2 ft (with array deployed), width 4 ft.

**Weight:** 2,545 lb (including 592-lb sensor).

**Performance:** DMSP satellites orbit Earth at about 500 miles altitude and scan an area 1,800 miles wide. Each system covers the Earth in about 12 hr.

#### COMMENTARY

For the last 40 years, the DMSP constellation has provided high-quality, timely weather information to strategic and tactical warfighters worldwide. In addition, DMSP satellites provide critical land, sea, and space environment data required by US forces across the globe. The DMSP constellation will be replaced by the tri-agency NPOESS late in this decade.

**Block 5D-2.** Two operational DMSP Block 5D-2 satellites survey the entire Earth four times a day. The last of the Block 5D-2 satellites was launched in December 1999. The Block 5D-2 spacecraft "sees" visible and IR cloud-cover imagery to analyze cloud patterns with the operational linescan system. Secondary instruments include microwave imagers and sounders and a suite of space environment sensors.

**Block 5D-3.** DMSP F16, the first Block 5D-3 satellite, was launched successfully on Oct. 18, 2003. (DMSP F15, with a 5D-3 satellite bus but 5D-2 sensors, was launched Dec. 12, 1999, and is credited as the first 5D-3 launch.) Block 5D-3 satellites have an improved spacecraft bus and sensors that provide for longer and more capable missions. Successful flyout of the DMSP Block 5D-3 satellites will help ensure a seamless transition to the NPOESS program for DOD.

#### Defense Satellite Communications System

**Brief:** A spacecraft traveling in geosynchronous orbit used to transmit SHF high-priority C2 communications.

**Function:** Communications satellite.

**Operator:** AFSPC.

**First Launch:** 1971 (DSCS II); 1982 (DSCS III); 2000 (DSCS III/SLEP).

**IOC:** Dec. 13, 1978 (DSCS II).

**Constellation:** five (III).

**Design Life:** 10 yr (III).

**Launch Vehicle:** Atlas II.

**Unit Location:** Schriever AFB, Colo.

**Orbit Altitude:** 22,000+ miles in geosynchronous orbit.

**Contractor:** Lockheed Martin.

**Power Plant:** solar arrays generating 1,269 watts, decreasing to 980 watts after 10 yr; 1,500 watts (SLEP).  
**Dimensions:** rectangular body 6 x 6 x 7 ft; 38-ft span with solar arrays deployed.

**Weight:** 2,580 lb; 2,716 lb (SLEP).

**Performance:** DSCS satellites orbit Earth at about 22,000 miles altitude and employ six SHF transponder channels for secure voice and high-rate data communications.

#### COMMENTARY

DSCS III satellites support globally distributed DOD

and national security users. The final four of 14 satellites received SLEP modifications, providing substantial capacity improvements through higher power amplifiers, more sensitive receivers, and additional antenna connectivity options. The DSCS communications payload includes six independent super high frequency (SHF) transponder channels that cover a 500 MHz bandwidth. Three receive and five transmit antennas provide selectable options for Earth coverage, area coverage, and/or spot beam coverage. A special-purpose single channel transponder is also on board.

The DSCS III system provides the capabilities needed for effective implementation of worldwide military communications. It can adapt to dynamic operating conditions and perform under stressed environments, providing nuclear hardened, antjam, high data rate, long-haul communications to military users globally. The final DSCS III satellite was launched in August 2003. The modernization of satellite communications will continue with the deployment of the Wideband Gap-filler System.

#### Defense Support Program

**Brief:** An early warning spacecraft that travels in geosynchronous orbit and provides alert of possible ballistic missile attack on US forces or homeland.

**Function:** Strategic and tactical launch detection system.

**Operator:** AFSPC.

**First Launch:** November 1970.

**IOC:** circa 1972.

**Constellation:** classified.

**Design Life:** three yr.

**Launch Vehicle:** Titan IV inertial upper stage.

**Unit Location:** Peterson AFB, Colo.

**Orbit Altitude:** 22,000+ miles in geosynchronous orbit.

**Contractor:** TRW (now Northrop Grumman).

**Power Plant:** solar arrays generating 1,485 watts.  
**Dimensions:** diameter 22 ft, height 32.8 ft, with solar paddles deployed.

**Weight:** 5,000 lb (approx).

**Performance:** orbits at approx 22,000 miles altitude in geosynchronous orbit; uses IR sensors to sense heat from missile and booster plumes against Earth's background.

#### COMMENTARY

The incredibly flexible Defense Support Program (DSP) satellite system was used extensively in Desert Storm to detect theater missile launches against coalition forces. Though not designed to spot and track smaller missiles, the system was highly successful in detecting launches, enabling timely warnings of Iraqi Scud attacks. Using existing sensors and data collection sources, global data related to theatre missile warning was transmitted to the Attack and Launch Early Reporting to Theater (ALERT) and Shield systems then located at the National Test Facility (NTF) at Schriever AFB, Colo. The Space Based Infrared System (SBIRS) mission control station (MCS), located at Buckley AFB, Colo., became operational in December 2001 and now performs both the strategic and theater missile warning missions. ALERT was deactivated in September 2001, and Shield continues as a research and development effort that evaluates and demonstrates the potential benefits of using multiple data sources and novel techniques in support of missile warning.

DSP satellites are a key part of the North American and theater early warning systems, capable of detecting missile launches and nuclear detonations. Warning data are fed to NORAD and US Strategic Command early warning centers at Cheyenne Mountain AFS, Colo. Since the first launch, DSP satellites have provided an uninterrupted early warning capability to the US; 21 satellites have been launched to date. The final two DSPs launched in 2004-05. America's early warning capability will be modernized with the introduction of the new SBIRS to be phased in beginning in FY07.

#### Global Positioning System

**Brief:** A constellation of orbiting space vehicles that provides highly precise and reliable navigation data, 24 hours a day, to military and civilian users around the world. Signals permit calculation of location within less than 100 ft.

**Function:** Worldwide navigation satellite.

**Operator:** AFSPC.

**First Launch:** Feb. 22, 1978.

**IOC:** Dec. 9, 1993.

**Constellation:** 28.

**Design Life:** six yr (II/IIA); 7.5 yr (IIR).

**Launch Vehicle:** Delta II.

**Unit Location:** Schriever AFB, Colo.

**Orbit Altitude:** 12,636 miles (IIA); 12,532 miles (IIR).  
**Contractor:** Boeing (II, IIA, IIF); Lockheed Martin (IIR, IIR-M).

**Power Plant:** solar arrays generating 700 watts (II/IIA); up to 2,900 watts (IIF).

**Dimensions:** IIR: body 5 x 6.3 x 6.25 ft, span incl solar arrays 38 ft.

**Weight:** 2,370 lb (IIR) on orbit.

**Performance:** GPS satellites orbit the Earth every 12 hr, emitting continuous navigation signals. The signals are so accurate that time can be figured to within one-millionth of a second, velocity within a fraction of a mile per hr, and location to within a few ft. Receivers are used in aircraft, ships, and land vehicles and can also be handheld.

#### COMMENTARY

Worldwide military operations, such as precision bombing, CSAR, mapping, and rendezvous, are successful in part due to the 24-hour, worldwide navigation service provided by the Global Positioning System (GPS) navigation satellite constellation. Accurate three-dimensional (latitude, longitude, and altitude) position, velocity, and precise time are provided continuously in real time to support an unlimited number of users around the globe, both civilian and military. Concern over potential enemy denial of GPS is being addressed under GPS modernization efforts. The modified Block IIR-M GPS satellites, launched 2004, have two jam-resistant channels for military-only use. Block IIF satellites with extended design life, faster processors, and a new civil signal on a third frequency launches 2006. Future generation GPS satellites are slated for launch 2012.

#### Milstar Satellite Communications System

**Brief:** A satellite communications system that provides secure, jam-resistant worldwide C2 communications for tactical and strategic forces in all levels of conflict, linking command authorities to ground forces, ships, submarines, and aircraft.

**Function:** Communications satellite.

**Operator:** AFSPC.

**First Launch:** Feb. 7, 1994.

**IOC:** July 1997 (Milstar I).

**Constellation:** five.

**Design Life:** 10 yr.

**Launch Vehicle:** Titan IV/Centaur.

**Unit Location:** Schriever AFB, Colo.

**Orbit Altitude:** 22,300 miles.

**Contractor:** Lockheed Martin; Boeing; TRW (now Northrop Grumman).

**Power Plant:** solar arrays generating 8,000 watts.  
**Dimensions:** length 51 ft, width 116 ft with full solar array extension.

**Weight:** 10,000 lb.

**Performance:** constellation consists of three satellites in low-inclined geosynchronous orbit, providing worldwide coverage between 65° north and 65° south latitude.

#### COMMENTARY

The backbone of strategic-tactical communications, Milstar is a joint service communications system that provides secure, jam-resistant EHF communications. Worldwide operations are made possible by this 24-hour, all-weather capability, ready to support any deployment at a moment's notice. The Milstar inventory was fully deployed in 2003, and modernization of satellite communications will continue with the Advanced EHF (AEHF) constellation deployment.

#### Polar MILSATCOM

**Brief:** Payload on a classified satellite that provides secure, survivable communications, supporting peacetime, contingency, and wartime operations in the North Pole region, above 65° north latitude.

**Function:** Communications satellite.

**Operator:** USN.

**First Launch:** late 1997.

**IOC:** 1997.

**Constellation:** three.

**Design Life:** host satellite dependent.

**Launch Vehicle:** not available.

**Unit Location:** Schriever AFB, Colo.

**Orbit Altitude:** 25,300 miles.

**Contractor:** classified.

**Power Plant:** 410 watts consumed by payload (power from host solar array).

**Dimensions:** numerous items integrated throughout host.

**Weight:** 470 lb (payload).

#### COMMENTARY

Augmenting the Milstar constellation, the Polar MILSATCOM payload is a cost-effective means of providing secure communications for the northern polar region. Like Milstar, the system enables worldwide operations by linking strategic and tactical forces with secure, jam-resistant EHF communication links. Polars 2 and 3 launch dates are 2004 and 2006, respectively. A much-improved next generation polar system is planned for launch circa 2010.

#### Space Based Infrared System High

**Brief:** Advanced surveillance system for missile warning, missile defense, battlespace characterization, and technical intelligence. System includes satel-



lites in geosynchronous Earth orbit (GEO) and highly elliptical orbit.

**Function:** IR space surveillance.

**Operator:** AFSPC.

**First Launch:** (planned) High GEO: FY07.

**IOC:** TBD.

**Constellation:** High: four GEO sats, two highly elliptical orbit sensors.

**Design Life:** not available.

**Launch Vehicle:** Evolved Expendable Launch Vehicle (EELV) Heavy.

**Unit Location:** Buckley AFB, Colo.

**Orbit Altitude:** High at approx 22,300 miles.

**Contractor:** Lockheed Martin; Northrop Grumman.

**Power Plant:** solar array, 2,435 watts.

**Dimensions:** 6 x 7 x 17 ft.

**Weight:** 5,442 lb.

#### COMMENTARY

The follow-on to the DSP is the Space Based Infrared System (SBIRS) High, an integrated "system of systems" including satellites in GEO, sensors hosted on satellites in highly elliptical orbits, and ground assets.

SBIRS is being fielded incrementally. Increment 1 consolidated all DSP ground processing in one CONUS master control station at Buckley AFB, Colo. IOC was declared Dec. 18, 2001. Increment 2 will field the space and ground assets. SBIRS High is in the EMD phase led by a Lockheed Martin team. The system will integrate the Space Tracking and Surveillance System (STSS) capabilities as they become available.

#### Space Tracking and Surveillance System

**Brief:** Advanced surveillance system with IR and visible sensors for detecting and tracking ballistic missiles. STSS (formerly SBIRS Low) will have satellites in low Earth orbit (LEO) that work in concert with SBIRS High and other missile defense systems.

**Function:** Space surveillance.

**Operator:** AFSPC.

**First Launch:** FY06-07 (planned).

**IOC:** TBD.

**Constellation:** TBD (from nine up to 30 under consideration).

**Design Life:** not available.

**Launch Vehicle:** TBD.

**Unit Location:** TBD.

**Orbit Altitude:** 60-300 miles.

**Contractor:** Northrop Grumman (completion and launch of two R&D satellites); Raytheon.

**Power Plant:** TBD.

**Dimensions:** not available.

**Weight:** not available.

#### COMMENTARY

The Missile Defense Agency manages the Space Tracking and Surveillance System (STSS), which, in December 2002, replaced the program known as SBIRS Low. In April 2002, MDA ended the SBIRS Low program definition and risk reduction competition and named TRW (purchased by Northrop Grumman) as prime contractor for a redefined space-based sensor R&D element of MDA's integrated Ballistic Missile Defense System (BMDS). The initial STSS contract calls for completion and launch of two LEO satellites in FY06-07 under Block 2006. New technologies will be inserted into subsequent R&D satellites under Block 2008 and beyond, leading to an operational system.

#### Wideband Gap-filler System (WGS)

**Brief:** Satellites that provide wideband communications for deployed tactical forces (air, land, and sea).

**Function:** Worldwide satellite communications.

**Operator:** AFSPC.

**First Launch:** Dec. 31, 2005 (planned); two further launches planned within a year.

**IOC:** August 2007 (planned).

**Constellation:** three-five satellites.

**Design Life:** 14 years.

**Launch Vehicle:** EELV, Delta IV.

**Unit Location:** Schriever AFB, Colo.

**Orbit Altitude:** GEO.

**Contractor:** Boeing.

**Power Plant:** solar arrays generating 9,934 watts.

**Dimensions:** based on Boeing 702 Bus.

**Weight:** 13,200 lb at launch.

**Performance:** approx 12 times the capability of a DSCS satellite.

#### COMMENTARY

The WGS constellation is planned to bridge the gap between current DSCS and GBS systems and the next generation system. It will provide two-way services for national leaders, Diplomatic Telecommunications Service, Defense Information System Network, and all military ground fixed and mobile users. In addition, it will provide direct broadcast of digital multimedia, high-bandwidth imagery, and video information directly from global and theater sites to deployed warfighters. Primarily a commercial product, the satellites will have X-band (DSCS III-like), Ka-band broadcast (GBS Phase 2-like), two-way Ka-band services,

and cross-channelization between its X- and Ka-band services.

## Aerial Targets

#### BQM-34 Firebee

**Brief:** A jet-powered, variable speed, recoverable target drone.

**Function:** Aerial target.

**Operator:** ACC.

**First Flight:** 1951; 1958 (BQM-34A).

**Delivered:** from 1951.

**IOC:** circa 1951.

**Production:** 1,800+.

**Inventory:** 33.

**Unit Location:** Tyndall AFB, Fla.

**Contractor:** Teledyne Ryan.

**Power Plant:** one General Electric J85-GE-100 turbojet, 2,850 lb thrust.

**Guidance and Control:** remote-control methods incl choice of radar, radio, active seeker, and automatic navigator developed by Teledyne Ryan; the current model of the BQM-34A is configured to accommodate the GRDCUS, which allows multiple targets to be flown simultaneously.

**Dimensions:** length 22.9 ft, body diameter 3.1 ft, span 12.9 ft.

**Weight:** launch weight 2,500 lb.

**Performance:** max level speed at 6,500 ft 690 mph, operating height range 10 ft to more than 60,000 ft, max range 796 miles, endurance (typical configuration) 30 min.

#### COMMENTARY

Current BQM-34As, with an upgraded General Electric J85-100 engine that provides a thrust-to-weight ratio of 1:1, offer higher climb rates and six-G maneuvering capability. A new microprocessor flight-control system provides a prelaunch and in-flight self-test capability. BQM-34s are used for research, development, test, and evaluation and the Weapon System Evaluation Program.

#### BQM-167 Skeeter

**Brief:** A jet-powered, variable speed, recoverable target drone.

**Function:** Aerial target.

**Operator:** ACC.

**First Flight:** Jan. 3, 2005.

**Production:** full-scale production began in 2004, with 350 Skeeters contracted over seven years.

**Unit Location:** Tyndall AFB, Fla.

**Contractor:** Composite Engineering Inc.

**Power Plant:** Microturbo Tri 60-5+ turbojet.

**Guidance and Control:** remote piloting methods.

**Dimensions:** length 20 ft, body diameter 2 ft, span 11 ft.

**Weight:** not available.

**Performance:** max level speed Mach 0.9 mph, operating height range 20,000-50,000 ft, endurance 3 hr.

#### COMMENTARY

BQM-167A will replace both the aging MQ-107 and BQM-34A as the Air Force's newest subscale aerial target. It features an increased load capability, higher speeds, G-loads, a digital architecture for avionics, and a composite airframe making it significantly lighter than the earlier platforms. Future development on this target will take it to supersonic speeds, internalize and miniaturize many countermeasures systems, and expand the flight envelope beyond any target system in the inventory today.

#### MQM-107 Streaker

**Brief:** A jet-powered, variable speed, recoverable target drone.

**Function:** Aerial target.

**Operator:** ACC.

**First Flight:** not available.

**Delivered:** from 1984 (B).

**IOC:** 1987.

**Production:** 70 (B); 221 (D); 78 (E).

**Unit Location:** Tyndall AFB, Fla.

**Contractor:** Raytheon (D model); Marconi (formerly Tracor) (E model).

**Power Plant:** initially on D model, one Teledyne CAE 373-8 engine, 950 lb thrust; MQM-107Ds delivered since 1989 have 950 lb thrust TRI 60-5 turbojets. Microturbo TRI 60-5 engine, 1,061 lb thrust or TCAE 373-8B (E model).

**Guidance and Control:** analog or digital, for both ground control and preprogrammed flight (D model); high-G autopilot provisions; digital autopilot and remote control by the Gulf Range Drone Control Upgrade System (GRDCUS), a multifunction C2 multilateration system (E model).

**Dimensions:** length 18.1 ft, body diameter 1.3 ft, span 9.8 ft.

**Weight:** max launch weight (excl booster) 1,460 lb.  
**Performance:** operating speed 207-630 mph, operating height 50-40,000 ft, endurance 2 hr 15 min.

#### COMMENTARY

MQM-107D. A third generation version of the MQM-107 Streaker, it is a recoverable, variable-speed target drone used for research, development, test, and evaluation and the Weapon System Evaluation Program.

MQM-107E. Improved performance follow-on to the MQM-107D. In operational service, it replaces the MQM-107D and expands the flight envelope.

MQM-107 Streakers are being replaced by the BQM-167 Skeeter.

#### QF-4

**Brief:** A converted, remotely piloted F-4 Phantom fighter used for full-scale training or testing.

**Function:** Aerial target.

**Operator:** ACC.

**First Flight:** August 1993.

**IOC:** not available.

**Unit Location:** Tyndall AFB, Fla. (detachment at Holloman AFB, N.M.)

**Contractor:** Marconi (formerly Tracor).

**Power Plant:** two General Electric J79-GE-17 turbojets, each with approx 17,000 lb thrust with afterburning.

**Guidance and Control:** remote-control methods incl the GRDCUS (Tyndall) and the Drone Formation and Control System (Holloman); will also accommodate the triservice Target Control System currently under development.

**Dimensions:** length 16 ft, height 6 ft, wingspan 38.4 ft.

**Weight:** mission operational weight 49,500 lb.

**Performance:** max speed Mach 2+, ceiling 55,000 ft, range (approx) 500 miles.

#### COMMENTARY

The QF-4 replaced the QF-106 Full-Scale Aerial Target (FSAT) in 1998 when the F-106 inventory was depleted. The QF-4 provides for a larger operational performance envelope (maneuvering) and greater payload capability compared with its predecessors.

More than 160 F-4 surplus aircraft have been converted to QF-4 FSATS since 1995. QF-4s are used for research, development, test, and evaluation and the Weapon System Evaluation Program. ■



BQM-167 Skeeter (MSgt. Michael Ammons)